

WEP 17-150 Quick RT (601078420) Angle grinder Cardboard box

Order no. 601078420
EAN 4007430314345



Representative picture



- Maximum productivity through strong power at a low weight
- Perfect ergonomics thanks to a slim grip area for maximum control and easily working overhead
- Metabo LongLife Motor with new cooling and carbon brush system for double the service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for disc change without tools at the push of a button
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical values

Parameters

| | |
|------------------------------|---------------|
| Amps | 14.6 AMPS |
| Grinding wheel Ø | 6 " |
| Output power | 1030 W |
| No-load speed | 9600 RPM |
| Revolutions at rated load | 9600 RPM |
| Torque | 39 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 5.6 lbs |
| Cable length | 8 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 8.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LWA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Inner support flange
M-Quick flange nut
Side handle Metabo VibraTech (MVT)