

RSEV 19-125 RT (603825750) Renovation grinders **Plastic Carry Case**

Order no. 603825750 EAN 4007430313669



Representative picture











- For effective spot sanding and removal of concrete, screed and coatings with diamond cup wheels
- Maximum productivity with low weight thanks to 1900 Watt Metabo Marathon-Motor
- High torque and overload capacity for demanding applications in continuous use
- Low weight, ideal for sanding walls and ceilings
- Perfect ergonomics thanks to a slim grip area for maximum control and easily working overhead
- Working close to edges thanks to integrated folding segment
- Optimum extraction results: Spring-mounted brush rim at the protective cover that adapts to any surface and segment height
- Front handle for safe and uniform guidance when polishing, adjustable without the need for tools
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly.
- Connection for dust extraction Ø 1-1/2"

www.metabo.com 1/2



Technical values		
Parameters		
Amps	15 AMPS	
Cup wheel Ø	5 "	
Torque	44 in-lbs	
No-load speed	3800 - 8200 RPM	
Rated input power	1900 W	
Output power	1240 W	
Revolutions at rated load	6800 RPM	
Spindle thread	5/8" - 11 UNC	
Weight (without power cable)	7.7 lbs	
Cable length	8 ft	
Vibration		
Surface grinding	6.94 m/s²	
Uncertainty of measurement K	1.5 m/s ²	
Noise emission		
Sound pressure level	92 dB(A)	
Sound power level (LwA)	103 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Bow type handle

Inner support flange

Nut with two holes

Replacement sealing brush

Suction adapter

Spanner wrench

Plastic carrying case

www.metabo.com 2 / 2