

Alpha Twincur Wheels

GQ PN	Description	Diameter	PSI	BAR	Belt Speed
900603	ALPHA TWINCUR, 4",100 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900604	ALPHA TWINCUR, 4", 200 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900605	ALPHA TWINCUR, 4", 500 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900606	ALPHA TWINCUR, 4",1000 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900607	ALPHA TWINCUR, 4" 2000 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900608	ALPHA TWINCUR, 4", 3000 GRIT, SNAIL LOCK	4"	13-26	1.0-2.0	30"
900609	ALP TWINCUR, 4", FINAL BUFF BLACK, SNL	4"	13-26	1.0-2.0	30"
900610	ALP TWINCUR, 4", FINAL BUFF WHITE, SNL	4"	13-26	1.0-2.0	30"

The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.