

Black Magic Combo Wheels					
GQ PN	Description	Diameter	PSI	BAR	Belt Speed
113968	BM COMBO 130MM SNL LCK RESIN P.1 100G	5"	29	2	18-28"
113969	BM COMBO 130MM SNL LCK RESIN P.2 200G	5"	29	2	18-28"
113970	BBM COMBO 130MM SNL LCK RESIN P.3 500G	5"	32	2.2	18-28"
113971	BM COMBO 130MM SNL LCK RESIN P.4 1000G	5"	35	2.4	18-28"
113972	BM COMBO 130MM SNL LCK RESIN P.5 2000G	5"	38	2.6	18-28"
113973	BM COMBO 130MM SNL LCK RESIN P.6 3500G	5"	38	2.6	18-28"
113974	BM COMBO 150MM SNL LCK RESIN P.1 100G	6"	29	2	18-28"
113975	BM COMBO 150MM SNL LCK RESIN P.2 200G	6"	29	2	18-28"
113976	BM COMBO 150MM SNL LCK RESIN P.4 500G	6"	32	2.2	18-28"
113977	BM COMBO 150MM SNL LCK RESIN P.4 1000G	6"	35	2.4	18-28"
113978	BM COMBO 150MM SNL LCK RESIN P.5 2000G	6"	38	2.6	18-28"
113979	BM COMBO 150MM SNL LCK RESIN P.6 3500G	6"	38	2.6	18-28"
114158	BM COMBO 130MM SNL LCK COPPER CRS 100G	5"	29	2	18-28"
114159	BM COMBO 130MM SNL LCK COPPER MED 200G	5"	29	2	18-28"
114160	BM COMBO 130MM SNL LCK COPPER FN 400G	5"	29	2	18-28"
114161	BM COMBO 130MM SNL LCK COPPER XFN 600G	5"	32	2.2	18-28"
114162	BM COMBO 150MM SNL LCK COPPER CRS 100G	6"	29	2	18-28"
114163	BM COMBO 150MM SNL LCK COPPER MED 200G	6"	29	2	18-28"
114164	BM COMBO 150MM SNL LCK COPPER FN 400G	6"	29	2	18-28"
114165	BM COMBO 150MM SNL LCK COPPER XFN 600G	6"	32	2.2	18-28"
The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.					