

Cyclone Straight Edge Wheels

GQ PN	Description	Diameter	PSI	BAR	Belt Speed
632206	CYC STR ED WHL 5" 50 GRT SNL	5"	35-40	2.5-2.7	15-20"
632201	CYC STR ED WHL 5" 100 GRT SNL	5"	35-40	2.5-2.7	15-20"
632203	CYC STR ED WHL 5" 200 GRT SNL	5"	35-40	2.5-2.7	15-20"
632205	CYC STR ED WHL 5" 400 GRT SNL	5"	35-40	2.5-2.7	15-20"
632207	CYC STR ED WHL 5" 800 GRT SNL	5"	35-40	2.5-2.7	15-20"
632202	CYC STR ED WHL 5" 1500 GRT SNL	5"	35-40	2.5-2.7	15-20"
632204	CYC STR ED WHL 5" 3000 GRT SNL	5"	35-40	2.5-2.7	15-20"
632214	CYC STR ED WHL 6" 50 GRT SNL	6"	35-40	2.5-2.7	15-20"
632209	CYC STR ED WHL 6" 100 GRT SNL	6"	35-40	2.5-2.7	15-20"
632211	CYC STR ED WHL 6" 200 GRT SNL	6"	35-40	2.5-2.7	15-20"
632213	CYC STR ED WHL 6" 400 GRT SNL	6"	35-40	2.5-2.7	15-20"
632215	CYC STR ED WHL 6" 800 GRT SNL	6"	35-40	2.5-2.7	15-20"
632210	CYC STR ED WHL 6" 1500 GRT SNL	6"	35-40	2.5-2.7	15-20"
632212	CYC STR ED WHL 6" 3000 GRT SNL	6"	35-40	2.5-2.7	15-20"

The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.