

Cyclone Ultra Flat Edge Wheels

GQ PN	Description	Diameter	PSI	BAR	Belt Speed
101184	CYCLONE ULTRA FLAT WHL 5" 50G SNL	5"	35-40	2.5-2.7	15-20"
101185	CYCLONE ULTRA FLAT WHL 5" 120G SNL	5"	35-40	2.5-2.7	15-20"
101186	CYCLONE ULTRA FLAT WHL 5" 220G SNL	5"	35-40	2.5-2.7	15-20"
101187	CYCLONE ULTRA FLAT WHL 5" 400G SNL	5"	35-40	2.5-2.7	15-20"
101188	CYCLONE ULTRA FLAT WHL 5" 800G SNL	5"	35-40	2.5-2.7	15-20"
101189	CYCLONE ULTRA FLAT WHL 5" 1800G SNL	5"	35-40	2.5-2.7	15-20"
101190	CYCLONE ULTRA FLAT WHL 5" 3500G SNL	5"	35-40	2.5-2.7	15-20"
101191	CYCLONE ULTRA FLAT WHL 6" 50G SNL	6"	35-40	2.5-2.7	15-20"
101191	CYCLONE ULTRA FLAT WHL 6" 50G SNL	6"	35-40	2.5-2.7	15-20"
101192	CYCLONE ULTRA FLAT WHL 6" 120G SNL	6"	35-40	2.5-2.7	15-20"
101193	CYCLONE ULTRA FLAT WHL 6" 220G SNL	6"	35-40	2.5-2.7	15-20"
101194	CYCLONE ULTRA FLAT WHL 6" 400G SNL	6"	35-40	2.5-2.7	15-20"
101195	CYCLONE ULTRA FLAT WHL 6" 800G SNL	6"	35-40	2.5-2.7	15-20"
101196	CYCLONE ULTRA FLAT WHL 6" 1800G SNL	6"	35-40	2.5-2.7	15-20"
101197	CYCLONE ULTRA FLAT WHL 6" 3500G SNL	6"	35-40	2.5-2.7	15-20"

The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.