

BACK TO INDEX



Ø20 mm

fitting 1/2" Gas

MICRON LINE

Pos	Slab Thickness [Inches or mm]	RPM (Min-Max)	Stock Removal [Inches or mm]	Feeding Speed [Inches/minute or mm/minute]	Note
1	3/4"-1 1/4" - 1 1/2" 20-30-40	6.000-7.000	shape	30" - 50" 750 - 1.250	Segmented 
2			0,008"-0,012" 0,2-0,3		
3			0,006"-0,008" 0,15-0,2		
4		5.500-6.000	0,002" 0,05	30" - 40" 750 - 1.000	
5	3/4"-1 1/4" - 1 1/2" 20-30-40	3.800-4.200	0,0011"-0,0019" 0,02-0,05	30" - 40" 750 - 1.000	ERASER (Only Flat Shape) 
5	3/4"-1 1/4" - 1 1/2" 20-30-40	3.800-4.200	0,0011"-0,0019" 0,02-0,05	30" - 40" 750 - 1.000	MFP5 
5	3/4"-1 1/4" - 1 1/2" 20-30-40	3.300-3.800	0,0011"-0,0019" 0,03-0,05 Pressure	30" - 40" 750 - 1.000	Express Polishing 
6					
7					
5	3/4"-1 1/4" - 1 1/2" 20-30-40	2.500-3.500	Dynamic Compensation for Diameter per Foot [Inch] 0,00024"	30" - 40" 750 - 1.000	Magic Polishing 
6			Dynamic Compensation for Radius per Meter [mm] 0,008-0,01		