

## Pulsar GSD Combo Wheels

GQ PN	Description	Diameter	PSI	BAR	Belt Speed
113620	PULSAR GSD COPPER COMBO WHL 5" 50G SNL	5"	35-40	2.5-2.75	15-30"
113621	PULSAR GSD COPPER COMBO WHL 5" 100G SNL	5"	35-40	2.5-2.75	15-30"
113622	PULSAR GSD COPPER COMBO WHL 5" 200G SNL	5"	35-40	2.5-2.75	15-30"
113623	PULSAR GSD COPPER COMBO WHL 5" 400G SNL	5"	35-40	2.5-2.75	15-30"
113624	PULSAR GSD COPPER COMBO WHL 5" 800G SNL	5"	35-40	2.5-2.75	15-30"
113625	PULSAR GSD RESIN COMBO WHL 5"1500G SNL	5"	35-40	2.5-2.75	15-30"
113626	PULSAR GSD RESIN COMBO WHL 5" 3000G SNL	5"	35-40	2.5-2.75	15-30"
113627	PULSAR GSD COPPER COMBO WHL 6" 50G SNL	6"	35-40	2.5-2.75	15-30"
113628	PULSAR GSD COPPER COMBO WHL 6" 100G SNL	6"	35-40	2.5-2.75	15-30"
113629	PULSAR GSD COPPER COMBO WHL 6" 200G SNL	6"	35-40	2.5-2.75	15-30"
113630	PULSAR GSD COPPER COMBO WHL 6" 400G SNL	6"	35-40	2.5-2.75	15-30"
113631	PULSAR GSD COPPER COMBO WHL 6" 800G SNL	6"	35-40	2.5-2.75	15-30"
113632	PULSAR GSD RESIN COMBO WHL 6"1500G SNL	6"	35-40	2.5-2.75	15-30"
113633	PULSAR GSD RESIN COMBO WHL 6" 3000G SNL	6"	35-40	2.5-2.75	15-30"

*The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.*