

Pulsar GSD Flat Edge Wheels

| GQ PN | Description | Diameter | PSI | BAR | Belt Speed |
|--------|-------------------------------------|----------|-------|---------|------------|
| 113634 | PULSAR GSD 4 STEP QRS FLAT 5" STP 0 | 5" | 22-30 | 1.5-2.0 | 48-60" |
| 113635 | PULSAR GSD 4 STEP QRS FLAT 5" STP 1 | 5" | 22-30 | 1.5-2.0 | 48-60" |
| 113636 | PULSAR GSD 4 STEP QRS FLAT 5" STP 2 | 5" | 22-30 | 1.5-2.0 | 48-60" |
| 113637 | PULSAR GSD 4 STEP QRS FLAT 5" STP 3 | 5" | 22-30 | 1.5-2.0 | 48-60" |
| 113638 | PULSAR GSD 4 STEP QRS FLAT 6" STP 0 | 6" | 22-30 | 1.5-2.0 | 48-60" |
| 113639 | PULSAR GSD 4 STEP QRS FLAT 6" STP 1 | 6" | 22-30 | 1.5-2.0 | 48-60" |
| 113640 | PULSAR GSD 4 STEP QRS FLAT 6" STP 2 | 6" | 22-30 | 1.5-2.0 | 48-60" |
| 113641 | PULSAR GSD 4 STEP QRS FLAT 6" STP 3 | 6" | 22-30 | 1.5-2.0 | 48-60" |

The information above represents a starting point for tool use. Adjust these parameters as necessary for your specific application, including material, machine, etc.