DESIGNED TO PENETRATE THE PAINT AND TEXTURE MATERIAL, LOOSENING THE BOND WITH THE SUR-FACE. ONCE APPLIED, THERE IS NO NEED TO COVER THE SURFACE WITH PLASTIC. SIMPLY SPRAY AND ALLOW TO DWELL FOR 15 MINUTES. THE TEXTURE CAN BE SCRAPED OFF WITH EASE. FOAMING FORMULA CLINGS TO THE SURFACE.







Biodegradable, Non-flammable, NPE Free, Phosphate-free, Chlorinated Solvent Free

## **Great For:**

Sheetrock · Plaster · Concrete Stone · Brick · Wood · Metals

## **BIOESQUE® TEXTURED CEILING REMOVER**

**HEAVY DUTY · FOAMING FORMULA** 









## **Directions For Use:**

Important: Always test first on an inconspicuous area. Use painters' tape and plastic drop cloths to protect any surfaces you do not intend to strip.

Note: Textured ceilings installed as late as the mid-80's may contain asbestos and/or lead and should be tested prior to removal. If test is positive, you must follow local, state and federal regulations on the containment, removal and disposal of these hazardous materials. You should wear a protective goggles and NIOSH approved respirator to control exposure. Carefully clean up with a wet mop or HEPA vacuum.

Directions: Apply liberally with a standard pump sprayer, foaming pump sprayer or Foam-It to the surface being stripped. Allow to dwell on surface for a minimum of 15 minutes, depending on the thickness of the paint and coating to be removed it could take longer. Using a scraper blade, test a small area, coating should remove easily from the surface. If not, allow more time to penetrate before testing again.

Once the coating is sufficiently softened, use a scarper blade to remove, taking care not to damage the underlying surface.

You should wear a Face mask and eye protection during this work. When scraping it is good idea to keep the texture wet to prevent dust.

After removal is complete dispose of material removed according to local, state and federal regulation. Prior to painting, wipe down the surface and patch any irregularities.

STORAGE: STORE IN ORIGINAL CONTAINER IN A DRY, COOL AND WELL VENTILATED AREA AWAY FROM STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT FREEZE. **Disposal:** Dispose of Contents/-CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT IN ACCORDANCE WITH APPLICABLE LOCAL/REGIONAL/NATIONAL AND INTERNATIONAL REGULATIONS AND PRODUCT CHARACTER-ISTICS AT TIME OF Disposal. FOR MORE INGREDIENT INFORMATION VISIT: WWW.BIOESQUESOLUTIONS.COM OR CALL 800-921-4634

## MADE IN USA



Distributed by NatuReal, LLC 2091 NE 36th Street #50548 Lighthouse Point, FL 33074 800.921.4634





NON-FLAMMABLE, AND BIODEGRADABLE FOR A SAFER CLEAN THAT IS FRIENDLIER TO THE ENVIRONMENT.

KEEP OUT OF REACH OF CHILDREN NET CONTENTS: 5 GALLONS (18.9 L) WARNING: KEEP OUT OF REACH OF CHILDREN. CAUSES SERIOUS EYE OR PHYSICIAN. FIRST AID: CONTACT WITH EYES: IF IN EYES.

LENGES IT BOST TO BO CONTINUE MINISTRY IT THE MINISTRY FEBRUARY FE

