according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 1/10

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

GQ 314P Premium Impregnator

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Mixture Impregnation, contains: organic solvents

1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

Supplier: GranQuartz

Street: 4963 South Royal Atlanta Drive
Postal code/city: USA- Tucker, GA 30084

 Telephone :
 +1 770 621-9777

 Telefax :
 +1 770 621-9771

 Contact :
 Technical Department

E-mail: admin@granquartz.com

Emergency telephone number: +1 770 621-9777

(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Asp. Tox. 1; H304 - Aspiration hazard: Category 1; May be fatal if swallowed and enters airways.

Flam. Liq. 3; H226 - Flammable liquids: Category 3; Flammable liquid and vapour.

STOT SE 3; H336 - STOT-single exposure: Category 3; May cause drowsiness or dizziness.

Additional information

This mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Remark

Full text of H- and EUH-phrases: see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms







Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS No.: (64742-48-9)

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7)

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 2 / 10

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with

local and national regulations.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; REACH registration No.: 01-2119463258-33-xxxx;

EC No. : 919-857-5; CAS No. : (64742-48-9)

Weight fraction : ≥ 85 - < 90 %

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; REACH registration No.: 01-2119472146-39-xxxx; EC No.: 918-167-

1; CAS No.: (64741-65-7)

Weight fraction : \geq 5 - < 10 %

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Asp. Tox. 1; H304 Aquatic Chronic 4; H413

Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; REACH registration No.: 01-2119456810-40-xxxx; EC No.: 920-901-

0; CAS No.: (90622-58-5)

Weight fraction : \geq 1 - < 5 % Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation. < 0,1% Benzene, REG(EC) No 1272/2008, Annex VI; J, P

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice. Observe risk of aspiration if vomiting occurs.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

After ingestion

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 3 / 10

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water alcohol resistant foam ABC-powder Carbon dioxide (CO2) Water spray

Unsuitable extinguishing media

High power water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO2) Hydrogen fluoride Fluoropolymers

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition. - No smoking. The product is: Combustible

Fire class :

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Hints on joint storage

Storage class (TRGS 510): 3

Recommended storage temperature 5 - 25 °C

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

7.3 Specific end use(s)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 4 / 10

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS No.: (64742-48-9)

Limit value type (country of origin): TRGS 900 (D)
Limit value: 600 mg/m³

Version:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7)

Limit value type (country of origin) : TRGS 900 (D) Limit value : 600 mg/m³

Version:

Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; CAS No.: (90622-58-5)

Limit value type (country of origin): TRGS 900 (D)
Limit value: 600 mg/m³

Version:

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection goggles

Required properties

DIN EN 166

Skin protection

Hand protection

Suitable gloves type: Gloves with long cuffs

 $\textbf{Suitable material}: NBR \; (Nitrile \; rubber), \; 0,4mm, \; >8h; \; FKM \; (fluoro \; rubber), \; 0,7mm, \; >8h; \;$

Recommended glove articles: Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures: Check leak tightness/impermeability prior to use.

Remark: Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Protective clothing.

Suitable protective clothing: Chemical protection clothing Chemical resistant safety shoes

Required properties: antistatic.

Recommended protective clothing articles: DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

Remark: Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 5/10

9.1 Information on basic physical and chemical properties

Appearance: liquid
Colour: colourless
Odour: solvent
Safety relevant basis data

Freezing point : (1013 hPa) < .13 °C Initial boiling point and boiling range (1013 hPa) approx. 149 °C Decomposition temperature : (1013 hPa) not determined

Decomposition temperature : (1013 hPa) not determined **Flash point :** approx. 35

Ignition temperature : not determined

Sustaining combustion

Yes

UN Test L2:Sustained combustibility test

°C

closed cup

ISO cup 4 mm

Lower explosion limit: not determined Upper explosion limit: not determined

Vapour pressure: (50 °C) < 3000 hPa

Density: (20 °C) approx. 0,8 g/cm³ Pyknometer

Solvent separation test: (20 °C) < 3 %

Water solubility (20 °C) hydrolysed pH: hydrolysed

 Iog P O/W :
 not determined

 Flow time :
 (23 °C)
 approx.
 12

VOC-FR

Odour threshold:

not determined
not determined
A+

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter: LD50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg

Parameter: LD50 (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No. : (64741-65-7)

Exposure route : Oral
Effective dose : > 5000 mg/kg

Parameter: LD50 (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (90622-58-5)

)

Exposure route: Oral

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 6 / 10

Effective dose: > 5000 mg/kg

Acute dermal toxicity

Parameter: LD50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/kg

Parameter: LD50 (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7)

)

Exposure route : Dermal
Effective dose : > 5000 mg/kg

Parameter: LD50 (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; CAS No.: (90622-58-5)

)

Exposure route : Dermal
Effective dose : > 5000 mg/kg
Specific symptoms in animal studies

No data available

Irritant and corrosive effects

Assessment/classification

Repeated exposure may cause skin dryness or cracking.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No indication of human carcinogenicity.

Germ cell mutagenicity

In vivo mutagenicity

Other information

No experimental indications of in vivo mutagenicity exist.

Human toxicological data

Other information

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

Practical experience/human evidence

No indications of human reproductive toxicity exist.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

 Species :
 Fish

 Effective dose :
 > 1000 mg/l

 Exposure time :
 96 h

 Method :
 OECD 203

Parameter: LC50 (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7)

Species: Fish Effective dose: > 100 mg/

Parameter: LC50 (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; CAS No. : (90622-58-5)

Species : Fish Effective dose : > 100 mg/l

Chronic (long-term) fish toxicity

Parameter: NOEC (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No. : (64742-48-9))

Species: Fish
Effective dose: > 0,1 - 1 mg/l

Parameter: NOEC (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics ; CAS No. : (64741-65-

7))

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date:
 23.05.2017
 Version (Revision):
 2.0.0 (1.0.0)

 Print date:
 25.08.2017
 Page:
 7 / 10

Species: Fish Effective dose: > 0,1 - 1 mg/l

Parameter: NOEC (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (90622-58-

Species: Fish
Effective dose: > 0,1 - 1 mg/l

Acute (short-term) daphnia toxicity

Parameter: EC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

 Species :
 Daphnia

 Effective dose :
 > 1000 mg/l

 Exposure time :
 48 h

 Method :
 OECD 202

Parameter: EC50 (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7)

)

Species : Daphnia
Effective dose : > 100 mg/l

Parameter: EC50 (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics ; CAS No. : (90622-58-5)

)

Species : Daphnia Effective dose : > 100 mg/l

Chronic (long-term) daphnia toxicity

Parameter: NOEC (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

Species: Daphnia
Effective dose: > 0,1 - 1 mg/l

Parameter: NOEC (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-

7))

Species : Daphnia Effective dose : > 0,1 - 1 mg/l

Parameter: NOEC (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; CAS No.: (90622-58-

5))
Species : Daphnia
Effective dose : > 0,1 - 1 mg/l

Acute (short-term) algae toxicity

Parameter: IC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; CAS

No.: (64742-48-9))

 Species :
 Algae

 Effective dose :
 > 1000 mg/l

 Exposure time :
 72 h

 Method :
 OECD 201

Parameter: IC50 (Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics; CAS No.: (64741-65-7))

Species : Algae Effective dose : > 100 mg/l

Parameter: IC50 (Hydrocarbons, C11-C13, isoalkanes, < 2% aromatics; CAS No.: (90622-58-5))

Species : Algae Effective dose : > 100 mg/l

Sediment toxicity

Toxicity to soil macroorganisms

Acute earthworm toxicity

Chronical earthworm toxicity (reproduction)

Long-term toxicity of organisms living in the sediment

Effects in sewage plants

Observe local regulations concerning effluent treatment.

12.2 Persistence and degradability

No data available

Abiotic degradation

Abiotic degradation in Water

Hydrolysis

Biodegradation

No data available

12.3 Bioaccumulative potential

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 8 / 10

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No data available

12.7 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (91/689/EEC): 07 01 04*

Waste code packaging

Waste code packaging: 15 01 10*

Waste treatment options

29/35 - Do not empty into drains; dispose of this material and its container in a safe way. Delivery to an approved waste disposal company.

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

 Class(es):
 3

 Classification code:
 F1

 Hazard identification number (Kemler No.):
 30

 Tunnel restriction code:
 D/E

Special provisions: $640E \cdot LQ \cdot 5I \cdot E \cdot 1$

Hazard label(s): 3

Sea transport (IMDG)

Class(es):3EmS-No.: $F-E / \underline{S-E}$ Special provisions: $LQ 5 | \cdot E 1$ Hazard label(s):3

Air transport (ICAO-TI / IATA-DGR)

Class(es): 3
Special provisions: E1

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: GQ 314P Premium Impregnator

 Revision date :
 23.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 25.08.2017
 Page :
 9 / 10

Hazard label(s): 3

14.4 Packing group

Ш

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (clp)

Directive 2008/98/EC of the European Parliament and of the Council on waste (2000/532/EC)

EN 2:1992 (DIN EN 2:2005-01)

Other regulations (EU)

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

National regulations

Observe in addition any national regulations! TRGS 510

Water hazard class (WGK)

Class: 2 (Hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

VOCV-Regulation (CH)

Maximum VOC content (Switzerland): 91,9 Wt % according to VOCV

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H413 May cause long lasting harmful effects to aquatic life.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily

(ΕN	/	D	
---	----	---	---	--

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

GQ 314P Premium Impregnator Trade name:

Revision date : 23.05.2017 Version (Revision) : 2.0.0 (1.0.0) Print date : 25.08.2017 Page: 10 / 10

valid for the new made-up material.