

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017

Version (Revision) :

2.0.0 (1.0.0)

Print date : 25.08.2017

Page :

1 / 8

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

GQ 313P Premium Waterbased Impregnator

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Mixture Impregnation, aqueous solution

1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

Supplier :

GranQuartz

Street :

4963 South Royal Atlanta Drive

Postal code/city :

USA- Tucker, GA 30084

Telephone :

+1 770 621-9777

Telefax :

+1 770 621-9771

Contact :

Technical Department

E-mail: admin@granquartz.com

Emergency telephone number:

+1 770 621-9777

(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Additional information

This substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

Remark

Full text of H- and EUH-phrases: see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH210

Safety data sheet available on request.

2.3 Other hazards

None

2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

ETHANEDIOL ; REACH registration No. : 01-2119456816-28-xxxx ; EC No. : 203-473-3; CAS No. : 107-21-1

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Acute Tox. 4 ; H302

PROPAN-2-OL ; REACH registration No. : 01-2119457558-25-xxxx ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017

Version (Revision) :

2.0.0 (1.0.0)

Print date : 25.08.2017

Page :

2 / 8

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Protect uninjured eye. In case of eye irritation consult an ophthalmologist.

After ingestion

When in doubt or if symptoms are observed, get medical advice. Rinse mouth thoroughly with water. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water alcohol resistant foam ABC-powder Carbon dioxide (CO₂) Water spray

Unsuitable extinguishing media

High power water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO₂) Hydrogen fluoride Fluoropolymers

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Coordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

Other information

Clear spills immediately.

6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017

Version (Revision) :

2.0.0 (1.0.0)

Print date : 25.08.2017

Page :

3 / 8

SECTION 7: Handling and storage

7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

Protective measures

Not useable after freezing. Inhalation of vapours or spray/mists Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

The product is not: Flammable Usual measures for fire prevention.

Fire class : -

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Hints on joint storage

Storage class (TRGS 510) : 10

Recommended storage temperature 5 - 25 °C

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

Protect against : Frost

7.3 Specific end use(s)

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ETHANEDIOL ; CAS No. : 107-21-1

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 10 ppm / 26 mg/m³

Peak limitation : 2(I)

Remark : H,Y

Version : 04.11.2017

Limit value type (country of origin) : STEL (EC)

Limit value : 40 ppm / 104 mg/m³

Remark : H

Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)

Limit value : 20 ppm / 52 mg/m³

Remark : H

Version : 08.06.2000

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 200 ppm / 500 mg/m³

Peak limitation : 2(II)

Remark : Y

Version : 04.11.2017

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Acetone / Whole blood (B) / End of exposure or end of shift

Limit value : 50 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Acetone / Urine (U) / End of exposure or end of shift

Limit value : 50 mg/l

Version : 31.03.2004

8.2 Exposure controls

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017
Print date : 25.08.2017

Version (Revision) : 2.0.0 (1.0.0)
Page : 4 / 8

Personal protection equipment

Eye/face protection

Usually no personal eye/face protection necessary. Eye/face protection necessary at: Splashes, Contact with eyes, Spray application.

Suitable eye protection

Eye glasses with side protection goggles

Required properties

DIN EN 166

Skin protection

Usually no personal skin protection necessary. Skin protection necessary at: Splashes, Contact with skin, Spray application.

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : NBR (Nitrile rubber), 0,4mm, >8h; Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : acid-resistant. alkali-resistant.

Recommended protective clothing articles : DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : unspecific

Safety relevant basis data

Freezing point :	(1013 hPa)	approx.	-10 °C	
Initial boiling point and boiling range :	(1013 hPa)	approx.	88 °C	
Decomposition temperature :	(1013 hPa)		not determined	
Flash point :		approx.	36 °C	closed cup
Ignition temperature :			not determined	
Sustaining combustion			No	UN Test L2:Sustained combustibility test
Lower explosion limit :			not determined	
Upper explosion limit :			not determined	
Vapour pressure :	(50 °C)	<	3000 hPa	
Density :	(20 °C)	approx.	1 g/cm ³	Pyknometer

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017
Print date : 25.08.2017

Version (Revision) : 2.0.0 (1.0.0)
Page : 5 / 8

Solvent separation test :	(20 °C)	<	3	%	
Water solubility	(20 °C)		miscible		
pH :		approx.	5		
log P O/W :			not determined		
Flow time :	(23 °C)	approx.	13	s	ISO cup 4 mm
Odour threshold :			not determined		
Vapourisation rate :			not determined		
VOC-FR			A+		

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Oral
Species : Rat
Effective dose : 5840 mg/kg
Method : OECD 401

Acute dermal toxicity

Parameter : LD50 (ETHANEDIOL ; CAS No. : 107-21-1)
Exposure route : Dermal
Species : Mouse
Effective dose : > 3500 mg/kg
Parameter : LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Dermal
Species : Rabbit
Effective dose : 13900 mg/kg
Method : OECD 402

Acute inhalation toxicity

Parameter : LC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Exposure route : Inhalation
Species : Rat
Effective dose : > 2,5 mg/l
Exposure time : 6 h
Parameter : LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Species : Rat
Effective dose : > 25 mg/l
Exposure time : 6 h
Method : OECD 403

Specific symptoms in animal studies

No data available

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017
Print date : 25.08.2017

Version (Revision) : 2.0.0 (1.0.0)
Page : 6 / 8

Irritant and corrosive effects

Assessment/classification

Causes serious eye damage. Causes severe burns.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No indication of human carcinogenicity.

Germ cell mutagenicity

In vivo mutagenicity

Other information

No experimental indications of in vivo mutagenicity exist.

Human toxicological data

Other information

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

Practical experience/human evidence

No indications of human reproductive toxicity exist.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Fish
Effective dose : 72860 mg/l
Exposure time : 96 h
Parameter : LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Fish
Effective dose : 9640 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Fish
Effective dose : 15380 mg/l
Exposure time : 7 d

Acute (short-term) daphnia toxicity

Parameter : EC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Daphnia
Effective dose : > 100 mg/l
Exposure time : 48 h
Method : OECD 202
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Daphnia
Effective dose : 9714 mg/l
Exposure time : 24 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Daphnia
Effective dose : 8590 mg/l
Exposure time : 7 d

Acute (short-term) algae toxicity

Parameter : IC50 (ETHANEDIOL ; CAS No. : 107-21-1)
Species : Algae
Effective dose : 6500 - 13000 mg/l
Exposure time : 96 h
Parameter : IC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Algae
Effective dose : > 100 mg/l
Exposure time : 72 h

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017

Version (Revision) :

2.0.0 (1.0.0)

Print date : 25.08.2017

Page :

7 / 8

Sediment toxicity

Toxicity to soil macroorganisms

Acute earthworm toxicity

Chronical earthworm toxicity (reproduction)

Long-term toxicity of organisms living in the sediment

Effects in sewage plants

Observe local regulations concerning effluent treatment.

12.2 Persistence and degradability

No data available

Abiotic degradation

Abiotic degradation in Water

Hydrolysis

Biodegradation

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No data available

12.7 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (91/689/EEC) : 07 01 99

Waste treatment options

29/35 - Do not empty into drains; dispose of this material and its container in a safe way.

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : GQ 313P Premium Waterbased Impregnator

Revision date : 30.05.2017

Version (Revision) : 2.0.0 (1.0.0)

Print date : 25.08.2017

Page : 8 / 8

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (clp)

Directive 2008/98/EC of the European Parliament and of the Council on waste (2000/532/EC)

EN 2:1992 (DIN EN 2:2005-01)

Other regulations (EU)

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

National regulations

Observe in addition any national regulations! TRGS 510

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

VOCV-Regulation (CH)

Maximum VOC content (Switzerland) : 9,5 Wt % according to VOCV

15.2 Chemical safety assessment

No information available.

15.3 Additional information

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.