

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **PROSEAL**
Chemical name and synonym **Cere e resine in soluzione**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Water and oil-proof superficial treatment.**

1.3. Details of the supplier of the safety data sheet

Name **Tenax Spa**
Full address **Via I Maggio, 226**
District and Country **37020 Volargne (VR)
Italy**
Tel. **+39 045 6887593**
Fax **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet **msds@tenax.it**

Product distribution by **TENAX USA - 625 Griffith Road - Unit 120 - Charlotte NC 28217 Tel. 001 704 583 1173 - Tel: (800) 341 0432 - Fax 001 704 583 3166 - info@tenaxusa.com**

1.4. Emergency telephone number

For urgent inquiries refer to **1-800-5355053 (1-352-323-3500 international)**

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Flammable liquid, category 3

Specific target organ toxicity - single exposure, category 3

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / lighting / . . . / equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.

Response:

P303+P361+P353 IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 2 / 10

US

SECTION 2. Hazards identification. ... / >>

P312 Call a POISON CENTER / doctor / . . . / if you feel unwell.
P370+P378 In case of fire: use . . . to extinguish.

Storage:
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:
P501 Dispose of contents / container to . . .

2.2. Other hazards.

Additional hazards.
Repeated exposure may cause skin dryness or cracking.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification:
NAPHTA (PETROL.) HYDROTREATED HEAVY		
CAS. 64742-48-9	50 - 100	
N-BUTYL ACETATE		
CAS. 123-86-4	30 - 50	Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336
Distillates (petroleum), hydrotreated light :Kerosine - unspecified		
CAS. 64742-47-8	5 - 10	
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
CAS. 34590-94-8	1 - 3,5	

Note: Upper limit is not included into the range.
The full wording of hazard (H) phrases is given in section 16 of the sheet

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 3 / 10

US

contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU TLV-ACGIH	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. ACGIH 2014

NAPHTA (PETROL.) HYDROTREATED HEAVY

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
TLV-ACGIH	-	1595			

SECTION 8. Exposure controls/personal protection. ... / >>

N-BUTYL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH	-	713	150	950	200
OSHA	USA	710	150		
CAL/OSHA	USA	710	150	950	200
NIOSH	USA	710	150	950	200

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	606	100	909	150	SKIN.
OEL	EU	308	50			SKIN.
OSHA	USA	600	100			SKIN.
CAL/OSHA	USA	600	100	900	150	SKIN.
NIOSH	USA	600	100	900	150	SKIN.

TLV of solvent mixture: 713 mg/m3.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid	
Colour	transparent	
Odour	aromatic	
Odour threshold.	Not available.	
pH.	Not available.	
Melting point / freezing point.	Not available.	
Initial boiling point.	Not available.	
Boiling range.	Not available.	
Flash point.	23 ≤ T ≤ 60	(°C/°F)
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Lower inflammability limit.	Not available.	
Upper inflammability limit.	Not available.	



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 5 / 10

US

SECTION 9. Physical and chemical properties. ... / >>

Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,82 Kg/l
Solubility	SOLUBLE IN AROMATIC
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER: may react with oxidising agents. When heated to decomposition it releases harsh and irritating fumes and vapours.

N-BUTYL ACETATE: decomposes readily with water, especially when warm.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

N-BUTYL ACETATE: risk of explosion on contact with: strong oxidising agents. Can react dangerously with alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE: avoid exposure to moisture, sources of heat and naked flames.

10.5. Incompatible materials.

N-BUTYL ACETATE: water, nitrates, strong oxidising agents, acids and alkalis and potassium tert-butoxide.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

N-BUTYL ACETATE: in humans the substance's vapours cause irritation to the eyes and nose. In the event of repeated exposure, there is skin irritation, dermatosis (with dryness and flaking of the skin) and keratitis.

N-BUTYL ACETATE	
LD50 (Oral).	> 6400 mg/kg Rat
LD50 (Dermal).	> 5000 mg/kg Rabbit
LC50 (Inhalation).	21,1 mg/l/4h Rat



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 6 / 10

US

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

DIPROPYLENE GLYCOL MONOMETHYL ETHER
Solubility in water. mg/l 1000 - 10000
Rapidly biodegradable.

N-BUTYL ACETATE
Solubility in water. mg/l 1000 - 10000

12.3. Bioaccumulative potential.

DIPROPYLENE GLYCOL MONOMETHYL ETHER
Partition coefficient: n-octanol/water. 0,0043

N-BUTYL ACETATE
Partition coefficient: n-octanol/water. 2,3
BCF. 15,3

12.4. Mobility in soil.

N-BUTYL ACETATE
Partition coefficient: soil/water. < 3

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to dangerous goods transport regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: UN: 1993

14.2. UN proper shipping name.

ADR / RID: FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE)
IMDG: FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE)
IATA: FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE)

SECTION 14. Transport information. ... / >>**14.3. Transport hazard class(es).**

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4. Packing group.**

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user.

ADR / RID:	Nr. Kemler: 30	Limited Quantity 5 L	Tunnel restriction code (D/E)
	Special Provision: 640E		
IMDG:	EMS: F-E, S-E	Limited Quantity 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**U.S. Federal Regulations:Clean Air Act Section 112(b):

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 8 / 10

US

SECTION 15. Regulatory information. ... / >>

EPCRA 302 EHS TPQ:
No component(s) listed.

EPCRA 304 EHS RQ:
No component(s) listed.

CERCLA RQ:
123-86-4 N-BUTYL ACETATE

EPCRA 313 TRI:
34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)

RCRA Code:
No component(s) listed.

CAA 112 (r) RMP TQ:
No component(s) listed.

State Regulations.

Massachusetts:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
123-86-4 N-BUTYL ACETATE

Minnesota:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
123-86-4 N-BUTYL ACETATE

New Jersey:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
123-86-4 N-BUTYL ACETATE

New York:

123-86-4 N-BUTYL ACETATE

Pennsylvania:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
123-86-4 N-BUTYL ACETATE

California:

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol ethers)
123-86-4 N-BUTYL ACETATE

Proposition 65:

This product does not contain any substances known to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS:

Information not available.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Fam. Liq. 3	Flammable liquid, category 3
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 9 / 10

US

SECTION 16. Other information. ... / >>

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.



Tenax Spa PROSEAL

Revision nr.1
Dated 21/5/2015
Printed on 21/5/2015
Page n. 10 / 10

US

SECTION 16. Other information. ... / >>

Provide appointed staff with adequate training on how to use chemical products.