Printing date 07/06/2015 Reviewed on 07/06/2015

1 Identification

- · Product identifier
- · Trade name: W&S Quick Water Clear Flowing
- · Article number: 1025213
- · Application of the substance / the mixture Polyester resin
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Company Name: Axson USA, Inc.

Head quarters:

31200 Stephenson Hwy Madison Heights, MI 48071 USA

ehs-us@axson.com

- · Information department: Product safety department
- · Emergency telephone number:

During normal opening times: +1(248) 588-2270 *Chemtec 24-hour Emergency:* +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Styrene

(Contd. on page 2)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 1)

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

May cause cancer.

May cause respiratory irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 2)

· Dangerous components:

100-42-5 Styrene 25-50%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

 $Ensure\ a dequate\ ventilation.$

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 3)

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

100-42-5 Styrene

ACGIH TLV Short-term value: 170 at 40 ppm mg/m³

Long-term value: 85 at 20 ppm mg/m³

OSHA PEL Long-term value: 100 ppm mg/m³

Ceiling limit value: 200 ppm mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical propert	ies		
Information on basic physical and chemical properties			
General Information	1 1		
Appearance:			
Form:	Liquid		
Color:	Clear		
Odor:	Aromatic		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	145 °C (293 °F)		
Flash point:	31 °C (88 °F)		
Flammability (solid, gaseous):	Not applicable.		
Ignition temperature:	490 °C (914 °F)		
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.		
Explosion limits:			
Lower:	0.9 Vol %		
Upper:	6.8 Vol %		
Vapor pressure at 20 °C (68 °F):	6 hPa (5 mm Hg)		
Density at 20 °C (68 °F):	1.14 g/cm³ (9.513 lbs/gal)		
Relative density	Not determined.		
Vapour density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water:	Not miscible or difficult to mix.		
Partition coefficient (n-octanol/water	r): Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		

(Contd. on page 6)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 5)

· Solvent content:

Organic solvents: 0.0 % VOC content: 33.9 %

386.7 g/l / 3.23 lb/gl

• *Other information* No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
100-42-5 S	100-42-5 Styrene			
Oral	LD50	316 mg/kg (mouse)		
		2650 mg/kg (rat)		
Dermal	<i>LD50</i>	>2000 mg/kg (rat)		
Inhalative	LC50/4 h	11.8 mg/l (rat)		

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

Carcinogenic.

· Carcinogenic categories

	· IARC (In	· IARC (International Agency for Research on Cancer)	
Γ	64-17-5	ethanol	1
	136-52-7	cobalt bis(2-ethylhexanoate)	2B
	108-10-1	4-methylpentan-2-one	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US/

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, IMDG, IATA	UN1866
· UN proper shipping name · DOT · IMDG, IATA	Resin solution RESIN SOLUTION
· Transport hazard class(es) · DOT, IMDG, IATA · Class	2 Elammable liquida
· Packing group · DOT, IMDG, IATA	3 Flammable liquids III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Flammable liquids F-E, <u>S-E</u>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	r Not applicable.

(Contd. on page 8)

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 7)

· Transport/Additional information:

 $\cdot DOT$

• Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

· UN ''Model Regulation'': UN1866, Resin solution, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

136-52-7 cobalt bis(2-ethylhexanoate)

108-10-1 4-methylpentan-2-one

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

108-10-1 4-methylpentan-2-one

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

108-10-1 4-methylpentan-2-one

142-82-5 heptane

D

· TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethanol

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

CHECO

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

(Contd. of page 8)

· Signal word Danger

· Hazard-determining components of labeling:

Styrene

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

May cause cancer.

May cause respiratory irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If swallowed: Call a poison center/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 07/06/2015 / 5

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)

(Contd. of page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/06/2015 Reviewed on 07/06/2015

Trade name: W&S Quick Water Clear Flowing

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Care 1A: Careinogenicity, Hazard Category 1A

Carc. 1A: Carcinogenicity, Hazard Category 1A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

JSA -