

SAFETY DATA SHEET

1. Identification

Product identifier LATAPOXY 310 Stone Adhesive Part B

Other means of identificationNot available.Recommended useAdhesive.Recommended restrictionsNone known.

Manufacturer / Importer / Supplier / Distributor information

Company Name
 LATICRETE International
 1 Laticrete Park, N
 Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves and eye/face

protection.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

Supplemental information

Hazard symbol



Hazard statement Toxic to aquatic life with long lasting effects.

917004 Version #: 01 Revision date: - Issue date: 15-January-2014

Precautionary statement

Prevention Avoid release to the environment.

Response Collect spillage.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propane, 2,2-bis[p-(2,3-epoxy propoxy)phenyl]-, polymers	25085-99-8	23-28
Calcium carbonate	471-34-1	19 - 21
Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin	28064-14-4	5-10
Alkyl(C12-14) glycidyl ether	68609-97-2	3-7
Titanium dioxide	13463-67-7	0.8-1.1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Rash, Irritant effects.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all releases.

LATAPOXY 310 Stone Adhesive Part B

SDS US

7. Handling and storage

Precautions for safe handling Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Persons with epoxy

allergy should not work with this product. Wear appropriate personal protective equipment. Provide

adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a well-ventilated place. Store away from incompatible

materials (See Section 10).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium carbonate (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.
•		15 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Valu	les		
Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Туре	Value	Form
Calcium carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Paste.
Color	Off-white.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not applicable
Initial boiling point and boiling range	Not applicable
Flash point	Non flammable.
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available.

LATAPOXY 310 Stone Adhesive Part B

917004 Version #: 01 Revision date: -3/7Issue date: 15-January-2014

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Not applicable Vapor pressure Not applicable Vapor density

Relative density 1.5

Insoluble Solubility(ies)

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

Masses of more than 1 pound of product plus an aliphatic amine will cause irreversible

polymerization with considerable heat build up.

Excessive heat. Contact with incompatible materials. Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

May cause discomfort if swallowed. Ingestion

Inhalation No adverse effects due to inhalation are expected. Irritating to skin. May cause an allergic skin reaction. Skin contact

Eye contact Irritating to eyes. Rash. Irritant effects. Symptoms related to the

physical, chemical and toxicological characteristics

Information on toxicological effects

May cause discomfort if swallowed. **Acute toxicity**

Test Results Components **Species**

Calcium carbonate (CAS 471-34-1)

Acute Oral

LD50

Rat 6450 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction. Germ cell mutagenicity Not expected to be mutagenic.

Carcinogenicity Not classified. Inhalation of titanium dioxide dust may cause cancer, however due to the physical

form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

LATAPOXY 310 Stone Adhesive Part B

SDS US

Specific target organ toxicity -

single exposure

No data available.

Specific target organ toxicity -

repeated exposure

No data available.

No data available. **Aspiration hazard**

Chronic effects Prolonged or repeated contact may cause drying, cracking, or irritation.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components **Species Test Results**

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers (CAS 25085-99-8)

Aquatic

Acute

IC50 11 mg/l, 72 hours Algae Algae EC50 Crustacea Daphnia 1.8 mg/l, 48 hours Fish LC50 Fish 1 - 10 mg/l

Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin (CAS 28064-14-4)

Aquatic

Bioaccumulative potential

Acute

LC50 Fish Fish 1 - 10 mg/l

No data available for this product.

Persistence and degradability No data is available on the degradability of this product.

Mobility in soil Not available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

> and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN3077

Environmentally hazardous substances, solid, n.o.s. (Propane, 2,2-bis[p-(2,3-epoxypropoxy)ph **UN proper shipping name**

enyl]-, polymers, Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin)

Transport hazard class(es) 9 Subsidiary class(es)

Packing group

Ш **Environmental hazards**

Marine pollutant Yes Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33 Special provisions

Packaging exceptions 155 Packaging non bulk 213 240 Packaging bulk

IATA

UN number UN3077

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Propane, 2,2-bis[p-(2,3-epoxypropoxy)ph

enyl]-, polymers, Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin)

Transport hazard class(es) Subsidiary class(es)

LATAPOXY 310 Stone Adhesive Part B

917004 Version #: 01 Revision date: -Issue date: 15-January-2014 SDS US

Ш **Packaging group Environmental hazards** Yes Labels required 9 **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN3077 **UN** number

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Propane, 2,2-bis[p-(2,3-epoxypropoxy)ph

enyl]-, polymers, Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin)

Transport hazard class(es) 9 Subsidiary class(es) Ш **Packaging group Environmental hazards**

Yes Marine pollutant Labels required 9 F-A, S-F **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and This substance/mixture is not intended to be transported in bulk.

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous

chemical

Yes

Nο

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 471-34-1) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Calcium carbonate (CAS 471-34-1)

LATAPOXY 310 Stone Adhesive Part B

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Titanium dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 15-January-2014

Revision date - 01

United States & Puerto Rico

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

DisclaimerThe information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be

beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATAPOXY 310 Stone Adhesive Part B

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).