Safety Data Sheet

SECTION 1: Identification

1.1. Identification

Product name : Quartz Renew-Snake Skin Revealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Heavy Scratch Remover for Plastic Surface

1.3. Details of the supplier of the safety data sheet

Surface Savers

18700 N 107th Ave, Suite 20

Sun City, AZ 85373

1.4. Emergency telephone number

Emergency number : 623-451-4569

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	68 - 86	Not classified
Aluminum oxide (Al2O3)	(CAS No) 1344-28-1	7 - 13	Not classified
Dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	3 - 7	Flam. Liq. 4, H227
Ceramic materials and wares, chemicals	(CAS No) 66402-68-4	3 - 7	Not classified
Proprietary copolymer dispersed in isoparaffin	None	1 - 5	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If mists or sprays of this product are inhaled, remove victim to fresh air. The contaminated individual must seek medical attention if any adverse effects occur.

First-aid measures after skin contact

If this product contaminates the skin, begin decontamination with running water. Minimum flushing is for 20 minutes. The contaminated individual must seek medical attention if any adverse effects occur after flushing.

First-aid measures after eye contact

: If this product enters the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have contaminated individual "roll" eyes. Minimum flushing is for 20 minutes. Contaminated individual must seek medical attention if adverse effect continues after flushing.

First-aid measures after ingestion

: If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If victim is convulsing, maintain an open airway and obtain immediate medical attention.

06/14/2017 EN (English US) Page 1

Safety Data Sheet

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Inhalation is not anticipated to be a significant route of overexposure to this product. If mists or sprays of this product are inhaled, they may mildly irritate the nose and other tissues of the

upper respiratory system. Symptoms are generally alleviated upon breathing fresh air.

Symptoms/injuries after skin contact

Skin contact may cause mild redness, discomfort, and irritation. Symptoms are generally alleviated upon rinsing. Repeated skin contact may cause dermatitis (dry, red skin). The Dipropylene Glycol Methyl Ether component of this product can be absorbed through intact

skin. Skin absorption is not anticipated to cause adverse effects. Though not anticipated to be a likely route of occupational exposure, injection of this material (via puncture or laceration by a contaminated object) may cause local reddening, tissue swelling, and discomfort in addition to

the wound.

Symptoms/injuries after eye contact : Depending on the duration and concentration of overexposure, eye contact may cause tearing

and redness.

Symptoms/injuries after ingestion : Ingestion is not anticipated to be a likely route of exposure to this product. If this material is

swallowed, it may cause headache, nausea, and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing material suitable to the surrounding fire, including halon, carbon dioxide, dry

chemical and ABC class.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : When involved in a fire, this material may decompose and produce irritating vapors and toxic

gases (including silicon, aluminum and carbon oxides).

Explosion hazard : None known.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Proper protective equipment should be used. In the event of a spill, clear the area and protect people. Eliminate all sources of ignition before cleanup begins. Use nonsparking tools. The atmosphere must have levels of components lower than those listed in Section 8, (Exposure Controls and Personal Protective Equipment) if applicable, and have at least 19.5 percent oxygen before personnel can be allowed into the area without Self-Contained Breathing Apparatus (SCBA).

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Stop the flow of material, if this is without risk.

Methods for cleaning up

: Small Spills: Absorb spilled material with polypads or other suitable, non-reacting sorbent, avoiding generation of aerosols, wearing gloves, goggles and apron. Place spilled material in appropriate container for disposal, sealing tightly. Remove all residue before decontamination of spill area.

Large Spills: Access to the spill area should be restricted. Spread should be limited by diking spill area. Absorb spilled liquid with polypads or other suitable absorbent materials.

Place all spill residue in a double plastic bag or other containment and seal. Decontaminate the area thoroughly. Do not mix with wastes from other materials. Dispose of in accordance with applicable Federal, State, and local procedures For spills on water, contain, minimize dispersion and collect. Dispose of recovered material and report spill per regulatory requirements.

6.4. Reference to other sections

No additional information available

06/14/2017 EN (English US) 2/6

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: All employees who handle this material should be trained to handle it safely. Keep container tightly closed when not in use. As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors or mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Empty containers may contain residual product; therefore, empty containers should be handled with care.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dipropylene glycol monomethyl ether (34590-94-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	600 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	600 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	600 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	900 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm

Aluminum oxide (Al2O3) (1344-28-1)		
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)

8.2. Exposure controls

Appropriate engineering controls

: Local exhaust and general ventilation must be adequate to meet exposure standards.

Hand protection

Wear butyl rubber, Teflon™, Barricade™, Chemrel™, nitrile or similar gloves for routine industrial use. Use triple gloves for spill response. If necessary, refer to applicable regulations

and standards.

Eye protection

assist in equipment selection.

Skin and body protection

Wear suitable working clothes.

Respiratory protection

: If airborne concentrations are above the applicable exposure limits, use NIOSH approved $\,$

respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous.
Color : Opaque, white.
Odor : Lemon

Odor threshold : No data available

pH : 9 - 10

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 93 °C (>199.4 °F)

Relative evaporation rate (butyl acetate=1) : < 1

Flammability (solid, gas) : No data available

06/14/2017 EN (English US) 3/6

Safety Data Sheet

Vapor pressure : No data available

Relative vapor density at 20 °C : > 1
Specific gravity : 1.188
Solubility : Soluble.

: No data available Log Pow Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic No data available **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Exposure to incompatible chemicals.

10.5. Incompatible materials

Strong oxidizers, water-reactive materials.

10.6. Hazardous decomposition products

Silicon, aluminum and carbon oxides.

Respiratory or skin sensitization

Germ cell mutagenicity

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5400 μl/kg
LD50 dermal rabbit	9500 mg/kg
ATE US (oral)	5230 mg/kg body weight
ATE US (dermal)	9500 mg/kg body weight

Aluminum oxide (Al2O3) (1344-28-1)		
LD50 oral rat	> 5000 mg/kg	
Water (7732-18-5)		
LD50 oral rat	> 90 ml/kg	

Skin corrosion/irritation : Not classified

pH: 9 - 10 : Not classified

Serious eye damage/irritation : Not classifie pH: 9 - 10

Not classifiedNot classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified

06/14/2017 EN (English US) 4/6

Safety Data Sheet

Specific target organ toxicity – repeated

exposure

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Dipropylene glycol monomethyl ether (34590-	94-8)
Log Pow	-0.064 (at 20 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Dipropylene glycol monomethyl ether (34590-94-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ceramic materials and wares, chemicals (66402-68-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Aluminum oxide (Al2O3) (1344-28-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1 % (fibrous forms)

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

06/14/2017 EN (English US) 5/6

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Aluminum oxide (Al2O3) (1344-28-1)

- U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Flam. Liq. 4	Flammable liquids Category 4
H227	Combustible liquid

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/14/2017 EN (English US) 6/6