

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Akepox 5000 Component A**

Article number: 10681, 10682, 11635

UFI: KRS1-N0QQ-300H-46P0

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.  
+44 (171) 635 91 91  
National Poison Inform. Centre  
Medical Toxicology Unit  
Avalonley Road  
London SE14 5ER

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

Signal word

Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane  
Cyclohexanedimethanol diglycidyl ether

Hazard statements

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P261 Avoid breathing vapours.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 1)

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information: Contains epoxy constituents. May produce an allergic reaction.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	bis[4-(2,3-epoxypropoxy)phenyl]propane ----- Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	50-100%
CAS: 14228-73-0 EINECS: 238-098-4	Cyclohexanedimethanol diglycidyl ether ----- Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	12.5-25%
CAS: 2530-83-8 EINECS: 219-784-2 Reg.nr.: 01-2119513212-58	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane ----- Eye Dam. 1, H318 Aquatic Chronic 3, H412	1-5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General information: Take affected persons out into the fresh air.  
Position and transport stably in side position.  
Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Rinse out mouth and then drink plenty of water.
- Information for doctor: Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may cause health damage. Irritates respiratory tract, digestion system, eyes and skin: e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorhydrine and should avoid any further contact with this chemical.  
The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight  $\leq 300$ . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 2)

· **4.2 Most important symptoms and effects, both acute and delayed**

disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

· Hazards

Breathing difficulty  
Coughing  
Allergic reactions  
Danger of impaired breathing.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

\* **SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· Suitable extinguishing agents:CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)  
Hydrogen chloride (HCl)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:Wear fully protective suit.  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.· Additional informationCollect contaminated fire fighting water separately. It must not enter the sewage system.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

\* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation  
Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose of the material collected according to regulations.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 13 for disposal information.  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

\* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 3)

- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.  
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from reducing agents.  
Store away from foodstuffs.
- Further information about storage conditions: Store receptacle in a well ventilated area.  
Keep container tightly sealed.
- Storage class: 12
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

## · DNELs

**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB) 3.571 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB) 0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m <sup>3</sup> Air (ARB) 0.87 mg/m <sup>3</sup> Air (BEV)

**2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane**

Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	21 mg/kg bw/day (ARB) 12.5 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	21 mg/kg bw/day (ARB) 12.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	147 mg/m <sup>3</sup> Air (ARB) 43.5 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	147 mg/m <sup>3</sup> Air (ARB) 43.5 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

PNEC (wässrig)	10 mg/l (KA)
	0.0006 mg/l (MW)
	0.006 mg/l (SW)

(Contd. on page 5)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 4)

PNEC (fest)	0.018 mg/l (WAS) 0.065 mg/kg Trockengew (BO) 0.034 mg/kg Trockengew (MWS) 0.341 mg/kg Trockengew (SWS)
<b>2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane</b>	
PNEC (wässrig)	>10 mg/l (KA) 0.1 mg/l (MW) 1 mg/l (SW) 1 mg/l (WAS)
PNEC (fest)	0.13 mg/kg Trockengew (BO) 0.79 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.  
Apply solvent resistant skin cream before starting work.  
Clean skin thoroughly immediately after handling the product.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:  
Filter A/P2  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.  
After use of gloves apply skin-cleaning agents and skin cosmetics.  
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:  
STOKO EMULSION (<http://www.stoko.com>)  
Skin protection recommendation for skin cleaning after product handling:  
Kresto Classic (<http://debstoko.com>)  
Skin protection agent recommendation for skin aftercare:  
STOKO VITAN (<http://www.stoko.com>)  
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.  
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7


Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level  $\leq$  6, 480 min  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)  
Fluorocarbon rubber (Viton)  
Vitoject (KCL, Art\_No. 890)
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR  
Camatril (KCL, 730, 731, 732, 733)  
Chloroprene rubber, CR  
Camapren (KCL, Art\_No. 720, 722, 726)
- Not suitable are gloves made of the following materials: Leather gloves  
Strong material gloves
- Eye protection:  Tightly sealed goggles
- Body protection: Protective work clothing

**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties**· General Information· Appearance:

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic

· pH-value: Not applicable

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

· Flash point: Not applicable.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Vapour pressure at 20 °C: 2 hPa

· Density at 20 °C: 1.15 g/cm<sup>3</sup>

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: AkepoX 5000 Component A**

(Contd. of page 6)

· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u>	
<u>Dynamic at 20 °C:</u>	3,900 mPas
<u>Kinematic:</u>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used and stored according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	May produce violent reactions with bases and numerous organic substances including alcohols and amines. Reacts with acids. Exothermic polymerisation.
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	Irritant gases/vapours Carbon monoxide and carbon dioxide Hydrogen chloride (HCl)

**SECTION 11: Toxicological information**

· <b>11.1 Information on toxicological effects</b>	
· <u>Acute toxicity</u>	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Inhalative	LC50/4 h	>359 mg/l (rat)
------------	----------	-----------------

**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

Oral	LD50	15,000 mg/kg (rat)
Dermal	LD50	23,000 mg/kg (rabbit)

**14228-73-0 Cyclohexanedimethanol diglycidyl ether**

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

**2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane**

Oral	LD50	8,025 mg/kg (rat) (OECD 401)
	NOAEL-Werte	≥5 mg/kg (mouse)
		200 mg/kg (rabbit) (OECD 414)
Dermal	LD50	500 mg/kg (rat) (OECD 415)
	LD50	4,250 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>5.3 mg/l (rat) (OECD 403)
	NOAEC	0.225 mg/l (rat) (OECD 412)

· <u>Primary irritant effect:</u>	
· <u>Skin corrosion/irritation</u>	Causes skin irritation.
· <u>Serious eye damage/irritation</u>	Causes serious eye irritation.
· <u>Respiratory or skin sensitisation</u>	May cause an allergic skin reaction.
· <u>Additional toxicological information:</u>	
· <u>CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)</u>	
· <u>Germ cell mutagenicity</u>	Based on available data, the classification criteria are not met.

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

- |                                 |   |                    |
|---------------------------------|---|--------------------|
| <u>· Carcinogenicity</u>        | Based on available data, the classification criteria are not met. | (Contd. of page 7) |
| <u>· Reproductive toxicity</u>  | Based on available data, the classification criteria are not met. |                    |
| <u>· STOT-single exposure</u>   | Based on available data, the classification criteria are not met. |                    |
| <u>· STOT-repeated exposure</u> | Based on available data, the classification criteria are not met. |                    |
| <u>· Aspiration hazard</u>      | Based on available data, the classification criteria are not met. |                    |

**SECTION 12: Ecological information****· 12.1 Toxicity**· Aquatic toxicity:**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	1.8 mg/l (daphnia magna)
NOEC/21d	0.3 mg/l (daphnia magna)
EC50/72h	11 mg/l (selenastrum capricornutum)
LC50/96h	2 mg/l (Oncorhynchus mykiss)

**14228-73-0 Cyclohexanedimethanol diglycidyl ether**

LC0/96h	10 mg/l (piscis)
LC50/96h	13 mg/l (piscis)

**2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane**

EC50/96h	350 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
	>100 mg/l (Salmo gairdneri)
EC50	119 mg/l (green alge)
IC50	255 mg/l (Scenedesmus subspicatus)
EC50/48h	324 mg/l (daphnia magna)
EC10/5h	1,500 mg/l (pseudomonas putida)
ErC50/72h	350 mg/l (Selenastrum capricornutum)
ECO/96h	44 mg/l (Cyprinus carpio)
NOEC	>100 mg/kg (Klärschlamm: Atmungs-/Vermehrungshemmung) (OECD 209)
NOEC/21d	≥100 mg/l (daphnia magna) (OECD 211)
EC50/48h	324-710 mg/l (daphnia magna) (OECD 202)
EC50/72h	255 mg/l (Scenedesmus subspicatus)
LC50/96h	55 mg/l (Cyprinus carpio) (OECD 203)
	237 mg/l (Oncorhynchus mykiss)

**· 12.2 Persistence and degradability**

No further relevant information available.

**· 12.3 Bioaccumulative potential**

No further relevant information available.

**· 12.4 Mobility in soil**

No further relevant information available.

· Ecotoxicological effects:· Remark:

Toxic for fish

· Additional ecological information:· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

**· 12.5 Results of PBT and vPvB assessment**· PBT:

Not applicable.

· vPvB:

Not applicable.

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 8)

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Alcohol  
acetone

### SECTION 14: Transport information

#### · 14.1 UN-Number

· ADR, IMDG, IATA UN3082

#### · 14.2 UN proper shipping name

· ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)

· IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane), MARINE POLLUTANT

· IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)

#### · 14.3 Transport hazard class(es)

· ADR



· Class

9 (M6) Miscellaneous dangerous substances and articles.

· Label

9

· IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles.

· Label

9

#### · 14.4 Packing group

· ADR, IMDG, IATA III

#### · 14.5 Environmental hazards:

· Marine pollutant: Yes  
Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

· Special marking (IATA): Symbol (fish and tree)

#### · 14.6 Special precautions for user

· Hazard identification number (Kemler code): Warning: Miscellaneous dangerous substances and articles.  
90

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

**Trade name: Akepox 5000 Component A**

(Contd. of page 9)

· EMS Number:	F-A,S-F
· Stowage Category	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE), 9, III

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU	
· <u>Named dangerous substances - ANNEX I</u>	None of the ingredients is listed.
· <u>Seveso category</u>	E2 Hazardous to the Aquatic Environment
· <u>Qualifying quantity (tonnes) for the application of lower-tier requirements</u>	200 t
· <u>Qualifying quantity (tonnes) for the application of upper-tier requirements</u>	500 t
· <u>National regulations:</u>	
· <u>Information about limitation of use:</u>	Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.
· <u>Waterhazard class:</u>	Water hazard class 2 (Self-assessment): hazardous for water.
· <u>VOC EU</u>	0.0 g/l
· <b>15.2 Chemical safety assessment:</b>	A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· <u>Relevant phrases</u>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
· <u>Recommended restriction of use</u>	refer to Technical Data Sheet (TDS)
· <u>Department issuing SDS:</u>	Laboratory

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 7

Revision: 09.02.2021

### Trade name: Akepox 5000 Component A

(Contd. of page 10)

· Contact:

Elke Hake  
Fon ++49 (0)911 64296-59  
@mail E.Hake@akemi.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB