

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Akepox 1005 Component B**
- Article number: 10574, 10656, 10658, 13656, 13661, 13756
- UFI: WX83-Y028-V00R-0V5Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Reaction resin

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

Signal word

Danger

Hazard-determining components of labelling:

1,3-Cyclohexanedimethanamine
Benzyl alcohol
benzyl dimethylamine

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 1)

- Hazard statements H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
 - P101 If medical advice is needed, have product container or label at hand.
 - P102 Keep out of reach of children.
 - P103 Read carefully and follow all instructions.
 - P260 Do not breathe vapours.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P310 Immediately call a POISON CENTER/doctor.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-xxxx	1,3-Cyclohexanedimethanamine ----- ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	50-100%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol ----- ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 103-83-3 EINECS: 203-149-1 Index number: 612-074-00-7 Reg.nr.: 01-2119529232-48-xxxx	benzyl dimethylamine ----- ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 3, H331 ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	1-5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 2)

- After swallowing: Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- Protective equipment: Wear fully protective suit.
Wear self-contained respiratory protective device.
Mount respiratory protective device.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 3)

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

No special requirements.

· Information about storage in one common storage facility:

Not required.

· Further information about storage conditions:

Keep container tightly sealed.

· Storage class:

8 B

· **7.3 Specific end use(s)**

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities:

No further data; see item 7.

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

2579-20-6 1,3-Cyclohexanedimethanamine

Inhalative	DNEL (Langzeit-wiederholt)	0.00947 mg/m ³ Air (ARB)
------------	----------------------------	-------------------------------------

100-51-6 Benzyl alcohol

Oral	DNEL (Kurzzeit-akut)	25 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	47 mg/kg bw/day (ARB)
	DNEL (Langzeit-wiederholt)	28.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	8 mg/kg bw/day (ARB)
	DNEL (Kurzzeit-akut)	5.7 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	450 mg/m ³ Air (ARB)
		40.55 mg/m ³ Air (BEV)
		22 mg/m ³ Air (ARB)
		8.11 mg/m ³ Air (BEV)

103-83-3 benzyldimethylamine

Oral	DNEL (Langzeit-wiederholt)	1.25 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	2.3 mg/kg bw/day (ARB)
		1.25 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	1-14.6 mg/m ³ Air (ARB)
		43.75 mg/m ³ Air (BEV)

· PNECs

2579-20-6 1,3-Cyclohexanedimethanamine

PNEC (wässrig)	10 mg/l (KA)
	0.003 mg/l (MW)
	0.033 mg/l (SW)

100-51-6 Benzyl alcohol

PNEC (wässrig)	39 mg/l (KA)
	0.1 mg/l (MW)
	1 mg/l (SW)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 4)

PNEC (fest)	2.3 mg/l (WAS) 0.456 mg/kg Trockengew (BO) 0.527 mg/kg Trockengew (MWS) 5.27 mg/kg Trockengew (SWS)
103-83-3 benzyldimethylamine	
PNEC (wässrig)	534 mg/l (KA) 0.00048 mg/l (MW) 0.0048 mg/l (SW)
PNEC (fest)	0.0114 mg/kg Trockengew (BO) 0.0071 mg/kg Trockengew (MWS) 0.071 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Avoid contact with the eyes and skin.
Not necessary if room is well-ventilated.
Short term filter device:
Filter A/P2

· Protection of hands:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR
Nitrile rubber, NBR
Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Dermatril (Art_No. 740, 741, 742)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Dermatril (KCL, Art_No. 740, 741, 742)

· Not suitable are gloves made of the following materials:

Leather gloves
Strong material gloves

· Eye protection:

Tightly sealed goggles

· Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties· **9.1 Information on basic physical and chemical properties**· General Information· Appearance:

Form: Fluid
Colour: Light yellow
Odour: Characteristic

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 205 °C

· Flash point: Not applicable.

· Ignition temperature: 435 °C

· Decomposition temperature: > 250 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 6)

· <u>Explosion limits:</u>	
Lower:	1.3 Vol %
Upper:	13 Vol %
· <u>Vapour pressure at 20 °C:</u>	0.1 hPa
· <u>Density at 20 °C:</u>	0.97 g/cm ³
· <u>Solubility in / Miscibility with water:</u>	Not miscible or difficult to mix.
· <u>Viscosity:</u>	
Dynamic:	Not determined.
Kinematic at 20 °C:	15 s (DIN 53211/4)
· <u>Solvent content:</u>	
Organic solvents:	26.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if swallowed.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	758 mg/kg
Dermal	LD50	1,767 mg/kg
Inhalative	LC50/4 h	23.2 mg/l (rat)

2579-20-6 1,3-Cyclohexanedimethanamine

Oral	LD50	700 mg/kg (rat)
	LD0	>300 mg/kg (rat)
	LD100	2,000 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)

100-51-6 Benzyl alcohol

Oral	LD50	1,040 mg/kg (mouse)
		1,040 mg/kg (rabbit)
		1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
NOAEL		200 mg/kg (mouse)
		400 mg/kg (rat)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 7)

Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	11 mg/l (rat)
	LC50/48h	360 mg/l (daphnia magna) 645 mg/l (goo)

103-83-3 benzyldimethylamine

Oral	LD50	579 mg/kg (rat)
	NOAEL-Werte	150 mg/kg (rat) (OECD 407)
Dermal	LD50	1,660 mg/kg (rbt)
	LD50	1,660 µl/kg (rabbit)
Inhalative	LC50/4 h	2.06 mg/l (rat)
	LC50	2,052 mg/m ³ (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**Aquatic toxicity:**2579-20-6 1,3-Cyclohexanedimethanamine**

EC50	>1,000 mg/l (BES)
	90 mg/l (pseudomonas putida)
EC50/48h	65.4 mg/l (daphnia magna)
ErC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)
LC100/96h	180 mg/l (Leuciscus idus)
NOELR/72h	14.4 mg/l (Pseudokirchneriella subcapitata)
EC50/72h	58.4 mg/l (selenastrum capricornutum)
LC50/96h	130 mg/l (Leuciscus idus)
EBC50	58.4 mg/l (Pseudokirchneriella subcapitata)

100-51-6 Benzyl alcohol

EC50/24h	55-400 mg/l (daphnia magna)
EC50/96h	640 mg/l (Scenedesmus pluvialis)
EC50	2,100 mg/l (BES) (OECD 209)
	79 mg/l (Scenedesmus quadricauda)
EC10/16h	658 mg/l (pseudomonas putida)
EC50/48h	230 mg/l (daphnia magna) (OECD 202)
EC0	640 mg/l (Scenedesmus quadricauda)
EC50/16h	658 mg/l (pseudomonas putida)
EC50/30min	71.4 mg/l (Photobac. phosphoreum)
	400 mg/l (pseudomonas putida)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 8)

IC5/96h	640 mg/l (Scenedesmus quadricauda)
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)
NOEC/21d	51 mg/l (daphnia magna) (OECD211)
EC50/72h	770 mg/l (green alge) (OECD 201)
	770 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	645 mg/l (goo)
	10 mg/l (Iepomis macrochirus)
	460 mg/l (Pimephales promelas)

103-83-3 benzyldimethylamine

EC5/16h	749.6 mg/l (bacteria) (DIN 38412 Part.8)
EC10/16h	534 mg/l (bacteria) (DIN 38412 Part 8)
EC50/48h	>100 mg/l (daphnia magna) (EU EC C.2)
ErC50/72h	1.34 mg/l (green alge) (EU EC C.3)
NOEC/21d	0.789 mg/l (daphnia magna)
LC50/96h	37.8 mg/l (piscis) (OECD 203)
	38 mg/l (Leuciscus idus)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- Additional ecological information:

- General notes:

Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- **12.5 Results of PBT and vPvB assessment**

- PBT: Not applicable.

- vPvB: Not applicable.

- **12.6 Other adverse effects**

No further relevant information available.

* **SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- Uncleaned packaging:

- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

* **SECTION 14: Transport information**

- **14.1 UN-Number**

- ADR, IMDG, IATA

UN2735

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 9)

· 14.2 UN proper shipping name· ADR

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanedimethanamine, BENZYLDIMETHYLAMINE)

· IMDG, IATA

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Cyclohexanedimethanamine, BENZYLDIMETHYLAMINE)

· 14.3 Transport hazard class(es)· ADR· Class

8 (C7) Corrosive substances.

· Label

8

· IMDG, IATA· Class

8 Corrosive substances.

· Label

8

· 14.4 Packing group· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:· Marine pollutant:

No

· 14.6 Special precautions for user· Hazard identification number (Kemler code):

80

· EMS Number:

F-A,S-B

· Segregation groups

Alkalis

· Stowage Category

A

· Segregation Code

SG35 Stow "separated from" SGG1-acids

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:· ADR· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

E

· IMDG· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE, BENZYLDIMETHYLAMINE), 8, II

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 10)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· VOC EU

252.7 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

· Recommended restriction of use

refer to Technical Data Sheet (TDS)

· Department issuing SDS:

Laboratory

· Contact:

Elke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Acute Tox. 3: Acute toxicity - inhalation – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.11.2020

Version number 2

Revision: 13.11.2020

Trade name: Akepox 1005 Component B

(Contd. of page 11)

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB