



# SAFETY DATA SHEET

Precision Mastermade Paints, Inc.  
Joplin, MO 64804

## Section 1—Product and Company Identification

Product Number: LC4001  
Product Name: SP BLACK SHADOW  
Manufacturer's Name: Precision Mastermade Paints, Inc.  
8040 E. Alliance Parkway, Joplin, MO 64804  
Phone: 417-659-8900  
Fax: 417-659-8901  
Emergency: 800-535-5053  
Website:

## Section 2—Hazard(s) Identification

WARNING! Flammable liquid and vapor.



\*\*HMIS Codes<sup>2</sup>  
Health: 3  
Flammability: 2  
Reactivity: 0

Inhalation of may cause irritation of the upper respiratory system  
Causes skin and eye irritation  
Keep away from sources of ignition  
Do not breathe gas, fumes, vapor, or spray

## Section 3—Composition/Information on Ingredients

### PFSDS Components

% by Weight	CAS Number	ComponentName	Unit	Vapor-Pressure
0.13	100-41-4	Ethylbenzene		7.0 mmhg@20c
		ACGIH TLV	100 Mg/M3	
		ACGIH TLV STEL	125 Mg/M3	
		OSHA PEL	100 Mg/M3	
		OSHA PEL STEL	125 Mg/M3	
9.68	108-10-1	MIBK		26.4 hPa @ 25c
		ACGIH TLV	20 Mg/M3	
		ACGIH TLV STEL	75 Mg/M3	
		OSHA PEL	100 Mg/M3	
		OSHA PEL STEL	75 Mg/M3	

0.28	108-64-6	PMA		
		ACGIH TLV	100 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	100 ppm	
		OSHA PEL STEL	ppm	
0.26	123-86-4	n-butyl acetate		13.3 mbar 20 C
		ACGIH TLV	150 ppm	
		ACGIH TLV STEL	200 ppm	
		OSHA PEL	150 ppm	
		OSHA PEL STEL	200 ppm	
0.52	1330-20-7	Xylene		6.6 6.6 mmhg @ 20c
		ACGIH TLV	100 Mg/M3	
		ACGIH TLV STEL	150 Mg/M3	
		OSHA PEL	100 Mg/M3	
		OSHA PEL STEL	150 Mg/M3	
2.36	1333-86-4	Carbon Black		N/A
		ACGIH TLV	3.5 Mg/M3	
		ACGIH TLV STEL	Mg/M3	
		OSHA PEL	3.5 Mg/M3	
		OSHA PEL STEL	Mg/M3	
48.50	141-78-6	ETHYL ACETATE		
		ACGIH TLV	0 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	0 ppm	
		OSHA PEL STEL	ppm	
0.00	2-BUTOXYET	2-BUTOXYETHANOL		
		ACGIH TLV	20 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	25 ppm	
		OSHA PEL STEL	ppm	
23.95	67-64-1	Aceton		24.7 kPa @68f
		ACGIH TLV	500 Mg/M3	
		ACGIH TLV STEL	750 Mg/M3	
		OSHA PEL	750 Mg/M3	
		OSHA PEL STEL	1000 Mg/M3	

0.17	8052-41-3	Minerial Spirits		2 mmhg @ 20c
		ACGIH TLV	100 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	300 ppm	
		OSHA PEL STEL	ppm	
12.70	B72	ACRYLIC		
		ACGIH TLV	ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	0 ppm	
		OSHA PEL STEL	ppm	
0.02	BUTYL GLYC	BUTYL GLYCOLATE		
		ACGIH TLV	0 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	0 ppm	
		OSHA PEL STEL	ppm	
0.05	POLYETHER	POLYETHER		
		ACGIH TLV	0 ppm	
		ACGIH TLV STEL	ppm	
		OSHA PEL	0 ppm	
		OSHA PEL STEL	ppm	
0.24	SILANE	SILANE		
		ACGIH TLV	15 Mg/M3	
		ACGIH TLV STEL	Mg/M3	
		OSHA PEL	15 Mg/M3	
		OSHA PEL STEL	Mg/M3	

#### Section 4—First Aid Measures

<b>Eye Contact</b>	Remove contact lenses. Flush Eyes with large amounts of water for 15 minutes. Seek medical attention.
<b>Skin Contact</b>	Remove and launder contaminated clothing. Wash affected area thoroughly with soap and water. DO NOT use solvents or thinners.
<b>Inhalation</b>	Remove to fresh air. Keep warm and at rest. Restore breathing. Seek medical attention.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately. Provide SDS to medical personnel.
<b>Other</b>	Treat symptomatically. Contact poison control and/or seek medical attention as needed.

#### Section 5—Fire-Fighting Measures

<b>Extinguishing Media</b>	Carbon dioxide, Dry chemical, Foam, Water spray fog
<b>Unsuitable Extinguishing Media</b>	Avoid solid water stream as this may spread flammable liquid.
<b>Unusual Fire And Explosion Hazards</b>	Closed containers may explode or auto ignite when exposed to extreme heat. Vapors may spread long distances and ignite. Vapors may form explosive mixtures with air. During emergency conditions, exposure to burning product may cause health hazard. Symptoms may not be immediately apparent. Seek medical attention.
<b>Special Fire Fighting Procedures</b>	Full protective equipment and self-contained breathing apparatus should be used.

#### Section 6—Accidental Release Measures

<b>Personal Precautions</b>	Avoid inhalation, ingestion, and contact with skin or eyes. Remove all sources of ignition. Ventilate area
<b>Emergency Procedures</b>	Wear appropriate PPE (Personal Protective Equipment). Contact appropriate authorities needed, if necessary, for immediate action and containment. Emergency Contact Number: 800-535-5053
<b>Environmental Precautions</b>	Do not allow to enter drains or water courses. In case of sewer or drain contamination, contact local water company; water stream contamination, contact EPA
<b>Spill Clean Up Methods</b>	Ventilate area. Dike area with inert material. Remove product with inert absorbent, shovel or sweep up. Keep in suitable containment for approved disposal.

## Section 7—Handling and Storage

<b>Handling and Precautions</b>	Use appropriate protective equipment. Use only adequate ventilation; wear appropriate respirator when ventilation is inadequate. Do not breathe dust, vapor mist, or gas. Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not ingest or get on eyes, skin, and clothing. Eating, drinking, and smoking should be prohibited in areas where this material is handled, processed, and/or stored. Wash hands and face thoroughly before eating and drinking. Take precautionary measures against electrostatic discharge. Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion proof electrical ventilating, lighting, and material handling equipment. Follow US NFPA 30, "Flammable & Combustible Liquids Code," or other national, state, and local codes on the safe handling of flammable liquids
<b>Storage</b>	Store in designated flammable area NFPA 30 and OSHA 29 CFS 1910.106 approved. Store in original containers or approved container with complete and appropriate labeling. Keep out of direct sunlight and in a cool, dry, well ventilated area; away from incompatible materials, oxidizing materials, and food or drink. Store away from heat, spark, open flame, or all other ignition sources. Keep container tightly sealed until use. Open containers must be carefully resealed and stored upright to prevent leakage. Avoid exposure to oxygen; exposure may increase the instance of exothermic reaction, resulting in smoldering and potential combustion. Improper storage may result in spontaneous generation of heat and ignition.

## Section 8—Exposure Controls/Personal Protection

<b>Exposure Controls/Personal Protection</b>	Use only with adequate ventilation Avoid contact with skin and eyes. Avoid breathing vapor or spray mist. Respiratory protection may be needed if adequate ventilation cannot be obtained. Eye protection should be used at all times when using this product. Intentional misuse by deliberate concentration and inhalation of this product can be harmful or fatal.
--	---

## Section 9--

Appearance	Black Liquid
Odor	Aromatic
Odor Threshold	N/A
Ph	N/A
Melting Point	N/A
Boiling Point	171 F
Flash Point	-4 F
Evaporation Rate	2 (Ether=1)
Flammability	Class 3 Flammable
Flammability Limits	Lel. 1% Uel. 8%
Vapor Pressure	5 (mm Hg)
Vapor Density	3 (Air =1)
Relative Density	less than 1

Solubility	Not Soluable in Water
Partition Coefficient	N/A
Ignition Temp	N/A
Decomposition Temp	N/A
Viscosity	> Water

## Section 10—Stability and Reactivity

<b>Reactivity</b>	Stable under normal conditions
<b>Chemical Stability</b>	Stable under the recommended storage and handling conditions (see Section 7); hazardous polymerization will not occur.
<b>Conditions to avoid</b>	Freezing, direct sunlight, high heat. All possible ignition and spark or flame sources. Do not pressurize, cut, braze drill, grind, or heat containers. Avoid pure oxygen.
<b>Materials to avoid</b>	Keep away from oxidizing agents and strongly alkaline and acidic materials to prevent the possibility of exothermic reaction.
<b>Hazardous Decomposition</b>	Under normal conditions, hazardous decomposition should not occur. In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced.

## Section 11—Toxicological Information

Toxicology:

### PFSDS Toxicology

Component	ComponentName	
100-41-4	Ethylbenzene	LD50 Oral 3,500 mg/kg rat
IARC:	IARC listed as 2B 'Possible Carcinogen'	LD50 Dermal 20,574 mg/kg rabbit LC50 Inhalation 1,7623 mg/m3 rat
108-10-1	MIBK	LD50 Oral 2080 mg/kg LD50 Dermal >2000 mg/kg LC50 Inhalation LC 4hour >8.2 < 16.4 mg/l
108-64-6	PMA	LD50 Oral LD50 Dermal LC50 Inhalation
123-86-4	n-butyl acetate	LD50 Oral 14,130 mg/kg (rat) LD50 Dermal 8,770 mg/kg (guinea pig) LC50 Inhalation 6 h >1800ppm (rat)
1330-20-7	Xylene	LD50 Oral 4,300 mg/kg rat LD50 Dermal 1,700 mg/kg rabbit LC50 Inhalation 18,892 mg/m3 rat

1333-86-4	Carbon Black	LD50 Oral >8,000 mg/kg rat
IARC:	IARC listed as 2B 'Possible Carcinogen'	LD50 Dermal LC50 Inhalation
141-78-6	ETHYL ACETATE	LD50 Oral LD50 Dermal LC50 Inhalation
2-BUTOXYET	2-BUTOXYETHANOL	LD50 Oral LD50 Dermal LC50 Inhalation
67-64-1	Aceton	LD50 Oral >2000 mg/kg (rat) LD50 Dermal >2000mg/kg (rabbit) LC50 Inhalation >5000 ppm / 1 hour (rat)
8052-41-3	Minerial Spirits	LD50 Oral 5,000 mg/kg rat LD50 Dermal 3,000 mg/kg rabbit LC50 Inhalation 5,500 ppm 4 hour rat
B72	ACRYLIC	LD50 Oral LD50 Dermal LC50 Inhalation
BUTYL GLYC	BUTYL GLYCOLATE	LD50 Oral LD50 Dermal LC50 Inhalation
POLYETHER	POLYETHER	LD50 Oral LD50 Dermal LC50 Inhalation
SILANE	SILANE	LD50 Oral LD50 Dermal LC50 Inhalation

## Section 12—Ecological Information

### Ecotoxicity

This product has been assessed following the conventional method and is not classified as dangerous for the environment but contains substances dangerous for the environment. The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of relations made under the Enviromental Protection Act may apply to this use of this product.

## Section 13—Disposal Considerations

### Waste Disposal Method

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions, and any by-product should, at all times, comply with the requirements of

environmental protection and waste disposal legislation and any regional local authority requirements. This product should not be allowed to enter drains or watercourses, or be deposited where it can affect ground or surface waters and soil. Empty containers should be disposed of in accordance with local requirements.

### Section 14—Transport Information

UN Number	1263
UN Proper Shipping Name	Paint
Transport Class	3
Packing Group Number	II
Environmental Hazard	Yes
Special Precautions	Flammable Liquid

### Section 15—Regulatory Information

SARA

## PFSDS SARA

Component Name	CAS Number	% by Weight
Ethylbenzene	100-41-4	0.13
MIBK	108-10-1	9.68
Xylene	1330-20-7	0.52
ETHYL ACETATE	141-78-6	48.50

### Section 16—Other Information

SDS Date	02/21/2013
Revision	2