

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Lettering Colour Spray Antique Silver**

Article number: 11417

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Lacquer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Danger

Hazard-determining components of labelling:

acetone
n-butyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 1)

<ul style="list-style-type: none"> · <u>Precautionary statements</u> 	P101 P102 P103 P210 P211 P251 P260 P280 P305+P351+P338 P410+P412 P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Wear protective gloves / eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international regulations.
<ul style="list-style-type: none"> · <u>Additional information:</u> 	EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.	
<ul style="list-style-type: none"> · 2.3 Other hazards · <u>Results of PBT and vPvB assessment</u> · <u>PBT:</u> Not applicable. · <u>vPvB:</u> Not applicable. 		

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	12.5-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1, H220 Press. Gas (Comp.), H280	<12.5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane ⚠ Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	<12.5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane ⚠ Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	1-5%
CAS: 9004-70-0 Index number: 603-037-00-6	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose ⚠ Flam. Sol. 1, H228	1-5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 2)

CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised) ⚠ Flam. Sol. 1, H228; Water-react. 3, H261	1-5%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32; 01-2119486136-34	reaction mass of ethylbenzole and xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air. Position and transport stably in side position. Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation continues, consult a doctor.
- After eye contact: Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness
Gastric or intestinal disorders
Nausea
Coughing
Profuse sweating

- Information for doctor: Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously. Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
- Hazards Danger of impaired breathing.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 3)

- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- Protective equipment: Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- Storage class: 2 B

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

· DNELs

67-64-1 acetone

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	186 mg/kg bw/day (ARB) 62 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	1,210 mg/m ³ Air (ARB)
		200 mg/m ³ Air (BEV)

115-10-6 dimethyl ether

Inhalative	DNEL (Langzeit-wiederholt)	1,894 mg/m ³ Air (ARB) 471 mg/m ³ Air (BEV)
------------	----------------------------	--

123-86-4 n-butyl acetate

Oral	DNEL (Langzeit-wiederholt)	3.4 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	7 mg/kg bw/day (ARB) 3.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	960 mg/m ³ Air (ARB)
		859.7 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	480 mg/m ³ Air (ARB) 102.34 mg/m ³ Air (BEV)

reaction mass of ethylbenzole and xylene

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	180 mg/kg bw/day (ARB) 108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-442 mg/m ³ Air (ARB)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 5)

	DNEL (Langzeit-wiederholt)	260 mg/m ³ Air (BEV) 77 mg/m ³ Air (ARB) 14.8-65.3 mg/m ³ Air (BEV)
--	----------------------------	--

64-17-5 ethanol

Oral	DNEL (Langzeit-wiederholt)	87 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	950 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	343 mg/kg bw/day (ARB) 206 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,900 mg/m ³ Air (ARB)
		950 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	950 mg/m ³ Air (ARB) 114 mg/m ³ Air (BEV)

· PNECs

67-64-1 acetone

PNEC (wässrig)	100 mg/l (KA)
	1.06 mg/l (MW)
	10.6 mg/l (SW)
	21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO)
	3.04 mg/kg Trockengew (MWS)
	30.4 mg/kg Trockengew (SWS)

115-10-6 dimethyl ether

PNEC (wässrig)	180 mg/l (KA)
	0.016 mg/l (MW)
	0.155 mg/l (SW)
PNEC (fest)	0.045 mg/kg Trockengew (BO)
	0.069 mg/kg Trockengew (MWS)
	0.681 mg/kg Trockengew (SWS)

123-86-4 n-butyl acetate

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

reaction mass of ethylbenzole and xylene

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
PNEC (fest)	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

64-17-5 ethanol

PNEC (wässrig)	580 mg/l (KA)
	0.79 mg/l (MW)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 6)

PNEC (fest)	0.96 mg/l (SW) 2.75 mg/l (WAS) 0.63 mg/kg Trockengew (BO) 0.72 mg/kg Trockengew (FUT) 2.9 mg/kg Trockengew (MWS) 3.6 mg/kg Trockengew (SWS)
-------------	--

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 1, 10 min

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019


Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 7)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable:
Nitrile rubber, NBR
Camatril (KCL, Art_No. 730, 731, 732, 733)
- As protection from splashes gloves made of the following materials are suitable:
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
- Not suitable are gloves made of the following materials:
Natural rubber, NR
Leather gloves
Strong material gloves
- Eye protection:
 Tightly sealed goggles
- Body protection:
Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

- | | |
|---------|-----------------|
| Form: | Aerosol |
| Colour: | Silver-coloured |
| Odour: | Characteristic |

- | | |
|-------------|----------------|
| · pH-value: | Not applicable |
|-------------|----------------|

· Change in condition

- | | |
|--|-----------------------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | Not applicable, as aerosol. |

- | | |
|----------------|-----------------------------|
| · Flash point: | Not applicable, as aerosol. |
|----------------|-----------------------------|

- | | |
|-------------------------|--------|
| · Ignition temperature: | 240 °C |
|-------------------------|--------|

- | | |
|------------------------------|------------------------------|
| · Auto-ignition temperature: | Product is not selfigniting. |
|------------------------------|------------------------------|

- | | |
|-------------------------|--|
| · Explosive properties: | In use, may form flammable/explosive vapour-air mixture. |
|-------------------------|--|

· Explosion limits:

- | | |
|--------|------------|
| Lower: | 1.7 Vol % |
| Upper: | 26.2 Vol % |

- | | |
|-----------------------------|-----------|
| · Vapour pressure at 20 °C: | 8,300 hPa |
|-----------------------------|-----------|

- | | |
|---------------------|------------------------|
| · Density at 20 °C: | 0.76 g/cm ³ |
|---------------------|------------------------|

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

- | | |
|------------|-----------------|
| Dynamic: | Not determined. |
| | Not applicable |
| Kinematic: | Not determined. |

- | | |
|----------------------------|----------------|
| · Solvent separation test: | Not applicable |
|----------------------------|----------------|

· Solvent content:

- | | |
|-------------------|--------|
| Organic solvents: | 92.4 % |
|-------------------|--------|

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 8)

Solids content:	1.3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal	LD50	89,268 mg/kg (rabbit)
Inhalative	LC50/4 h	>112-115 mg/l (rat)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
	NOAEL-Werte	22,500 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat) >15,800 mg/kg (rbt)
	Inhalative	LC50/4 h 76 mg/l (rat) LC50/48h 2,262 mg/l (daphnia magna)

115-10-6 dimethyl ether

Inhalative	LC50/4h	164,000 mg/m ³ (rat)
	LC50/4 h	308 mg/l (rat)
	LC50/48h	>4,000 mg/l (daphnia magna)

106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

123-86-4 n-butyl acetate

Oral	LD50	10,800 mg/kg (rat) (OECD 423)
Dermal	LD50	>17,600 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m ³ (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

75-28-5 isobutane

Inhalative	LC50/4 h	>50 mg/l (rat)
------------	----------	----------------

7429-90-5 aluminium powder (stabilised)

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 9)

Inhalative	LC50/4h	>888 mg/m ³ (rat)
	LC50/4 h	>5 mg/l (rat)
	NOAEC	0.01 mg/l (rat)
reaction mass of ethylbenzole and xylene		
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m ³ (rat)
	LC50/4 h	6.35-6.7 mg/l (rat)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat) (OECD 401)
	NOAEL-Werte	>3,000 mg/kg (rat) (OECD 451)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4h	20,000 mg/m ³ (rat)
	LC50/4 h	120 mg/l (rat) (OECD 403)
	LC50/48h	5,012 mg/l (ceriodaphnia Dubai)
		12,340 mg/l (daphnia magna)
		8,150 mg/l (Leuciscus idus)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information· **12.1 Toxicity**· Aquatic toxicity:**67-64-1 acetone**

EC50/96h	7,200 mg/l (green alge)
	8,300 mg/l (piscis)
	8,300 mg/l (Iepomis macrochirus)
	7,500 mg/l (Selenastrum capricornutum)
EC50	1,700 mg/l (bacteria)
LC50	6,368 mg/l (piscis)
EC5/16h	1,700 mg/l (Pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (Microcystis aeruginosa)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
EC50/48h	3,400 mg/l (green alge)
	8,800 mg/l (daphnia magna)
NOEC	1,700 mg/kg (Pseudomonas putida)
	4,740 mg/kg (Selenastrum capricornutum)

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 10)

NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.)
LC50/96h	6,100 mg/l (daphnia magna)
	8,300 mg/l (lem)
	8,300 mg/l (Iepomis macrochirus)
	7,500 mg/l (Leuciscus idus)
	5,540 mg/l (Oncorhynchus mykiss)
	8,120 mg/l (Pimephales promelas)

115-10-6 dimethyl ether

EC50/96h	154.9 mg/l (green alge)
	>4,000 mg/l (poecilia reticulata)
EC50/48h	>4,000 mg/l (daphnia magna)
LC50/96h	>4,000 mg/l (poecilia reticulata)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (green alge)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)
	674 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.)
	81 mg/l (piscis)
	100 mg/l (Iepomis macrochirus)
	62 mg/l (Leuciscus idus) (DIN 38412)
	18 mg/l (pimephales promelas) (OECD 203)

reaction mass of ethylbenzole and xylene

LC50/24h	1 mg/l (daphnia magna)
EC50/48h	3.2-9.5 mg/l (daphnia magna)
NOEC	16 mg/l (BES)
	1.3 mg/l (piscis)
NOELR/72h	0.44 mg/l (green alge)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	2.2 mg/l (selenastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)
	8.9-16.4 mg/l (pimephales promelas)

64-17-5 ethanol

LC50/24h	11,200 mg/l (Salmo gairdneri)
EC50/48h	9,268-14,221 mg/l (daphnia magna)
	12,900 mg/l (Selenastrum capricornutum) (OECD 201)
EC0	6,500 mg/l (pseudomonas putida)
	5,000 mg/l (scenedesmus quadricauda)
EC10	11.5 mg/l (CHV)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 11)

EC50/72h	275 mg/l (CHV) (OECD 201)
LC50/96h	13,000 mg/l (Oncorhynchus mykiss) (OECD 203)
	15,300 mg/l (pimephales promelas)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- Recommendation: Non contaminated packagings may be recycled.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- Recommended cleansing agents: Alcohol
acetone

SECTION 14: Transport information

- **14.1 UN-Number**
- ADR, IMDG, IATA UN1950
- **14.2 UN proper shipping name**
- ADR 1950 AEROSOLS
- IMDG AEROSOLS
- IATA AEROSOLS, flammable

(Contd. on page 13)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 12)

· 14.3 Transport hazard class(es)· ADR

· Class 2 5F Gases.
 · Label 2.1

· IMDG, IATA

· Class 2.1
 · Label 2.1

· 14.4 Packing group· ADR, IMDG, IATA Void**· 14.5 Environmental hazards:**· Marine pollutant: No**· 14.6 Special precautions for user**

· Danger code (Kemler): -
 · EMS Number: F-D,S-U
 · Stowage Code SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre:
 Category A. For AEROSOLS with a capacity above 1 litre:
 Category B. For WASTE AEROSOLS: Category C, Clear of living
 quarters.
 · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except
 for division 1.4. For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2. For
 WASTE AEROSOLS: Segregation as for the appropriate
 subdivision of class 2.

**· 14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:· ADR

· Limited quantities (LQ) 1L
 · Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

· Transport category 2
 · Tunnel restriction code D

· IMDG

· Limited quantities (LQ) 1L
 · Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 13)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- VOC EU 702.5 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H261 In contact with water releases flammable gases.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2019

Version number 5

Revision: 03.04.2019

Trade name: Lettering Colour Spray Antique Silver

(Contd. of page 14)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 1: Flammable liquids – Category 1
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Sol. 1: Flammable solids – Category 1
 Water-react. 3: Substances and mixtures which in contact with water emit flammable gases – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 REACH directive 1907/2006/EC

- Sources

- * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC