

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Color Intensifier**
- Article number: 10887, 10888, 11855, 10886/10900
- UFI: SQD3-E5KM-Q31T-WCNW

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Application of the substance / the mixture: Protective impregnation
- No further relevant information available.

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstr. 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644556
e-mail info@akemi.de

- Further information obtainable from: Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.
+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS05 GHS08 GHS09

- Signal word: Danger

- Hazard-determining components of labelling:

Polydimethylsiloxane, hydroxy-terminated reaction product of trimethoxy methyl silane, and N-[3 - (trimethoxysilyl) propyl] -1,2-ethanediamine
2,2,4,6,6-pentamethylheptan
Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics
octadec-1-ene

- Hazard statements: H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 1)

· <u>Precautionary statements</u>	P101 P102 P103 P210 P261 P273 P280 P301+P310 P302+P352 P305+P351+P338 P403+P235 P405 P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours/spray. Avoid release to the environment. Wear protective gloves. IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.
-----------------------------------	---	--

· **2.3 Other hazards**· Results of PBT and vPvB assessment· PBT: Not applicable.· vPvB:

540-97-6 | Dodecamethylcyclohexasiloxan

SECTION 3: Composition/information on ingredients· **3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 13475-82-6 EINECS: 236-757-0 Reg.nr.: 01-2119490725-29	2,2,4,6,6-pentamethylheptan ----- Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	25-50%
EC number: 923-037-2 Reg.nr.: 01-2119471991-29-xxxx	Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics ----- Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	25-50%
CAS: 69430-37-1	Polydimethylsiloxane, hydroxy-terminated reaction product of trimethoxy methyl silane, and N-[3 - (trimethoxysilyl) propyl] -1,2-ethanediamine ----- Eye Dam. 1, H318 Skin Irrit. 2, H315	12.5-25%
CAS: 112-88-9 EINECS: 204-012-9	octadec-1-ene ----- Asp. Tox. 1, H304 Aquatic Chronic 4, H413	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**· **4.1 Description of first aid measures**

· General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 2)

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor: Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
 - a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
 - b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
 Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.

- **4.2 Most important symptoms and effects, both acute and delayed**
 - Breathing difficulty
 - Headache
 - Dizziness
 - Dizziness
 - Nausea
 - Profuse sweating
 - Danger of impaired breathing.

- Hazards
- **4.3 Indication of any immediate medical attention and special treatment needed**
 - If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - Formation of toxic gases is possible during heating or in case of fire.
 - In case of fire, the following can be released:
 - Carbon monoxide (CO)
 - Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- Protective equipment:
 - Do not inhale explosion gases or combustion gases.
 - Wear fully protective suit.
 - Wear self-contained respiratory protective device.
- Additional information
 - Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation
 - Keep away from ignition sources.
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from oxidising agents.
Store away from foodstuffs.
- Further information about storage conditions: Store receptacle in a well ventilated area.
Keep container tightly sealed.
- Storage class: 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
The lists valid during the making were used as basis.
- Additional information:
- **8.2 Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures: Do not eat, drink, smoke or sniff while working.
Apply solvent resistant skin cream before starting work.
Use skin protection cream for skin protection.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
- Respiratory protection: Filter AX
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 4)

Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

STOKODERM (<http://www.stoko.com>)

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level \leq 6, 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

Nitrile rubber, NBR

Camatril (KCL, Art_No. 730, 731, 732, 733)

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Not suitable are gloves made of the following materials:

Natural rubber, NR

Leather gloves

Strong material gloves

Eye protection:**Tightly sealed goggles**

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 5)

· Body protection: Protective work clothing**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

· <u>Form:</u>	Fluid
· <u>Colour:</u>	Colourless
· <u>Odour:</u>	Characteristic

· pH-value: Not applicable**· Change in condition**

· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Initial boiling point and boiling range:</u>	180 °C

· Flash point: 44 °C· Ignition temperature: 240 °C· Auto-ignition temperature: Product is not selfigniting.· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**· Explosion limits:**

· <u>Lower:</u>	0.6 Vol %
· <u>Upper:</u>	7 Vol %

· Vapour pressure at 20 °C: 1 hPa· Density at 20 °C: 0.78 g/cm³**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· Viscosity:

· <u>Dynamic:</u>	Not determined.
· <u>Kinematic at 20 °C:</u>	11 s (DIN 53211/4)

· Solvent content:· Organic solvents: 80.4 %· Solids content: 4.8 %**· 9.2 Other information**

No further relevant information available.

SECTION 10: Stability and reactivity**· 10.1 Reactivity**

No further relevant information available.

· 10.2 Chemical stability**· Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactionsReacts with strong oxidising agents.
Forms flammable gases/fumes.**· 10.4 Conditions to avoid**

No further relevant information available.

· 10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 6)

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

13475-82-6 2,2,4,6,6-pentamethylheptan

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/8h	>5 ppm (rat)

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/8h	>5 mg/l (rat)

69430-37-1 Polydimethylsiloxane, hydroxy-terminated reaction product of trimethoxy methyl silane, and N-[3 - (trimethoxysilyl) propyl] -1,2-ethanediamine

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

· Primary irritant effect:

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Additional toxicological information:

- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity**

· Aquatic toxicity:

13475-82-6 2,2,4,6,6-pentamethylheptan

IC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	>1,000 mg/l (daphnia magna)
LC50/96h	>1,000 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics

EL0/48h	1,000 mg/l (daphnia magna)
EL0/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
LL0/96h	1,000 mg/l (Oncorhynchus mykiss)
NOELR/72h	1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR/21d	<1 mg/l (daphnia magna)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 7)

· vPvB:

540-97-6 Dodecamethylcyclohexasiloxan

· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.· European waste catalogue

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 13* solvents

· Uncleaned packaging:· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.· Recommended cleansing agents: Alcohol
acetone**SECTION 14: Transport information**· **14.1 UN-Number**

· ADR, IMDG, IATA UN3295

· **14.2 UN proper shipping name**· ADR 3295 HYDROCARBONS, LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS
· IMDG HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons, C10-C12, Isoalkanes, <2% aromatics), MARINE POLLUTANT
· IATA HYDROCARBONS, LIQUID, N.O.S.· **14.3 Transport hazard class(es)**

· ADR



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG



· Class 3 Flammable liquids.

· Label 3

· IATA



· Class 3 Flammable liquids.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 8)

· <u>Label</u>	3
· 14.4 Packing group · <u>ADR, IMDG, IATA</u>	III
· 14.5 Environmental hazards: · <u>Marine pollutant:</u> · <u>Special marking (ADR):</u>	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · <u>Hazard identification number (Kemler code):</u> · <u>EMS Number:</u> · <u>Stowage Category</u>	Warning: Flammable liquids. 30 F-E,S-D A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>Transport category</u> · <u>Tunnel restriction code</u>	3 D/E
· <u>IMDG</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
 - Named dangerous substances - ANNEX I
 - Seveso category
 - Qualifying quantity (tonnes) for the application of lower-tier requirements
 - Qualifying quantity (tonnes) for the application of upper-tier requirements
 - REGULATION (EC) No 1907/2006 ANNEX XVII
- None of the ingredients is listed.
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- 200 t
- 500 t
- Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.01.2021

Version number 14

Revision: 14.01.2021

Trade name: Color Intensifier

(Contd. of page 9)

- VOC EU 625.2 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

- * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB