

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Akepox 2030 Component A**
- Article number: 10601, 10602, 10612, 10613, 10563, 10603, 10604, 10564, 10600, 10565, 10605, 10566, 10614, 11649
- UFI: KUF3-V0PP-000W-NED5

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER
Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS07 GHS09

Signal word

Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 1)

<ul style="list-style-type: none"> · <u>Precautionary statements</u> 	P101 P102 P103 P261 P273 P280 P302+P352 P305+P351+P338 P333+P313 P337+P313 P501	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. Avoid breathing vapours. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international regulations.
<ul style="list-style-type: none"> · 2.3 Other hazards · <u>Results of PBT and vPvB assessment</u> · <u>PBT:</u> Not applicable. · <u>vPvB:</u> Not applicable. 		

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-xxxx	bis[4-(2,3-epoxypropoxy)phenyl]propane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-0003	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	12.5-25%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41-0005	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<12.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

<ul style="list-style-type: none"> · <u>General information:</u> · <u>After inhalation:</u> · <u>After skin contact:</u> · <u>After eye contact:</u> · <u>After swallowing:</u> · <u>Information for doctor:</u> 	Take affected persons out into the fresh air. Position and transport stably in side position. Immediately remove any clothing soiled by the product. Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation. If skin irritation continues, consult a doctor. Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse out mouth and then drink plenty of water. Bisphenol-A based resins: Inhalation, swallowing or dermal incorporation may cause health damage. Irritates respiratory tract, digestion system, eyes and skin:
--	---

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 2)

e.g., cough, dyspnea, lacrimation, burning. May cause health interferences such as dermal changes, renal, hepatic damage, and blood count changes. May provoke skin allergies. Sensitized users can react towards very low concentrations of Bisphenol-A-Epichlorhydrine and should avoid any further contact with this chemical.

The sensitizing effect of epoxide based resins is mainly caused by the concentration of epoxy resin polymers with a specific molecular weight ≤ 300 . The observed allergic dermal and respiratory appearances should be treated symptomatically in dependence of the severity. An epoxy resin based allergic disease belongs to a cell mediated (interaction of lymphocytes) type IV allergy.

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
Dizziness
Headache
Dizziness
Nausea

· **Hazards**

Allergic reactions

Danger of impaired breathing.

Skin contact with polyester and epoxy resin solutions as ingredient of the product should be avoided due to risks of skin irritations or allergic skin appearances. If occasional hand contact can not be avoided, protection gloves, proper protection ointments and protective agents generating a protective layer on the skin were applied.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

* **SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:** Dispose of the material collected according to regulations. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

* SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed. Store in cool, dry place in tightly closed receptacles. Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle. Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from reducing agents. Store away from foodstuffs.
- **Further information about storage conditions:** Store receptacle in a well ventilated area. Keep container tightly sealed.
- **Storage class:** 12
- **7.3 Specific end use(s)** No further relevant information available.

* SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB)
Inhalative		0.0893 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	12.25 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m ³ Air (ARB)
		0.87 mg/m ³ Air (BEV)

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 4)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	DNEL (Langzeit-wiederholt)	6.25 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	104.15 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	62.5 mg/kg bw/day (BEV)
		29.39 mg/m ³ Air (ARB)
		8.7 mg/m ³ Air (BEV)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Oral	DNEL (Kurzzeit-akut)	0.83 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	1.7 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2.8 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	1.7 mg/kg bw/day (BEV)
		4.9 mg/m ³ Air (ARB)
		2.9 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	4.9 mg/m ³ Air (ARB)
		2.9 mg/m ³ Air (BEV)

· PNECs

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC (wässrig)	10 mg/l (KA)
	0.0006 mg/l (MW)
	0.006 mg/l (SW)
	0.018 mg/l (WAS)
PNEC (fest)	0.065 mg/kg Trockengew (BO)
	0.034 mg/kg Trockengew (MWS)
	0.341 mg/kg Trockengew (SWS)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

PNEC (wässrig)	10 mg/l (KA)
	0.0003 mg/l (MW)
	0.003 mg/l (SW)
	0.025 mg/l (WAS)
PNEC (fest)	0.237 mg/kg Trockengew (BO)
	0.029 mg/kg Trockengew (MWS)
	0.294 mg/kg Trockengew (SWS)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

PNEC (wässrig)	1 mg/l (KA)
	0.00115 mg/l (MW)
	0.0115 mg/l (SW)
	0.115 mg/l (WAS)
PNEC (fest)	0.223 mg/kg Trockengew (BO)
	0.0283 mg/kg Trockengew (MWS)
	0.283 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.· **8.2 Exposure controls**· Personal protective equipment:· General protective and hygienic measures:

Use skin protection cream for skin protection.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 5)

- Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- Respiratory protection: Not necessary if room is well-ventilated.
Short term filter device:
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKO EMULSION (<http://www.stoko.com>)
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (<http://debstoko.com>)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (<http://www.stoko.com>)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
-  Protective gloves
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves Butyl rubber, BR
Chloroprene rubber, CR
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level \leq 6, 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
Butyl rubber, BR
Butoject (KCL, Art_No. 897, 898)
Nitrile rubber, NBR
Camatril (KCL, Art_No. 730, 731, 732, 733)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 6)

- | | |
|---|--|
| <ul style="list-style-type: none"> · <u>As protection from splashes gloves made of the following materials are suitable:</u> · <u>Not suitable are gloves made of the following materials:</u> · <u>Eye protection:</u> · <u>Body protection:</u> | <p>Dermatril (Art_No. 740, 741, 742)
Chloroprene rubber, CR
Camapren (KCL, Art_No. 720, 722, 726)</p> <p>Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Chloroprene rubber, CR</p> <p>Leather gloves
Strong material gloves</p> <div style="text-align: center;">  </div> <p>Tightly sealed goggles</p> <p>Protective work clothing</p> |
|---|--|

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**General InformationAppearance:

- | | |
|---------|----------------------------------|
| Form: | Pasty |
| Colour: | Different according to colouring |
| Odour: | Characteristic |

pH-value:	Not applicable
-----------	----------------

Change in condition

- | | |
|--|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | >200 °C |

Flash point:	Not applicable.
--------------	-----------------

Ignition temperature:	>300 °C
-----------------------	---------

Decomposition temperature:	> 200 °C °C
----------------------------	-------------

Auto-ignition temperature:	Product is not selfigniting.
----------------------------	------------------------------

Explosive properties:	Product does not present an explosion hazard.
-----------------------	---

Vapour pressure at 20 °C:	2 hPa
---------------------------	-------

Density at 20 °C:	1.52 g/cm ³
-------------------	------------------------

Solubility in / Miscibility with water:	Not miscible or difficult to mix.
---	-----------------------------------

Viscosity:

- | | |
|-------------------|-----------------|
| Dynamic at 20 °C: | 70,000 mPas |
| Kinematic: | Not determined. |

Solvent content:

Solids content:	83.0 %
-----------------	--------

9.2 Other information	No further relevant information available.
-----------------------	--

SECTION 10: Stability and reactivity

10.1 Reactivity	No further relevant information available.
-----------------	--

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 7)

- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 - May produce violent reactions with bases and numerous organic substances including alcohols and amines.
 - Reacts with strong acids.
 - Reacts with reducing agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

Oral	LD50	15,000 mg/kg (rat)
Dermal	LD50	23,000 mg/kg (rabbit)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl]oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Oral	LD50	2,190 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**· Aquatic toxicity:**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	1.8 mg/l (daphnia magna)
NOEC/21d	0.3 mg/l (daphnia magna)
EC50/72h	11 mg/l (selenastrum capricornutum)
LC50/96h	2 mg/l (Oncorhynchus mykiss)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 8)

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

EC50/48h	2.55 mg/l (daphnia magna)
EC50/72h	1.8 mg/l (green alge)
LC50/96h	2.54 mg/l (piscis)

933999-84-9 Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

EC50/48h	23.1 mg/l (green alge) 47 mg/l (daphnia magna)
LC50/96h	30 mg/l (Leuciscus idus)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Ecotoxicological effects:
Remark:

Toxic for fish

Additional ecological information:
General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

12.5 Results of PBT and vPvB assessment
PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:
Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleansing agents:
Alcohol
acetone
SECTION 14: Transport information
14.1 UN-Number
ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name
ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane, Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 9)

· IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane,
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane),
MARINE POLLUTANT

· IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane,
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane)

· **14.3 Transport hazard class(es)**· ADR· Class

9 (M6) Miscellaneous dangerous substances and articles.

· Label

9

· IMDG, IATA· Class

9 Miscellaneous dangerous substances and articles.

· Label

9

· **14.4 Packing group**· ADR, IMDG, IATA

III

· **14.5 Environmental hazards:**· Marine pollutant:

Yes

· Special marking (ADR):

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

· Hazard identification number (Kemler code):

90

· EMS Number:

F-A,S-F

· Stowage Category

A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:· ADR· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG· Limited quantities (LQ)

5L

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 10)

· <u>Excepted quantities (EQ)</u>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <u>UN "Model Regulation":</u>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, REACTION MASS OF 2,2'-[METHYLENEBIS(4,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE AND [2-({2-[4-(OXIRAN-2-YLMETHOXY)BENZYL]PHENOXY} METHYL)OXIRANE AND [2,2'-[METHYLENEBIS(2,1-PHENYLENEOXYMETHYLENE)]DIOXIRANE), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 0.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.03.2021

Version number 19

Revision: 03.03.2021

Trade name: Akepox 2030 Component A

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB