

Safety Data Sheet According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

FILA MP90 Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use ANTI-STAIN PROTECTIVE SOLVENT BASED FOR POLISHED SURFACE

Identified Uses Industrial Professional Consumer Uses 1.3. Details of the supplier of the safety data sheet Fila Chemicals USA 10800 NW 21st St Ste # 170 Full address District and Country Miami, FL 33172

Tel. (305) 513-0708 Fax. (305) 513-0728

filausa@filasolutions.com

e-mail address of the competent person

responsible for the Safety Data Sheet sds@filasolutions.com

1.4. Emergency telephone number

For urgent inquiries refer to 800-424-9300 CHEMTREC

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

dizziness.

Classification and Hazard Statement

Hazard pictograms:

Flammable liquid, category 3 Flammable liquid and

vapour. May be fatal if Aspiration hazard, category 1 swallowed and enters airways. Specific target organ toxicity - single exposure, category 3 May cause

drowsiness or







Signal words:

Danger

Hazard statements:

FIR	Fila Chemicals USA	Revision nr. 5
		Dated 7/16/2020
	MP90	Printed on 16/07/2020
	••	Page n. 2/12
		Replaced revision:4 (Dated: 5/6/2019)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P242 Use only non-sparking tools.

P280 Wear protective gloves/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.
P240 Ground/ bond container and receiving equipment.
P243 Take precautionary measures against static discharge.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Response:

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P301+P310 IF SWALLOWED: immediately call a POISON CENTER/ doctor.

P312 Call a POISON CENTER/ doctor/ if you feel unwell.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: use foam, powder or Carbon Dioxide to extinguish.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container in accordance with local/ regional/ national/ international regulation.

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:	Trade Secret:
DISTILLATES (PETROLEUM), LIGHT FRACTION			
CAS 64742-47-8	85 ≤ x < 90	Flammable liquid, category 3 H226, Aspiration hazard, category 1 H304, Specific target organ toxicity - single exposure, category 3 H336	§
EC		exposure, satisfiery of nood	
INDEX -			
Nonane			
CAS 111-84-2	4 ≤ x < 5	Flammable liquid, category 3 H226, Aspiration hazard, category 1 H304, Specific target organ toxicity - single exposure, category 3 H336	§
EC		oxposule, sulegely citiess	
INDEX -			
C11-C15 ISO-ALKANES			
CAS 90622-58-5	0.7 ≤ x < 1	Aspiration hazard, category 1 H304, Specific target organ toxicity - single exposure, category 3 H336	§

AND THE STATE OF T	Fila Chemicals USA	Revision nr. 5
		Dated 7/16/2020
	MP90	Printed on 16/07/2020
		Page n. 3/12
		Replaced revision:4 (Dated: 5/6/2019)

EC 292-460-6

INDEX -

Note: Upper limit is not included into the range.

§ the exact percentage (concentration) of composition has been withheld as a trade secret.

The full wording of the hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/ attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/ attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).


6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions



The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

JSA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).

DISTILLATES (PETROLEUM), LIGHT FRACTION

Threshold Limit Value	9				
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
CAL/OSHA-PEL	USA	1200	197		

Nonane

	inresnoid Limit value					
	Туре	Country	TWA/8h		STEL/15min	
					, ,	
			mg/m3	ppm	mg/m3	ppm
	0.41 /0.0114	1104	4.05	000		
	CAL/OSHA	USA	1.05	200		
-	NIOSH	USA	1050	200		
	NIOSH	USA	1030	200		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

TLV of solvent mixture: 262 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired

Fila Chemicals USA	Revision nr. 5
	Dated 7/16/2020
MP90	Printed on 16/07/2020
55	Page n. 5/12
	Replaced revision:4 (Dated: 5/6/2019)

through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Generally not necessary. In case of prolonged contact use gloves to protect hands with category III work gloves (ref. Standard EN 374).

Recommended material: Nitrile, minimum 0.38 mm thick or equivalent barrier material with a high level performance for continuous contact use conditions, with a minimum permeability time of 480 minutes according to the CEN EN 420 and EN standard 374.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (eg TLV-TWA) of the substance or one or more of the substances present in the product is exceeded, it is advisable to wear a mask with type A filter whose class (1, 2 or 3) must be chosen in relation to the limit concentration of use (see standard EN 14387). If there are gases or vapors of a different nature and/ or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided.

The use of respiratory protective equipment is necessary if the technical measures adopted are not sufficient to limit the worker's exposure to the threshold values taken into consideration. However, the protection offered by the masks is limited.

In the event that the substance considered is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an open circuit compressed air breathing apparatus (see standard EN 137) or a breathing apparatus outdoor air (see standard EN 138). For the correct choice of the respiratory protection device, refer to the EN 529 standard. The activities with great dispersion leading to a probable release of aerosols (eg use with spray application with airless system) are reserved for EXCLUSIVE PROFESSIONAL USE. Use additional protective measures: use an approved air-powered respirator operating at positive pressure. Air-fed respirators with a waste bottle may be appropriate when oxygen levels are inadequate, if the risks of gases/ vapors are low, and if the capacity/ values of air-purifying filters can be exceeded. For high airborne concentrations, also use waterproof clothing to protect the skin and protect the face.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Activities involving widespread dispersion that may lead to extensive aerosol emissions (e.g. use with airless system spray applications) are reserved for PROFESSIONAL USE ONLY. As a further protective measure, use an approved positive pressure supplied-air respirator (SAR). Supplied-air respirators (SARs), fitted with a discharge bottle, may be appropriate when oxygen levels are insufficient, if the gas/vapour risks are low or if the capacity/values of the air purification filters may be exceeded.

For high airborne concentrations, also use waterproof clothing to protect the skin and face protection.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid
Colour colourless

Odour Light hydrocarbon smell

Odour threshold Not available
pH Not available
Melting point / freezing point Not available
Initial boiling point Not available
Boiling range Not available
Flash point 40 °C

Evaporation Rate

Flammability of solids and gases

Lower inflammability limit

Upper inflammability limit


Not available

Lower explosive limit

Not available

Upper explosive limit

Not available



Not available Vapour pressure Vapour density Not available Relative density Not available Solubility Not available Partition coefficient: n-octanol/water Not available Not available Auto-ignition temperature Decomposition temperature Not available Not available Viscosity Explosive properties not applicable Oxidising properties not applicable

9.2. Other information

VOC: 94,00 % - 0,00 g/litre

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects


Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure



Information not available

Interactive effects

Information not available

ACUTE TOXICITY

DISTILLATES (PETROLEUM), LIGHT FRACTION LD50 (Oral) > 5000 mg/kg rat LD50 (Dermal) > 5000 mg/kg rabbit

LC50 (Inhalation) > 4951 mg/l/4h rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

DISTILLATES (PETROLEUM), LIGHT

EC50 - for Algae / Aquatic Plants

FRACTION


LC50 - for Fish

EC50 - for Crustacea

> 1000 mg/l/96h Oncorhynchus mykiss

1000 mg/l/48h Daphnia magna

> 1000 mg/l/72h Pseudokirchneriella subcapitata



12.2. Persistence and degradability

DISTILLATES (PETROLEUM), LIGHT

FRACTION

Rapidly degradable

Nonane

Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

Product is regulated under DOT/TDG and other transportation regulations.

Rail and Truck Shipments

DOT Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (ISODECANE and n-DECANE)

DOT ID Number UN 3295

DOT Hazard Class & Packing

3 (Flammable liquid), III

DOT Shipping Label Flammable

TDG Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (ISODECANE and n-DECANE)

TDG ID Number UN 3295

TDG DOT Hazard Class & Packing

3 (Flammable liquid), III

TDG Shipping Label Flammable

Water Shipments

HYDROCARBONS, LIQUIDS, N.O.S. (ISODECANE and n-DECANE) **IMO Shipping Name:**

IMO ID Number UN 3295


IMO DOT Hazard Class & Packing

Group

3 (Flammable liquid), III

IMO Shipping Label 3 (Flammable)

IMO EMS F-E, S-D



Air Shipments IATA Shipping Name: HYDROCARBONS, LIQUIDS, N.O.S. (ISODECANE and n-DECANE)

IATA ID Number UN 3295

IATA DOT Hazard Class & Packing 3 (Flammable liquid), III

Group

IATA Shipping Label 3 (Flammable)

IATA Packing Instructions 310 Maximum quantity: 220 L Cargo:

Passenger: 309 Maximum quantity: 60 L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

Clean Air Act Section 112(b):

34590-94-8 DIPROPYLENE GLYCOL MONOMETHYL ETHER (Glycol

ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act -

Priority Pollutants:

No component(s) listed.

Clean Water Act -

Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

DIPROPYLENE GLYCOL 34590-94-8

MONOMETHYL ETHER (Glycol ethers)

METHANOL

67-56-1 EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

67-56-1 METHANOL

EPCRA 313 TRI:

34590-94-8 DIPROPYLENE GLYCOL

MONOMETHYL ETHER (Glycol

ethers)

67-56-1 METHANOL

RCRA Code:

67-56-1 METHANOL

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

111-84-2 Nonane

34590-94-8 DIPROPYLENE GLYCOL

MONOMETHYL ETHER (Glycol

ethers)

Minnesota:

111-84-2 Nonane

34590-94-8 DIPROPYLENE GLYCOL

MONOMETHYL ETHER (Glycol

ethers)

New Jersey:

111-84-2 Nonane

34590-94-8 DIPROPYLENE GLYCOL

MONOMETHYL ETHER (Glycol

ethers)

New York:

No component(s) listed.

Pennsylvania:

111-84-2 Nonane

34590-94-8 DIPROPYLENE GLYCOL

MONOMETHYL ETHER (Glycol

ethers)

California:

111-84-2 Nonane

34590-94-8 DIPROPYLENE GLYCOL


MONOMETHYL ETHER (Glycol

ethers)

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations



Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
 EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety

FASS turted our statution	Fila Chemicals USA	Revision nr. 5
		Dated 7/16/2020
	MP90	Printed on 16/07/2020
	00	Page n. 12/12
		Replaced revision:4 (Dated: 5/6/2019)

- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the criteria set out in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

08.