

# SAFETY DATA SHEET

Issue Date 27-Feb-2015 Revision Date 12-Jan-2021 Version 1

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name New Energy NL405

Other means of identification

Product Code JC-013-005

Details of the supplier of the safety data sheet

Company Name Newline Industries LLC

111 Highline Drive Longwood, FL 32750 407-480-5464

Emergency telephone number

Emergency Telephone INFOTRAC 1-800-535-5053

# 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 5
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

### Label elements

### **Emergency Overview**

# **Danger**

### **Hazard statements**

Harmful if swallowed
May be harmful in contact with skin
Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer

Causes damage to organs through prolonged or repeated exposure



Appearance Clear Physical state Liquid Odor Butyl cellosolve

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/gas/mist/vapors/spray

# **Precautionary Statements - Response**

Specific Treatment (See Section 4 on the SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

### **Precautionary Statements - Storage**

Store locked up

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

### Other Information

- Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life

Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
2-butoxyethanol	111-76-2	30-60	*
Orange Terpenes	5989-27-5	1-5	*
Mineral Spirits (Rule 66)	68551-16-6	1-5	*
2-Propanol	67-63-0	1-5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

First aid measures

**General advice** Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

If symptoms persist, call a physician.

**Skin Contact**Consult a physician if necessary. Wash contaminated clothing before reuse. Wash off

immediately with plenty of water. Wash off immediately with soap and plenty of water. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

**Inhalation** Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer

artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of

accidental inhalation of vapors. If symptoms persist, call a physician.

Ingestion Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Clean mouth with

water and drink afterwards plenty of water. Never give anything by mouth to an

unconscious person. Call a physician. Do NOT induce vomiting.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Any additional important symptoms and effects are described in Section 11: Toxicology

Information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** May cause sensitization of susceptible persons. Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **6. ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak. Use personal protective equipment as required.

#### Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. Do not flush into

surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover

powder spill with plastic sheet or tarp to minimize spreading. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not

eat, drink or smoke when using this product. Use with local exhaust ventilation. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly

labeled containers.

Incompatible materials None known based on information supplied.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

**Exposure Guidelines** Exposure guidelines noted for ingredient(s).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³	
Mineral Spirits (Rule 66) 68551-16-6	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³	
2-Propanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers, Eyewash stations & Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles. Face protection shield.

**Skin and body protection**Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Handle in accordance with good industrial hygiene and safety practice. Wash contaminated

clothing before reuse. When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended. Wear suitable gloves and eye/face

protection.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state Liquid
Appearance Clear
Color Colorless
Odor Butvl cellosolve

Odor threshold No Information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** Not Applicable

Specific Gravity No Information available

Viscosity Water Thin

Melting point/freezing point No Information available

Flash point No Information available

Boiling point / boiling range No Information available

Evaporation rate

Flammability (solid, gas) No data available

Flammability Limits in Air

Upper flammability limit:No Information availableLower flammability limit:No Information availableVapor pressureNo Information availableVapor densityNo Information available

Water solubility Complete

Partition coefficientNo Information availableAutoignition temperatureNo Information availableDecomposition temperatureNo Information available

**Other Information** 

Density Lbs/Gal No Information available

VOC Content (%) 53.4

# 10. STABILITY AND REACTIVITY

Reactivity

No data available

### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Extremes of temperature and direct sunlight.

#### Incompatible materials

None known based on information supplied.

### **Hazardous Decomposition Products**

None known based on information supplied.

### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

Inhalation No data available. Avoid breathing vapors or mists. May cause central nervous system

depression with nausea, headache, dizziness, vomiting, and incoordination.

**Eye contact** Severely irritating to eyes.

**Skin Contact** May be harmful in contact with skin.

**Ingestion** No data available. May be harmful if swallowed. Do not taste or swallow. Harmful if

swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat)4 h = 486 ppm (Rat)4 h
Orange Terpenes 5989-27-5	= 4400 mg/kg (Rat) = 5200 mg/kg (Rat) = 5300 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
2-Propanol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³ (Rat ) 4 h

#### Information on toxicological effects

**Symptoms** No Information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No Information available.
No Information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

			. againer material and mile	,
Chemical Name	ACGIH	IARC	NTP	OSHA
2-butoxyethanol 111-76-2	A3	Group 3	-	-
Orange Terpenes 5989-27-5	-	Group 3	-	X
2-Propanol 67-63-0	-	Group 3	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 -Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No Information available.

**STOT - single exposure**STOT - repeated exposure
No Information available.
No Information available.

Chronic toxicity Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated

exposure. May cause adverse effects on the bone marrow and blood-forming system. May

cause adverse liver effects.

Target organ effects Blood, Central nervous system, EYES, hematopoietic system, Kidney, Liver, Respiratory

system, Skin.

Aspiration hazard No Information available.

# Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 990.20 mg/kg ATEmix (inhalation-dust/mist) 3.30 mg/l

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-butoxyethanol 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Orange Terpenes 5989-27-5	-	0.619 - 0.796: 96 h Pimephales promelas mg/L LC50 flow-through 35: 96 h Oncorhynchus mykiss mg/L LC50	-
2-Propanol 67-63-0	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	11130: 96 h Pimephales promelas mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
Sodium Sulfate 7757-82-6	-	13500 - 14500: 96 h Pimephales promelas mg/L LC50 3040 - 4380: 96 h Lepomis macrochirus mg/L LC50 static 13500: 96 h Lepomis macrochirus mg/L LC50 6800: 96 h Pimephales promelas mg/L LC50 static	2564: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No Information available.

# **Bioaccumulation**

No Information available.

Chemical Name	Partition coefficient
2-butoxyethanol 111-76-2	0.81
2-Propanol 67-63-0	0.05

Other adverse effects No Information available

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Orange Terpenes 5989-27-5	Toxic
2-Propanol 67-63-0	Toxic Ignitable

# 14. TRANSPORT INFORMATION

The basic description below is specific to the container size. This information is provided for at a glance DOT information. Please refer to the container and/or shipping papers for the appropriate shipping description before tendering this material for shipment. For additional information, please contact the distributor listed in section 1 of this SDS.

**DOT** 

UN/ID No. NA1993

Proper Shipping Name Combustible Liquid, n.o.s.(Ethylene Glycol Monobutyl Ether)

Hazard Class 8
Packing Group PG III

Special Provisions DOT Label/Placard Exemption 173.150(f) applies

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# US Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
2-butoxyethanol - 111-76-2	1.0	
2-Propanol - 67-63-0	1.0	

# SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

# CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

### US State Regulations

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-butoxyethanol 111-76-2	X	X	X
Orange Terpenes 5989-27-5	Х	-	-
Mineral Spirits (Rule 66) 68551-16-6	X	X	X
2-Propanol 67-63-0	X	X	X
Sodium Sulfate 7757-82-6	-	X	X

#### U.S. EPA Label Information

#### EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION					
<u>NFPA</u>	Health hazards 2	Flammability 0	Instability 0	Physical and Chemical	
HMIS	Health hazards 2	Flammability 0	Physical hazards 0	Properties - Personal protection B	
Issue Date	27-Feh-20	015			

 Issue Date
 27-Feb-2015

 Revision Date
 12-Jan-2021

**Revision Note** 

No Information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**