

PRO SERIES GREEN CA GLUE 20Z. THIN

SAFETY DATA SHEET

Product number	500905
Product identifier	GranQuartz Pro Series CA
Company information	GranQuartz
	3850 Steve Douglas Blvd Norcross, GA 30093
Company phone	General Assistance (800) 458-6222

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA & Canada)

2. Hazard(s) identification

1. Identification

WARNING:	BONDS SKIN IN SECONDS.	
	COMBUSTIBLE LIQUID.	
	CAUSES EYE IRRITATION.	
	MAY CAUSE RESPIRATORY IRRITATIO	N.
		Category 4 Category 2B
Physical hazards	Flammable aerosols	Category 3
Health hazards	Serious eye damage/eye irritation	Calegory 3
	Specific target organ toxicity, single expo	osure
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified	
Label elements	PIC	CTOGRAM(S)
	•	!

EMERGENCY OVERVIEW

Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces – no smoking. Avoid breathing vapors, mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well ventilated area. Wear protective gloves, eye protection and face protection.

Response: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or a physician if victim feels unwell. IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing if irritation persists. Get medical attention. IN CASE OF FIRE: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well ventilated area. Keep container tightly closed as product will react with moisture

Disposal: Dispose of contents in accordance with Federal, State or local environmental regulations.

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a w ell- ventilated area. Wear protective gloves, eye protection, and face protection.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use foam, drychemical or carbon dioxide to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

3. Composition/information on ingredients

Hazardous Component(s)	CAS Number	Percentage
Ethyl 2-cyanoacrylate	7085-85-0	> 80 - 90

4. First-aid measures

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin contact: Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heatby a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warmwater by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.

Ingestion: Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.

Symptoms: See Section 11.

5. Fire-fighting measures

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.

Product name: Nitro Pro Series CA Activator

Unusual fire or explosion hazards: None

Hazardous combustion products: Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

6. Accidental release measures

Environmental precautions: Ventilate area. Do not allow product to enter sew er or waterways.

Clean-up methods: Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. Handling and storage

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods.Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage: For safe storage, store between -20 °C (-4°F) and 50 °C (122°F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. Exposure controls/personal protection

Employers should complete an assessment of all work places to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	1 ppm STEL 0.2 ppm TWA (Respiratory sensitization) (Dermal sensitization)	None	None	None
Engineering controls:	insuffic	sitive dow n-draft exh ientto maintain vapor ire limits.		
Respiratory protection:	Use a N	IIOSH approved air-puri	fying respirator with an o	rganic vapor cartridge.
Eye/face protection:	protect	goggles or safety glas ion shouldbe used if t t exists.		
Skin protection:		rile gloves and aprons PVC, nylon or cottor	<i>,</i>	vent contact. Do

9. Physical and chemical properties

Physical state: Liquid, transparent Color: Colorless, Straw Odor: Irritating Odor threshold: Not available. pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/range: Not available. Vapor density: Not available. Vapor density: Not available. Flash point: 80 - 93 °C (176°F - 199.4 °F) Flammable/Explosive limits - low er: Not available. Flammable/Explosive limits - upper: Not available. Flammable/Explosive limits - upper: Not available. Flammable/Explosive limits - upper: Not available. Flammablity: Not applicable Evaporation rate: Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water):Not available. VOC content: < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated)

Product name: Nitro Pro Series CA Activator

Decomposition temperature: Not available.

10. Stability and reactivity

 Stability: Stable under recommended storage conditions.

 Hazardous reactions:
 Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

 Hazardous Decomposition Products: None
 Incompatible materials: Water, amines, alkalis and alcohols.

 Reactivity: Not available.
 Conditions to avoid: Spontaneous polymerization.

11. Toxicological information

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest

Skin contact: May cause skin irritation. Bonds skin in seconds. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response rare.

Eye contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected to be harmful by ingestion

Hazardous Component(s)	LD50s and LC50	LD50s and LC50s		and Delayed Health Effects
Ethyl 2-cyanoacrylate	None Irritant, Allergen, Respiratory		t, Allergen, Respiratory	
Hazardous Component(s)	NTP Carcinogen	IARC Ca	rcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	N	0	No

12. Ecological information

Not available

13. Disposal considerations

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Dispose of this material and its container at hazardous or special waste collectionpoint. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

14. Transport information

U.S.

Department of Transportation Grou	Ind (49 CFR)
Proper shipping name:	Combustible liquid, n.o.s. (Cyanoacrylate ester)
Hazard class or division:	Combustible Liquid
Identification number:	NA 1993
Packing group:	III
Exceptions :	(Not more than 450 Liters), Unrestricted
International Air Transportation (ICA Proper shipping name:	O/IATA) Aviation regulated liquid, n.o.s. (Cyanoacrylate ester
Hazard class or division:	9
Identification number:	UN 3334
Packing group: Exceptions :	III Primary packs containing less than 500ml are unregulated by this mode oftransport and may be shipped unrestricted.
Water Transportation (IMO/IMDG) Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. Regulatory information

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt fromlisting on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS Section 311/312: CERCLA/SARA Section 313:	: None above reporting de minimis. CERCLA/SARA Immediate Health, Delayed Health, Fire, Reactive None above reporting de minimis.
California Proposition 65:	No California Proposition 65 listed chemicals are know n to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into

16. Other information, including date of preparation or last revision

Issue date	10-02-21
Version #	01

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names