

GranQuartz Pro Series CA Activator

SAFETY DATA SHEET

1. Identification

Product number	500909
Product identifier	GranQuartz Pro Series CA Activator
Company information	GranQuartz
	3850 Steve Douglas Blvd Norcross, GA 30093

Company phone General Assistance (800) 458-6222

In Case of Emergency Contact CHEMTREC: 800-424-9300 (USA & Canada)

Version #	01
Recommended use	Lubricant
Recommended restrictions	None known.

2. Hazard(s) identification

 Physical hazards
 Flammable aerosols
 Category 1

 Health hazards
 Serious eye damage/eye irritation
 Category 2A

 Sensitization, skin
 Category 1

 Carcinogenicity
 Category 2

 Specific target organ toxicity, single exposure
 Category 3 narcotic effects

 Environmental hazards
 Not classified.
 Vot classified.



Danger

Signal word Hazard statement

Label elements

Extremely flammable aerosol. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statement

Product name: Nitro Pro Series CA Activator

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Not available.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	40 - 60
Acetone		67-64-1	20 - 40
Propane		74-98-6	10 - 20
Hydroquinone		123-31-9	0.1 - 1
Other components below reportable levels			1 - 2.5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately take off all contaminated clothing. Call a physician or Poison Control Center Skin contact immediately. Get medical attention if irritation develops or persists. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Call a physician Eye contact or Poison Control Center immediately. Ingestion If material is ingested, immediately contact a poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth to a victim who is unconscious or is having convulsions. Dermatitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose Most important and throat. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, symptoms/effects, acute and and blurred vision. May cause an allergic skin reaction. delayed Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special treatment needed **General information** IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

Fire-fighting measures	
Suitable extinguishing media	Powder. Alcohol resistant foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk. Do not direct water at source of leak or safety devices; icing may occur. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
5. Accidental release mea	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Pay attention to flashback. Wear appropriate protective equipment and clothing during clean-up. Stay upwind. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Pay attention to flashback. Wear appropriate protective equipment and clothing during clean-up. Stay upwind. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Clean contaminated surface thoroughly.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Keep locked-up. Level 3 Aerosol.
including any incompatibilities	Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Keep this material away from food, drink and animal feed. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

7. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Type		Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Hydroquinone (CAS 123-31-9)	PEL	2 mg/m3	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Hydroquinone (CAS	TWA	1 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Hydroquinone (CAS 123-31-9)	Ceiling	2 mg/m3	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
* - For sampling details, pl	lease see the sourc	e document.			
Exposure guidelines	No Exposure	standards allocated.			
Appropriate engineering controls	Provide eyew	rash station.			
Individual protection measure	<i>,</i> ,				
Eye/face protection	Wear safety g	Wear safety glasses with side shields (or goggles). Do not get this material in contact with eyes.			
Hand protection	Wear appropriate chemical resistant gloves.				
Skin protection					
Other	Do not get thi	s material in contact with	skin. Wear appr	opriate chemical resistant clothin	ıg. Wear

Other	Do not get this material in contact with skin. Wear appropriate chemical resistant clothing. Wear
	appropriate chemical resistant gloves. Use of an impervious apron is recommended.
Skin protection	

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

- Thermal hazards Wear appropriate thermal protective clothing, when necessary.
- General hygiene considerations Do not get this material in contact with eyes. When using do not smoke. Do not get this material in contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace

8. Physical and chemical properties

Appearance

Physical state Gas. Product name: Nitro Pro Series CA Activator

Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
Melting point/freezing point	Not available
. Flash point -156.0 °F (-104.4	°C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available
Vapor pressure	55 - 75 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.65 estimated
.Upper/lower flammability or exp	plosive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper	Not available.

9. Stability and reactivity

(%)

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of explosion.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine. Do not mix with other chemicals.
Hazardous decomposition products	May include oxides of carbon. No hazardous decomposition products are known.

10. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects.
Skin contact	May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Dermatitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.

Information on toxicological effects		Product Species
Acute toxicity	Acute LD50: 52214 mg/kg, Rat, Dermal Narcotic effects. May cause an allergic skin reaction.	12 OZ 2P-10 PROF WOOD ACTIVATOR NL 12PK (CAS Mixture)

Product name: Nitro Pro Series CA Activator

Acute		
Dermal		
LD50	Rat	
Inhalation		Test Results
LC50	Rat	
Oral		
LD50	Rat	
		52214 mg/kg
Components	Species	168 mg/l/4h
Acetone (CAS 67-64-1)		
Acute		
Dermal		Test Results
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours

Components	Species	Test Results	
Inhalation			
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral			
LD50	Mouse	3000 mg/kg	
	Rabbit	5340 mg/kg	
	Rat	5800 mg/kg	
		2.2 ml/kg	
Other			
LD50	Mouse	1297 mg/kg	
	Rat	5500 mg/kg	
Butane (CAS 106-97-8)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Hydroquinone (CAS 123-31-9)			
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg, 24 Hours	
	Rat	> 900 mg/kg, 24 Hours	
Oral			
LD100	Rat	600 mg/kg	
LD50	Rat	300 - 600 mg/kg	
Other			
LD50	Mouse	160 mg/kg	
	Rat	160 mg/kg	
Propane (CAS 74-98-6)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* Estimates for product may	be based on additional component data not shown.		
Skin corrosion/irritation	Not expected to be hazardous by OSHA criteria.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitizatio	on		
Respiratory sensitization	Not available.		
Skin sensitization	May cause an allergic skin reaction. Prolonged or r drying of the skin which may result in skin irritation		
Germ cell mutagenicity	Not expected to be hazardous by OSHA criteria. Not	ot expected to be hazardous by WHMIS criteri	
Carcinogenicity	Suspected of causing cancer. Not expected to be h	nazardous by WHMIS criteria.	

Product name: Nitro Pro Series CA Activator

Hydroquinone (CAS 123	3-31-9)	3 Not classifiable as	s to carcinogenicity to humans.		
	,	ces (29 CFR 1910.1001-1050)			
Not listed.					
Reproductive toxicity	Not expected to be hazardous by OSHA criteria.				
Specific target organ toxicity - single exposure	May caus	May cause drowsiness and dizziness.			
Specific target organ toxicity - epeated exposure	Not class	Not classified.			
Aspiration hazard	Not likely	, due to the form of the product.			
Chronic effects	Prolonge	d or repeated exposure may cause lung inj	jury.		
11. Ecological informatio	n				
Ecotoxicity		.93 mg/L, Fish, 96.00 Hours			
		911 mg/L, Daphnia, 48.00 Hours			
Product		Species	Test Results		
12 OZ 2P-10 PROF WOOD	ACTIVATOR	R NL 12PK (CAS Mixture)			
Aquatic					
Crustacea	EC50	Daphnia	31911 mg/L, 48 Hours		
Fish	LC50	Fish	29.9346 mg/L, 96 Hours		
Components		Species	Test Results		
Acetone (CAS 67-64-1) Aquatic					
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours		
Hydroquinone (CAS 123-31-	9)				
Aquatic					
Algae	IC50	Algae	13.5 mg/L, 72 Hours		
Crustacea	EC50	Daphnia	0.29 mg/L, 48 Hours		
		Water flea (Daphnia magna)	0.12 - 0.15 mg/l, 48 hours		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.044 mg/l, 96 hours		
* Estimates for product may	be based on	additional component data not shown.			
Bioaccumulative potential	No data a	available.			
Partition coefficient n-octa	nol / water (• ,			
Acetone Butane		-0.24 2.89			
Hydroquinone		0.59			
Propane		2.36			
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.				
12. Disposal consideration	ons				
Disposal instructions	under pre point. Do	nd reclaim or dispose in sealed containers essure. Dispose of this material and its cont not puncture, incinerate or crush. Dispose onal/national/international regulations.	tainer at hazardous or special waste collection		
Local disposal regulations	-	n accordance with all applicable regulation	s.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.				

US RCRA Hazardous Waste U List: Reference

Acetone	(CAS	67-64-1)
---------	------	----------

U002 Waste from residues / unused Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Empty containers should be taken to an approved waste handling site for recycling or disposal. **Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

13. Transport information

DOT

products


UN number UN proper shipping name	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.

Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.



IATA; IMDG

15. Regulatory information

io. Regulatory miorina					
US federal regulations	Standard, 2	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.			
TSCA Section 12(b) Ex	port Notification (40 CFR 707, Su	ıbpt. D)		
Not regulated.					
CERCLA Hazardous Su	ubstance List (40	CFR 302.4)			
Acetone (CAS 67-64			Listed.		
Hydroquinone (CAS			Listed.		
SARA 304 Emergency		201	400 DC		
Hydroquinone (CAS OSHA Specifically Reg	,	e (20 CEP 1010	100 LBS		
Not listed.		5 (25 01 1 1510	.1001-1050)		
		- A -t -f 4000 /0			
Superfund Amendments ar Hazard categories		n Act of 1986 (S Hazard - Yes	ΑΚΑ)		
Hazard Categories	Delayed Ha				
	Fire Hazard				
		azard - Yes			
	Reactivity I				
SARA 302 Extremely h			_	 , , , , ,	
Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Hydroquinone	123-31-9	100		500 lbs	10000 lbs
SARA 311/312 Hazardo chemical	us No				
SARA 313 (TRI reportin	ig)		040	0/	
Chemical name			CAS number	% by wt.	
Hydroquinone			123-31-9	0.1 - 1	
Other federal regulations					
Clean Air Act (CAA) Se	ction 112 Hazard	ous Air Pollutar	nts (HAPs) List		
Hydroquinone (CAS Clean Air Act (CAA) Se	,	lental Release F	Prevention (40 CFR 68	3.130)	
, , , , , , , , , , , , , , , , , , ,	ction 112(r) Accic 7-8)	lental Release I	Prevention (40 CFR 68	3.130)	

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** Acetone (CAS 67-64-1) 6532 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) Acetone (CAS 67-64-1) 35 %WV **DEA Exempt Chemical Mixtures Code Number** Acetone (CAS 67-64-1) 6532 **US** state regulations **US. Massachusetts RTK - Substance List** Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Hydroquinone (CAS 123-31-9) Propane (CAS 74-98-6) US. New Jersey Worker and Community Right-to-Know Act Acetone (CAS 67-64-1)

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Hydroquinone (CAS 123-31-9) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Hydroquinone (CAS 123-31-9) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Hydroquinone (CAS 123-31-9) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name On inv	entory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	10-02-21
Version #	01

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names