Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000

Section I – Product and Company Identification

Product Identifier:Superior Gold GV-1 FlowingProduct Description/Use:Acrylic Adhesive and FillerProduct Restrictions:None KnownProduct Code:30000Chemical Family:AcrylicCompany:Superior Stope Products Inc.

Superior Stone Products, Inc. 8580 Byron Commerce Drive Byron Center, MI 49315 Phone: (616) 583-0176

Section II – Hazards Identification

GHS Hazard Classification(s): Flammable Liquid: Category 2

Skin Sensitization: Category 1

CHEMTREC 800-424-9300

Skin Irritation: Category 2 Specific Target Organ Systemic Toxicity - Single Exposure: Category 3, Respiratory Tract Irritation



Symbols:

Hazard Statements:

H225: Highly Flammable liquid and vapor. H315: Causes skin irritation.

H335: May cause respiratory irritation.

Precautionary Statements:

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

Precautionary Statements: - Response:

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Signal Word(s): Danger

H317: May cause allergic skin reaction. H402: Harmful to aquatic life.

P261: Avoid breathing fumes.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area. P272: Contaminated work clothing should not be allowed out of the work area.

24 Hour Emergency Telephone Number:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P312: Call a POISON CENTER or physician if you feel unwell.



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000

P301+P361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P332+313: If skin irritation occurs: Get medical attention.

Precautionary Statements: - Storage: P403+235: Store in a well-ventilated place. Keep cool.

Precautionary Statements: - Disposal:

P501: Dispose of contents and container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u> Unsaturated Resin	<u>Synonym(s)</u> N/A	<u>% (By Weight)</u> 60-65%	<u>CAS#</u> N/A	<u>EINECS Nc.</u> N/A
Methyl Methacrylate	Methylacrylate Monomer, Methyl Ester fo Methacrylic Acid, Methyl-2-methyl-2-	30-35%	80-62-6	201-297-1
	propenoate			

Section IV – First Aid Measures

If Swallowed: DO NOT INDUCE VOMITING (aspiration hazard). Seek immediate medical aid.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Consult a physician if any signs or symptoms described in this document occur. Wash contaminated clothing.

If Inhaled: Remove victim from exposure. If victim is unconscious, administer artificial respiration and/or oxygen as needed. Seek medical aid.

Eyes: Flush with copious amounts of water for 15 minutes. Seek immediate medical aid.

Most important symptoms/effects, acute and delayed:

Headache, confusion, skin sensitization. Causes skin and eye irritation. Nausea, dermatitis. May cause irritations of the respiratory tract. Inhalation can lead to irritation of the mucous membrane.

Note to Physicians: Treat symptomatically.

Section V - Fire Fighting Measures

Suitable Extinguishing Media: Water Spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Unsuitable Extinguishing Media: Do not use water jet.

Special Fire Fighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear selfcontained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use. **Unusual Fire and Explosion Hazards:** At elevated temperatures, such as in a fire, polymerization may take place. If polymerization takes place in a closed container, there is the possibility of violent rupture of the container. Product vapors may form an explosive mixture in air.

Hazardous Products of Combustion: Decomposition products may include the following material: carbon oxides, nitrogen oxides.



P233: Keep container tightly closed.

and easy to do. Continue rinsing.

attention.

P305+351+338: IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present

P337+313: If eye irritation persists: Get medical

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000



Other Remarks: Liquid and vapor may cause flash fire or ignite explosively. Vapor is heavier than air and may settle in low places or spread long distances to a source of ignition and flashback. Explosive atmospheres may linger. Closed containers can rupture and release toxic vapors or decomposition products.

Section VI - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

Methods and Materials for Containment and Cleaning Up

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. **Large Spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section VII - Handling and Storage

Precautions for Safe Handling

Protective Measures: Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Use explosion-roof electrical (ventilating, lighting and material handling) equipment. Use only on-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and con be hazardous. Do no reuse container.

Advice on General Occupational Health: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for Safe Storage, Including and Incompatibles: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information.

Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000



Section VIII - Exposure Controls/Personal Protection

Likely Routes of Exposure: Inhalation, Dermal, Ingestion. Control Parameters Occupational exposure Limits:

			United :	States			Aust	tralia
	OSHA-PEL ACGIH-TLV NIOSH-REL			SV	VA			
	TWA	Ceiling	TWA	STEL	TWA	STEL	TWA	STEL
Methyl Methacrylate	100 ppm	N/A	50 ppm	100 ppm	100 ppm	N/A	50 ppm	N/A

Engineering Controls: Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures: Wash Hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. **Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory Protection:** Use a properly fitted, air-purifying of air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section IX – Physical and Chemical Properties

Physical State: Thin Paste Color: Yellowish White Odor: Acrid, fruity. Odor Threshold: 0.05 ppm pH: Not Available Melting Point/Freezing Point: -54.4°F/-48°C Boiling Point: 212.5°F/100.3°C

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000



Boiling Range: Not Available Flash Point: 75°F/24°C Burning Time: Not Applicable Burning Rate: Not Applicable Evaporation Rate: 3.1 (Butyl acetate) = 1) Flammability (solid, gas): Not Available Lower and Upper Explosive (Flammable) Limits: Lower: 2.1% Upper: 12.5% Vapor Pressure: 29 mm Hg @ 68°F/20°C (Methyl Methacrylate) Vapor Density: 3.5 (Air = 1) (Methyl Methacrylate) Relative Density: 0.94 (Water = 1) Solubility: Insoluble Partition Coefficient: n-Octanol/water: Not Available Auto-Ignition temperature: 790°F/421°C **Decomposition Temperature:** Not Available SADT: Not Available Viscosity: Not Available.

Section X - Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: Material is stable

Hazardous Polymerization: None under normal conditions.

Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. **Incompatibility (materials to avoid):** Strong acids and oxidizing agents

Hazardous Decomposition: Heating of this material to decomposition may cause fumes containing organic acids, carbon dioxide and carbon monoxide.

Section XI - Toxicological Information

Acute Toxicity:	-				
Product/Ingredient Name	<u>Result</u>	<u>Spe</u>	<u>ecies</u>	Dose	<u>Exposure</u>
Methyl Methacrylate	LC50 Inhalation	Rat	t	78,000 mg/m ³	4 hours
	LD50 Oral	Rat	t	7,872 mg/kg	-
	LD50 Dermal	Rat	t	>5,000 mg/kg	-
Irritation/Corrosion: Not ava	ilable				
Sensitization: Not available					
Mutagenicity: Not available					
Carcinogenicity: Not availabl	e				
- .					
Classification:					
Product/Ingredient Name	<u>OSHA</u>		<u>IARC</u>	<u>NTP</u>	
Methyl Methacrylate	No Component of this product prese	nt	3	No Component of this prod	uct present at
	at levels greater than or equal to 0.1	L%		levels greater than or equa	l to 0.1% is
	is identified as a carcinogen or			identified as a known or an	ticipated
	potential carcinogen by OSHA			carcinogen by NTP	
Reproductive Toxicity: Not a	vailable			- ,	
Teratogenicity: Not available					
-	y (Single Exposure): May cause respira	atory	irritation		

Specific Target Organ Toxicity (Repeated Exposure): Not available

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000

Aspiration Hazard: Not available Likely Routes of Exposure: Inhalation, Dermal, Ingestion.

Section XII - Ecological Information

Toxicity:

Product/Ingredient NameResultMethyl MethacrylateEC50 170 µ

EC50 170 µg/l Fresh Water

EC50 720 μg/l Fresh WaterDaphnia - Daphnia magnaLC50 125.5-275.0 μg/l Fresh WaterFish - Pimephales promelas

Persistence and Degradability: Not Available Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Section XIII - Disposal Considerations

<u>Species</u> Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia magna Fish - Pimephales promelas <u>Exposure</u> 96 hours

96 hours

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

Special Precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do no cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soul, water ways, drains and sewers.

Section XIV - Transportation Information

Tachnical Namas Dasin Colution
Technical Name: Resin Solution
Hazard Class: 3
NA/UN Number: 1866
Packing Group: III
Please refer to TDG Regulations for more info
International Maratime Organization (IMO)
Technical Name: Resin Solution
Hazard Class: 3
NA/UN Number: 1866
Packing Group: III
EmS: F-E, S-E
Marine Pollutant: No
Please refer to IMO regulations for more info.

Special Precautions for User: Transport within users' premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000



Section XV - Regulatory Information

United States Federal Regulations:

Sara Title III - Section 311/312 <u>Criteria</u> Immediate (Acute) Health E Chronic (Delayed) Health E Fire Hazard: Sudden Release of Pressure Reactivity:	Effects: ffects:	<u>Yes/No</u> Yes Yes No No		
Sara Title III - Section 313				
<u>Criteria</u>	Product/Ingredie	<u>ent Name</u>	CAS Number	<u>%</u>
Form R - Reporting	Methyl Methacry	/late	80-62-6	30-35%
Requirements Supplier Notification	Methyl Methacry	/late	80-62-6	30-35%
	, ,			

State Regulations:

Massachusetts: The following components are listed: Methyl Methacrylate

New Jersey: The following components are listed: Methyl Methacrylate

California Prop. 65: Warning: This product is not known to contain a chemical known to the State of California to cause cancer or other reproductive harm.

Section XVI - Other Information

Hazardous Material Information System (United States):

Health	2
Flammability	3
Physical Hazards	0

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Asociation (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (United States):



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-1 Flowing** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30000



Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010

Section I – Product and Company Identification

Product Identifier:Superior Gold GV-5 Knife GradeProduct Description/Use:Acrylic Adhesive and FillerProduct Restrictions:None KnownProduct Code:30010Chemical Family:AcrylicCompany:Company:

Superior Stone Products, Inc. 8580 Byron Commerce Drive Byron Center, MI 49315 Phone: (616) 583-0176

Section II – Hazards Identification

GHS Hazard Classification(s): Flammable Liquid: Category 2

Skin Sensitization: Category 1

CHEMTREC 800-424-9300

Skin Irritation: Category 2 Specific Target Organ Systemic Toxicity - Single Exposure: Category 3, Respiratory Tract Irritation



Symbols:

Hazard Statements:

- H225: Highly Flammable liquid and vapor.
- H315: Causes skin irritation.
- H335: May cause respiratory irritation.

Precautionary Statements: - Prevention

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

Precautionary Statements: - Response:

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Signal Word(s): Danger

H317: May cause allergic skin reaction. H402: Harmful to aquatic life.

P261: Avoid breathing fumes.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area. P272: Contaminated work clothing should not be allowed out of the work area.

24 Hour Emergency Telephone Number:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P312: Call a POISON CENTER or physician if you feel unwell.



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010

P301+P361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P332+313: If skin irritation occurs: Get medical attention.

Precautionary Statements: - Storage: P403+235: Store in a well-ventilated place. Keep cool.

Precautionary Statements: - Disposal:

P501: Dispose of contents and container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u> Unsaturated Resin	<u>Synonym(s)</u> N/A	<u>% (By Weight)</u> 60-65%	<u>CAS#</u> N/A	<u>EINECS Nc.</u> N/A
Methyl Methacrylate	Methylacrylate Monomer, Methyl Ester fo Methacrylic Acid, Methyl-2-methyl-2-	25-30%	80-62-6	201-297-1
Hydrophobic Amorphous Fumed Silica	Hetriaci yiic Acid, Metriyi-2-metriyi-2- propenoate Hydrophobized Dispersed Silica, Synthetic Silica, X-ray Amorphous Silicon Dioxide	5-10%	67762-90-7	N/A

Section IV – First Aid Measures

If Swallowed: DO NOT INDUCE VOMITING (aspiration hazard). Seek immediate medical aid.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Consult a physician if any signs or symptoms described in this document occur. Wash contaminated clothing.

If Inhaled: Remove victim from exposure. If victim is unconscious, administer artificial respiration and/or oxygen as needed. Seek medical aid.

Eyes: Flush with copious amounts of water for 15 minutes. Seek immediate medical aid.

Most important symptoms/effects, acute and delayed:

Headache, confusion, skin sensitization. Causes skin and eye irritation. Nausea, dermatitis. May cause irritations of the respiratory tract. Inhalation can lead to irritation of the mucous membrane.

Note to Physicians: Treat symptomatically.

Section V - Fire Fighting Measures

Suitable Extinguishing Media: Water Spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Unsuitable Extinguishing Media: Do not use water jet.

Special Fire Fighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear selfcontained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use. **Unusual Fire and Explosion Hazards:** At elevated temperatures, such as in a fire, polymerization may take place. If polymerization takes place in a closed container, there is the possibility of violent rupture of the container. Product vapors may form an explosive mixture in air.

Hazardous Products of Combustion: Decomposition products may include the following material: carbon oxides, nitrogen oxides.



P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical attention.

P233: Keep container tightly closed.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010



Other Remarks: Liquid and vapor may cause flash fire or ignite explosively. Vapor is heavier than air and may settle in low places or spread long distances to a source of ignition and flashback. Explosive atmospheres may linger. Closed containers can rupture and release toxic vapors or decomposition products.

Section VI - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

Methods and Materials for Containment and Cleaning Up

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. **Large Spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section VII - Handling and Storage

Precautions for Safe Handling

Protective Measures: Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from compatible materials, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Use explosion-roof electrical (ventilating, lighting and material handling) equipment. Use only on-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and con be hazardous. Do no reuse container.

Advice on General Occupational Health: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for Safe Storage, Including and Incompatibles: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information.

Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010



Section VIII - Exposure Controls/Personal Protection

Likely Routes of Exposure: Inhalation, Dermal, Ingestion. Control Parameters Occupational exposure Limits:

			United :	States			Aust	tralia	
	09	SHA-PEL	ACGI	(H-TLV	NIOS	H-REL	SV	VA	
	TWA	Ceiling	TWA	STEL	TWA	STEL	TWA	STEL	
Methyl Methacrylate	100 ppm	N/A	50 ppm	100 ppm	100 ppm	N/A	50 ppm	N/A	-

Engineering Controls: Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures: Wash Hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. **Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory Protection:** Use a properly fitted, air-purifying of air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section IX – Physical and Chemical Properties

Physical State: Thin Paste Color: Yellowish White Odor: Acrid, fruity Odor Threshold: 0.05 ppm pH: Not Available Melting Point/Freezing Point: -54.4°F/-48°C (Methyl Methacrylate) Boiling Point: 212.5°F/100.3°C (Methyl Methacrylate)

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010



Boiling Range: Not Available Flash Point: 75°F/24°C Burning Time: Not Applicable Burning Rate: Not Applicable Evaporation Rate: 3.1 (Butyl acetate) = 1) Flammability (solid, gas): Not Available Lower and Upper Explosive (Flammable) Limits: Lower: 2.1% Upper: 12.5% Vapor Pressure: 29 mm Hg @ 68°F/20°C (Methyl Methacrylate) Vapor Density: 3.5 (Air = 1) (Methyl Methacrylate) Relative Density: 0.94 (Water = 1) Solubility: Insoluble Partition Coefficient: n-Octanol/water : Not Available Auto-Ignition temperature: 790°F/421°C **Decomposition Temperature:** Not Available SADT: Not Available Viscosity: Not Available.

Section X - Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: Material is stable

Hazardous Polymerization: None under normal conditions.

Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. **Incompatibility (materials to avoid):** Strong acids and oxidizing agents

Hazardous Decomposition: Heating of this material to decomposition may cause fumes containing organic acids, carbon dioxide and carbon monoxide.

Section XI - Toxicological Information

Specific Target Organ Toxicity (Repeated Exposure): Not available

Acute Toxicity:					
Product/Ingredient Name	Result	Species	<u>.</u>	<u>Dose</u>	Exposure
Methyl Methacrylate	LC50 Inhalation	Rat		78,000 mg/m ³	4 hours
	LD50 Oral	Rat		7,872 mg/kg	-
	LD50 Dermal	Rat		>5,000 mg/kg	-
Irritation/Corrosion: Not ava	ilable				
Sensitization: Not available					
Mutagenicity: Not available					
Carcinogenicity: Not availabl	e				
0 .					
Classification:					
Product/Ingredient Name	OSHA	IAF	RC NTP		
Methyl Methacrylate	No Component of this product prese			nponent of this prod	uct present at
, ,	at levels greater than or equal to 0.1			greater than or equa	•
	is identified as a carcinogen or		-	ed as a known or an	
	potential carcinogen by OSHA			gen by NTP	
Reproductive Toxicity: Not a	, <u> </u>			5	
Teratogenicity: Not available					
e ,		atory irrita	ation.		
e .	: t y (Single Exposure): May cause respira	atory irrita	ation.		

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010

Aspiration Hazard: Not available Likely Routes of Exposure: Inhalation, Dermal, Ingestion.

Section XII - Ecological Information

Toxicity:

Product/Ingredient NameResultMethyl MethacrylateEC50 170 µg/l Fresh Water

ECEO 720 ug/l Fresh Water

EC50 720 μg/l Fresh WaterDaphnia - Daphnia magnaLC50 125.5-275.0 μg/l Fresh WaterFish - Pimephales promelas

Persistence and Degradability: Not Available Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Section XIII - Disposal Considerations

<u>Species</u> Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia magna Fish - Pimephales promelas Exposure 96 hours

96 hours

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

Special Precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do no cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soul, water ways, drains and sewers.

Section XIV - Transportation Information

DOT (DEPARTMENT OF TRANSPORTATION)	Canada (TDG)
Technical Name: Resin Solution	Technical Name: Resin Solution
Hazard Class: 3	Hazard Class: 3
NA/UN Number: 1866	NA/UN Number: 1866
Packing Group: III	Packing Group: III
Marine Pollutant: No	2
Please refer to DOT regulations for more info	Please refer to TDG Regulations for more info
International Air Transport Association (IATA)	International Maratime Organization (IMO)
Technical Name: Resin Solution	Technical Name: Resin Solution
Hazard Class: 3	Hazard Class: 3
NA/UN Number: 1866	NA/UN Number: 1866
Packing Group: III	Packing Group: III
ERG Code: 3L	EmS: F-E, S-E
Marine Pollutant: No	Marine Pollutant: No
Please refer to IATA regulations for more info.	Please refer to IMO regulations for more info.

Special Precautions for User: Transport within users premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010



Section XV - Regulatory Information

United States Federal Regulations:

Sara Title III - Section 311/312 Criteria Immediate (Acute) Health E Chronic (Delayed) Health Ef Fire Hazard: Sudden Release of Pressure Reactivity:	ffects: fects:	<u>Yes/No</u> Yes Yes No No	
Sara Title III - Section 313			
<u>Criteria</u> Form R - Reporting	Product/Ingredie Methyl Methacry		<u>CAS Number</u> 80-62-6

Requirements			
Supplier Notification	Methyl Methacrylate	80-62-6	25-30%

State Regulations:

Massachusetts: The following components are listed: Methyl Methacrylate

New Jersey: The following components are listed: Methyl Methacrylate

California Prop. 65: Warning: This product is not known to contain a chemical known to the State of California to cause cancer or other reproductive harm.

<u>%</u> 25-30%

Section XVI - Other Information


Hazardous Material Information System (United States):

Health	2
Flammability	3
Physical Hazards	0

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Asociation (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (United States):



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-5 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30010



Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020

Section I – Product and Company Identification

Product Identifier:Superior Gold GV-9 Knife GradeProduct Description/Use:Acrylic Adhesive and FillerProduct Restrictions:None KnownProduct Code:30010Chemical Family:AcrylicCompany:D

Superior Stone Products, Inc. 8580 Byron Commerce Drive Byron Center, MI 49315 Phone: (616) 583-0176

Section II – Hazards Identification

GHS Hazard Classification(s): Flammable Liquid: Category 2

Skin Sensitization: Category 1

CHEMTREC 800-424-9300

Skin Irritation: Category 2 Specific Target Organ Systemic Toxicity - Single Exposure: Category 3, Respiratory Tract Irritation



Symbols:

Hazard Statements:

- H225: Highly Flammable liquid and vapor.
- H315: Causes skin irritation.
- H335: May cause respiratory irritation.

Precautionary Statements: - Prevention

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

Precautionary Statements: - Response:

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Signal Word(s): Danger

H317: May cause allergic skin reaction. H402: Harmful to aquatic life.

P261: Avoid breathing fumes.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area. P272: Contaminated work clothing should not be allowed out of the work area.

24 Hour Emergency Telephone Number:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P312: Call a POISON CENTER or physician if you feel unwell.



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020

P301+P361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P332+313: If skin irritation occurs: Get medical attention.

Precautionary Statements: - **Storage:** P403+235: Store in a well-ventilated place. Keep cool.

Precautionary Statements: - Disposal:

P501: Dispose of contents and container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u> Unsaturated Resin	<u>Synonym(s)</u> N/A	<u>% (By Weight)</u> 60-65%	<u>CAS#</u> N/A	<u>EINECS Nc.</u> N/A
Methyl Methacrylate	Methylacrylate Monomer, Methyl Ester fo Methacrylic Acid, Methyl-2-methyl-2-	25-30%	80-62-6	201-297-1
Hydrophobic Amorphous Fumed Silica	Propenoate Hydrophobized Dispersed Silica, Synthetic Silica, X-ray Amorphous Silicon Dioxide	5-10%	67762-90-7	N/A

Section IV – First Aid Measures

If Swallowed: DO NOT INDUCE VOMITING (aspiration hazard). Seek immediate medical aid.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Consult a physician if any signs or symptoms described in this document occur. Wash contaminated clothing.

If Inhaled: Remove victim from exposure. If victim is unconscious, administer artificial respiration and/or oxygen as needed. Seek medical aid.

Eyes: Flush with copious amounts of water for 15 minutes. Seek immediate medical aid.

Most important symptoms/effects, acute and delayed:

Headache, confusion, skin sensitization. Causes skin and eye irritation. Nausea, dermatitis. May cause irritations of the respiratory tract. Inhalation can lead to irritation of the mucous membrane.

Note to Physicians: Treat symptomatically.

Section V - Fire Fighting Measures

Suitable Extinguishing Media: Water Spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Unsuitable Extinguishing Media: Do not use water jet.

Special Fire Fighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear selfcontained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use. **Unusual Fire and Explosion Hazards:** At elevated temperatures, such as in a fire, polymerization may take place. If polymerization takes place in a closed container, there is the possibility of violent rupture of the container. Product vapors may form an explosive mixture in air.

Hazardous Products of Combustion: Decomposition products may include the following material: carbon oxides, nitrogen oxides.



P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical attention.

P233: Keep container tightly closed.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020



Other Remarks: Liquid and vapor may cause flash fire or ignite explosively. Vapor is heavier than air and may settle in low places or spread long distances to a source of ignition and flashback. Explosive atmospheres may linger. Closed containers can rupture and release toxic vapors or decomposition products.

Section VI - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

Methods and Materials for Containment and Cleaning Up

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. **Large Spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section VII - Handling and Storage

Precautions for Safe Handling

Protective Measures: Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from compatible materials, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Use explosion-roof electrical (ventilating, lighting and material handling) equipment. Use only on-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and con be hazardous. Do no reuse container.

Advice on General Occupational Health: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for Safe Storage, Including and Incompatibles: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information.

Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020



Section VIII - Exposure Controls/Personal Protection

Likely Routes of Exposure: Inhalation, Dermal, Ingestion. Control Parameters Occupational exposure Limits:

			United	States			Aust	ralia
	OSHA-PEL A			ACGIH-TLV NIOSI		NIOSH-REL		VA
	TWA	Ceiling	TWA	STEL	TWA	STEL	TWA	STEL
Methyl Methacrylate	100 ppm	N/A	50 ppm	100 ppm	100 ppm	N/A	50 ppm	N/A

Engineering Controls: Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures: Wash Hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. **Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory Protection:** Use a properly fitted, air-purifying of air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section IX – Physical and Chemical Properties

Physical State: Thin Paste Color: Yellowish White Odor: Acrid, fruity Odor Threshold: 0.05 ppm pH: Not Available Melting Point/Freezing Point: -54.4°F/-48°C (Methyl Methacrylate) Boiling Point: 212.5°F/100.3°C (Methyl Methacrylate)

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020



Boiling Range: Not Available Flash Point: 75°F/24°C Burning Time: Not Applicable Burning Rate: Not Applicable Evaporation Rate: 3.1 (Butyl acetate) = 1) Flammability (solid, gas): Not Available Lower and Upper Explosive (Flammable) Limits: Lower: 2.1% Upper: 12.5% Vapor Pressure: 29 mm Hg @ 68°F/20°C (Methyl Methacrylate) Vapor Density: 3.5 (Air = 1) (Methyl Methacrylate) Relative Density: 0.94 (Water = 1) Solubility: Insoluble Partition Coefficient: n-Octanol/water : Not Available Auto-Ignition temperature: 790°F/421°C **Decomposition Temperature:** Not Available SADT: Not Available Viscosity: Not Available.

Section X - Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: Material is stable

Hazardous Polymerization: None under normal conditions.

Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. **Incompatibility (materials to avoid):** Strong acids and oxidizing agents

Hazardous Decomposition: Heating of this material to decomposition may cause fumes containing organic acids, carbon dioxide and carbon monoxide.

Section XI - Toxicological Information

Acute Toxicity:	-				
Product/Ingredient Name	Result	<u>Spe</u>	<u>ecies</u>	Dose	Exposure
Methyl Methacrylate	LC50 Inhalation	Rat	t	78,000 mg/m ³	4 hours
	LD50 Oral	Rat	t	7,872 mg/kg	-
	LD50 Dermal	Rat	t	>5,000 mg/kg	-
Irritation/Corrosion: Not ava	ilable				
Sensitization: Not available					
Mutagenicity: Not available					
Carcinogenicity: Not availabl	e				
0					
Classification:					
Product/Ingredient Name	<u>OSHA</u>		<u>IARC</u>	<u>NTP</u>	
Methyl Methacrylate	No Component of this product prese	ent	3	No Component of this prod	luct present at
, ,	at levels greater than or equal to 0.1			levels greater than or equa	•
	is identified as a carcinogen or			identified as a known or ar	
	potential carcinogen by OSHA			carcinogen by NTP	•
Reproductive Toxicity: Not a	, ,			<i>S</i> ,	
Teratogenicity: Not available					
u	ty (Single Exposure): May cause respiration	atory	irritation.		

Specific Target Organ Toxicity (Repeated Exposure): Not available

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020

Aspiration Hazard: Not available Likely Routes of Exposure: Inhalation, Dermal, Ingestion.

Section XII - Ecological Information

Toxicity:

Product/Ingredient NameResultMethyl MethacrylateEC50 170 µg/l Fresh Water

EC50 720 µg/l Fresh Water

LC50 125.5-275.0 µg/l Fresh Water Fish - Pimephales promelas

Persistence and Degradability: Not Available Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Section XIII - Disposal Considerations

<u>Species</u> Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia magna Fish - Pimephales promelas Exposure 96 hours

-96 hours

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

Special Precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do no cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soul, water ways, drains and sewers.

Section XIV - Transportation Information

DOT (DEPARTMENT OF TRANSPORTATION)	Canada (TDG)
Technical Name: Resin Solution	Technical Name: Resin Solution
Hazard Class: 3	Hazard Class: 3
NA/UN Number: 1866	NA/UN Number: 1866
Packing Group: III	Packing Group: III
Marine Pollutant: No	
Please refer to DOT regulations for more info	Please refer to TDG Regulations for more info
International Air Transport Association (IATA)	International Maratime Organization (IMO)
Technical Name: Resin Solution	Technical Name: Resin Solution
Hazard Class: 3	Hazard Class: 3
NA/UN Number: 1866	NA/UN Number: 1866
Packing Group: III	Packing Group: III
ERG Code: 3L	EmS: F-E, S-E
Marine Pollutant: No	Marine Pollutant: No
Please refer to IATA regulations for more info.	Please refer to IMO regulations for more info.

Special Precautions for User: Transport within users' premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.

Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020



%

Section XV - Regulatory Information

United States Federal Regulations:

Sara Title III - Section 311/312 <u>Criteria</u> Immediate (Acute) Health E Chronic (Delayed) Health E Fire Hazard: Sudden Release of Pressure Reactivity:	Effects: ffects:	<u>Yes/No</u> Yes Yes No No		
Sara Title III - Section 313				
<u>Criteria</u> Form R - Reporting	<u>Product/Ingredient Name</u> Methyl Methacrylate		<u>CAS Number</u> 80-62-6	

Form R - Reporting	Methyl Methacrylate	80-62-6	25-30%
Requirements			
Supplier Notification	Methyl Methacrylate	80-62-6	25-30%

State Regulations:

Massachusetts: The following components are listed: Methyl Methacrylate

New Jersey: The following components are listed: Methyl Methacrylate

California Prop. 65: Warning: This product is not known to contain a chemical known to the State of California to cause cancer or other reproductive harm.

Section XVI - Other Information


Hazardous Material Information System (United States):

Health	2
Flammability	3
Physical Hazards	0

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (United States):



Company Name: Superior Stone Products, Inc. **Product Name: Superior Gold GV-9 Knife Grade** Issue Date: 12/4/09 Revision Date: 8/12/19 SDS Number: 200-30020



Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.