

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section I – Product and Company Identification

**Product Identifier:** Gold Evolution – SSP Translucent – Part A

**Product Description/Use:** Vinyl Ester/Acrylic Adhesive and Filler

**Product Restrictions:** None Known

**Product Code:** 30030

**Chemical Family:** Vinyl Ester

**Company:**

Superior Stone Products, Inc.

8580 Byron Commerce Drive

Byron Center, MI 49546

Phone: (616) 583-0171

**24 Hour Emergency Telephone Number:  
CHEMTREC 800-424-9300**

## Section II – Hazards Identification

**GHS Hazard Classification(s):**

**Flammable Liquid:** Category 2

**Skin Sensitization:** Category 1

**Skin Irritation:** Category 2

**Specific Target Organ Systemic Toxicity - Single Exposure:** Category 3, Respiratory Tract Irritation



**Symbols:**

**Hazard Statements:**

H225: Highly Flammable liquid and vapor.

H315: Causes skin irritation.

H335: May cause respiratory irritation.

**Signal Word(s): Danger**

H317: May cause allergic skin reaction.

H402: Harmful to aquatic life.

**Precautionary Statements: - Prevention**

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing fumes.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the work area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary Statements: - Response**

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P312: Call a POISON CENTER or physician if you feel unwell.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



P301+P361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P332+313: If skin irritation occurs: Get medical attention.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical attention.

## Precautionary Statements: - Storage:

P403+235: Store in a well-ventilated place. Keep cool.

P233: Keep container tightly closed.

## Precautionary Statements: - Disposal:

P501: Dispose of contents and container in accordance with local/regional/national/international regulations.

**Hazards not otherwise classified:** Polymerization with heat evolution may occur in the presence of radical forming substances (e.g., peroxides), reducing substances, and/or heavy metal ions.

## Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u>	<u>Synonym(s)</u>	<u>% (By Weight)</u>	<u>CAS#</u>	<u>EINECS No.</u>
Methyl Methacrylate	Methylacrylate Monomer, Methyl Ester of Methacrylic Acid, Methyl-2-methyl-2-propenoate	25-30%	80-62-6	201-297-1

## Section IV – First Aid Measures

**If Swallowed:** DO NOT INDUCE VOMITING (aspiration hazard). Seek immediate medical aid.

**Skin Contact:** Remove contaminated clothing. Wash with soap and water. Consult a physician if any signs or symptoms described in this document occur. Wash contaminated clothing.

**If Inhaled:** Remove victim from exposure. If the victim is unconscious, administer artificial respiration and/or oxygen as needed. Seek medical aid.

**Eyes:** Flush with copious amounts of water for 15 minutes. Seek immediate medical aid.

**Most important symptoms/effects, acute and delayed:**

Headache, confusion, skin sensitization. Causes skin and eye irritation. Nausea, dermatitis. May cause irritations of the respiratory tract. Inhalation can lead to irritation of the mucous membrane.

**Note to Physicians:** Treat symptomatically.

## Section V - Fire Fighting Measures

**Suitable Extinguishing Media:** Water Spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent.

**Unsuitable Extinguishing Media:** Do not use water jet.

**Special Fire Fighting Procedures:** Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use.

**Unusual Fire and Explosion Hazards:** At elevated temperatures, such as in a fire, polymerization may take place. If polymerization takes place in a closed container, there is the possibility of violent rupture of the container. Product vapors may form an explosive mixture in air.

**Hazardous Products of Combustion:** Decomposition products may include the following material: carbon oxides, nitrogen oxides.

**Other Remarks:** Liquid and vapor may cause flash fire or ignite explosively. Vapor is heavier than air and may settle in low places or spread long distances to a source of ignition and flashback. Explosive atmospheres may linger. Closed containers can rupture and release toxic vapors or decomposition products.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section VI - Accidental Release Measures

### Personal Precautions, Protective Equipment and Emergency Procedures

**For Non-Emergency Personnel:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

**For Emergency Responders:** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear an appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

### Methods and Materials for Containment and Cleaning Up

**Small Spill:** Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

**Large Spill:** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g., sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section VII - Handling and Storage

### Precautions for Safe Handling

**Protective Measures:** Put on appropriate personal protection equipment (see Section 8). Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Workers should wash their hands and face before eating, drinking, and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin, and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear an appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from compatible materials, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting, and material handling) equipment. Use only on-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on General Occupational Health:** Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking, and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for Safe Storage, Including and Incompatibles:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool, and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information.

Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

## Section VIII - Exposure Controls/Personal Protection

**Likely Routes of Exposure:** Inhalation, Dermal, Ingestion.

**Control Parameters**

**Occupational exposure Limits:**

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



	United States						Australia	
	OSHA-PEL		ACGIH-TLV		NIOSH-REL		SWA	
	TWA	Ceiling	TWA	STEL	TWA	STEL	TWA	STEL
<b>Methyl Methacrylate</b>	100 ppm	N/A	50 ppm	100 ppm	100 ppm	N/A	50 ppm	N/A

**Engineering Controls:** Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental Exposure Controls:** Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. .

## Individual Protection Measures

**Hygiene Measures:** Wash hands, forearms, and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/Face Protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Hand Protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots, and gloves.

**Other Skin Protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory Protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section IX – Physical and Chemical Properties

**Physical State:** Thin Paste

**Color:** Yellowish White

**Odor:** Acrid, fruity

**Odor Threshold:** 0.05 ppm

**pH:** Not Available

**Melting Point/Freezing Point:** -54.4°F/-48°C (Methyl Methacrylate)

**Boiling Point:** 212.5°F/100.3°C (Methyl Methacrylate)

**Boiling Range:** Not Available

**Flash Point:** 75°F/24°C

**Burning Time:** Not Applicable

**Burning Rate:** Not Applicable

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



**Evaporation Rate:** 3.1 (Butyl acetate) = 1)

**Flammability (solid, gas):** Not Available

**Lower and Upper Explosive (Flammable) Limits:** Lower: 2.1%  
Upper: 12.5%

**Vapor Pressure:** 29 mm Hg @ 68°F/20°C (Methyl Methacrylate)

**Vapor Density:** 3.5 (Air = 1) (Methyl Methacrylate)

**Relative Density:** 0.94 (Water = 1)

**Solubility:** Insoluble

**Partition Coefficient: n-Octanol/water:** Not Available

**Auto-Ignition temperature:** 790°F/421°C

**Decomposition Temperature:** Not Available

**SADT:** Not Available

**Viscosity:** Not Available.

## Section X - Stability and Reactivity

**Reactivity:** No specific test data related to reactivity is available for this product or its ingredients.

**Chemical Stability:** Material is stable.

**Hazardous Polymerization:** None under normal conditions.

**Conditions to avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

**Incompatibility (materials to avoid):** Strong acids and oxidizing agents.

**Hazardous Decomposition:** Heating of this material to decomposition may cause fumes containing organic acids, carbon dioxide and carbon monoxide.

## Section XI - Toxicological Information

**Acute Toxicity:**

<u>Product/Ingredient Name</u>	<u>Result</u>	<u>Species</u>	<u>Dose</u>	<u>Exposure</u>
Methyl Methacrylate	LC50 Inhalation	Rat	78,000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7,872 mg/kg	-
	LD50 Dermal	Rat	>5,000 mg/kg	-

**Irritation/Corrosion:** Not available

**Sensitization:** Not available

**Mutagenicity:** Not available

**Carcinogenicity:** Not available

**Classification:**

<u>Product/Ingredient Name</u>	<u>OSHA</u>	<u>IARC</u>	<u>NTP</u>
Methyl Methacrylate	No Component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA	3	No Component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

**Reproductive Toxicity:** Not available

**Teratogenicity:** Not available

**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.

**Specific Target Organ Toxicity (Repeated Exposure):** Not available

**Aspiration Hazard:** Not available

**Likely Routes of Exposure:** Inhalation, Dermal, Ingestion.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section XII - Ecological Information

Toxicity:

<u>Product/Ingredient Name</u>	<u>Result</u>	<u>Species</u>	<u>Exposure</u>
Methyl Methacrylate	EC50 170 µg/l Fresh Water	Algae - Pseudokirchneriella subcapitata	96 hours
	EC50 720 µg/l Fresh Water	Daphnia - Daphnia magna	-
	LC50 125.5-275.0 µg/l Fresh Water	Fish - Pimephales promelas	96 hours

**Persistence and Degradability:** Not Available

**Bioaccumulative Potential:** No data available.

**Mobility in Soil:** No data available.

## Section XIII - Disposal Considerations

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

**Disposal Methods:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special Precautions:** This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, water ways, drains and sewers.

## Section XIV - Transportation Information

**DOT (DEPARTMENT OF TRANSPORTATION)**

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

Marine Pollutant: Yes

Please refer to DOT regulations for more info

**Canada (TDG)**

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

Please refer to TDG Regulations for more info.

**International Air Transport Association (IATA)**

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

ERG Code: 3L

Marine Pollutant: Yes

Please refer to IATA regulations for more info.

**International Maritime Organization (IMO)**

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

EmS: F-E, S-D

Marine Pollutant: Yes

Please refer to IMO regulations for more info.

**Special Precautions for User:** Transport within users' premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section XV - Regulatory Information

United States Federal Regulations:

### Sara Title III - Section 311/312

<u>Criteria</u>	<u>Yes/No</u>
Immediate (Acute) Health Effects:	Yes
Chronic (Delayed) Health Effects:	Yes
Fire Hazard:	Yes
Sudden Release of Pressure Hazard:	No
Reactivity:	No

### Sara Title III - Section 313

<u>Criteria</u>	<u>Product/Ingredient Name</u>	<u>CAS Number</u>	<u>%</u>
Form R - Reporting Requirements	Methyl Methacrylate	80-62-6	25-30%
Supplier Notification	Methyl Methacrylate	80-62-6	25-30%

### State Regulations:

Massachusetts: The following components are listed: Methyl Methacrylate

New Jersey: The following components are listed: Methyl Methacrylate

**California Prop. 65: Warning:** This product is not known to contain a chemical known to the State of California to cause cancer or other reproductive harm.

## Section XVI - Other Information


### Hazardous Material Information System (United States):

Health	2
Flammability	3
Physical Hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (United States):



# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to a certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**MANUFACTURER DISCLAIMER:** This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility for damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.



# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section I – Product and Company Identification

**Product Identifier:** Gold Evolution – SSP Translucent - Part B

**Product Description/Use:** Organic Peroxide Activator

**Product Restrictions:** None Known

**Product Code:** 33105

**Chemical Family:** Organic Peroxide

**Company:**

Superior Stone Products, Inc.

8580 Byron Commerce Drive

Byron Center, MI 49546

Phone: (616) 583-0171

**24 Hour Emergency Telephone Number:**

**CHEMTREC 800-424-9300**

## Section II – Hazards Identification

**GHS Hazard Classification(s):**

**Eye Irritation:** Category 2B

**Reproductive Toxicity:** Category 1B

**Short-term (acute) aquatic:** Category 1

**Skin Sensitization:** Category 1

**Germ Cell Mutagenicity:** Category 2

**Long-term (chronic) aquatic:** Category 1



**Symbols:**

**Signal Word(s):** **Danger**

**Hazard Statements:**

H317: May cause an allergic skin reaction.

H320: Causes eye irritation.

H341 - Suspected of causing genetic defects.

H360: May damage fertility or the unborn child.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

**Precautionary Statements: Prevention**

P203: Obtain, read, and follow all safety instructions before use.

P261: Avoid breathing fumes/gas/vapor.

P264+265: Wash hands and face thoroughly after handling. Do not touch eyes.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary Statements: Response:**

P302+352 - IF ON SKIN: wash with plenty of soap and water.

P333+313 - If skin irritation or rash occurs: Get medical help.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+317 - If eye irritation persists: Get medical help.

P318 - if exposed or concerned, get medical advice.

P362+364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazards not otherwise classified:** None known.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u>	<u>% (By Weight)</u>	<u>CAS#</u>	<u>EINECS No.</u>
Dibenzoyl Peroxide	<10%	94-36-0	202-327-6
Dibutyl Phthalate	<5%	84-74-2	201-557-4
Epoxy Resins	0-6%	25068-38-6	500-033-5
2,3-epoxypropyl o-totyl ether	0-3%	2210-79-9	218-645-3

## Section IV – First Aid Measures

**If Swallowed:** Rinse mouth. DO NOT INDUCE VOMITING. Call a POISON CENTER or doctor.

**Skin Contact:** Remove immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse.

**If Inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER OR doctor/physician if symptoms persist.

**Eyes:** Flush with copious amounts of water for at least 10 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Seek immediate medical aid.

**Most important symptoms and effects, both acute and delayed:** May cause and allergic skin reaction. Causes eye irritation.

## Section V - Fire Fighting Measures

**Suitable Extinguishing Media:** Water Spray, foam, dry chemical, carbon dioxide or any extinguishing agent suitable for surrounding fire.

**Unsuitable Extinguishing Media:** None known.

**Special Fire Fighting Procedures:** Fire may produce irritation and/or toxic gasses. In the event of fire and/or explosion, do not breathe fumes. May cause sensitization and/or irritation by skin contact. Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire fighting to enter drains or water courses.

**Hazardous Products of Combustion:** Toxic fumes may be formed.

## Section VI - Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures**

**For Non-Emergency Personnel:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

**For Emergency Responders:** If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment to avoid contact with skin, eyes or clothing. See also the information for non-emergency personnel.

**Methods and Materials for Containment and Cleaning Up:** Stop leak if without risk. Move containers from spill area. Clean with detergents. Avoid solvent cleaners. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal. Dispose of via a licensed waste disposal contractor. Do not allow into any sewer, on the ground or any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section VII - Handling and Storage

### Precautions for Safe Handling

**Protective Measures:** Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Empty containers retain product residue and can be hazardous. Do no reuse container.

**Advice on General Occupational Health:** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for Safe Storage, Including and Incompatibles:** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information. Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

## Section VIII - Exposure Controls/Personal Protection

**Likely Routes of Exposure:** Dermal, Ingestion.

### Control Parameters

#### Occupational exposure Limits:

	United States				Australia		
	OSHA-PEL	ACGIH-TLV		NIOSH-REL		SWA	
	TWA	TWA	STEL	TWA	STEL	TWA	STEL
Dibenzoyl Peroxide	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	N/A	5 mg/m <sup>3</sup>	N/A	5 mg/m <sup>3</sup>	N/A
Dibutyl Phthalate	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	N/A	5 mg/m <sup>3</sup>	N/A	5 mg/m <sup>3</sup>	N/A

**Engineering Controls:** Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits.

**Environmental Exposure Controls:** Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual Protection Measures

**Hygiene Measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/Face Protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Hand Protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other Skin Protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory Protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section IX – Physical and Chemical Properties

**Physical State:** Viscous Liquid

**Color:** Translucent/White

**Odor:** Weak, Characteristic

**Odor Threshold:** Not Available

**pH:** Not Available

**Melting Point:** Not Available

**Boiling Point:** Not Available

**Flash Point:** >200.0°F/93.3°C

**Burning Time:** Not Available

**Burning Rate:** Not Available

**Evaporation Rate:** Not Available

**Flammability (solid, gas):** Not Available

**Lower and Upper Explosive (Flammable) Limits:** Not Available

**Vapor Pressure:** Not Available

**Vapor Density:** Not Available (Air = 1)

**Relative Density:** Not Determined (Water = 1)

**Solubility:** Partially Soluble in Water

**Partition Coefficient: n-Octanol/water:** Not Available

**Auto-Ignition temperature:** Not Available

**Decomposition Temperature:** Not Available

**SADT:** Not Available

**Viscosity:** Not Available

**Molecular Weight:** Not Available

## Section X - Stability and Reactivity

**Reactivity:** No specific test data related to reactivity available for this product or its ingredients.

**Chemical Stability:** Material is stable at normal temperature and pressure.

**Conditions to avoid:** Avoid excessive heating. Avoid contact with strong oxidizing agent, heat, spark and flames.

**Incompatibility (materials to avoid):** Strong acids, amines, bases, and oxidizing agents.

**Hazardous Decomposition:** May product hazardous carbon oxides, chloro hydrogen.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section XI - Toxicological Information

### Acute Toxicity:

<u>Product/Ingredient Name</u>	<u>Result</u>	<u>Species</u>	<u>Dose</u>	<u>Exposure</u>
Dibutyl Phthalate	LD50 Oral	Rat	8,000 mg/kg	-
	LD50 Dermal	Rabbit	20,000 mg/kg	-
Dibenzoyl peroxide	LD50 Oral	Rat	7,710 mg/kg	-

**Irritation/Corrosion:** Irritant to skin and mucous membranes

**Sensitization:** May cause an allergic reaction when in contact with skin.

**Mutagenicity:** Not classified.

**Carcinogenicity:** Not available.

**Reproductive Toxicity:** Not available.

**Teratogenicity:** Not available.

**Specific Target Organ Toxicity (Single Exposure):** No data.

**Specific Target Organ Toxicity (Repeated Exposure):** Not available.

**Aspiration Hazard:** Not available

**Likely Routes of Exposure:** Inhalation, Dermal, Ingestion.

### Potential Acute Health Effects:

Eye Contact: May cause eye irritation.

Inhalation: Not applicable.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: Not applicable

**Potential Chronic Health Effects:** Not Available.

**Numerical Measures of Toxicity:**

Acute Toxicity Estimates: Not available.

## Section XII - Ecological Information

**Toxicity:** Very toxic for aquatic organisms.

**Persistence and Degradability:** Not Available

**Bioaccumulative Potential:**

**Mobility in Soil:**

Soil/water Partition Coefficient (Koc): Not available

Other Adverse Effects: No known significant effects or critical hazards.

## Section XIII - Disposal Considerations

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

**Disposal Methods:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

**Special Precautions:** This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, water ways, drains and sewers.

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



## Section XIV - Transportation Information

### DOT (DEPARTMENT OF TRANSPORTATION)

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

Marine Pollutant: Yes

Please refer to DOT regulations for more info

### Canada (TDG)

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

Please refer to TDG Regulations for more info

### International Air Transport Association (IATA)

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

ERG Code: 3L

Marine Pollutant: Yes

Please refer to IATA regulations for more info.

### International Maritime Organization (IMO)

Technical Name: Adhesives containing flammable liquid

Hazard Class: 3

NA/UN Number: 1133

Packing Group: III

EmS: F-E, S-D

Marine Pollutant: Yes

Please refer to IMO regulations for more info.

**Special Precautions for User:** Transport within users' premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.


## Section XV - Regulatory Information

### United States Federal Regulations:

#### Sara Title III - Section 311/312

<u>Criteria</u>	<u>Yes/No</u>
Immediate (Acute) Health Effects:	No
Chronic (Delayed) Health Effects:	Yes
Fire Hazard:	No
Sudden Release of Pressure Hazard:	No
Reactivity:	No

### State Regulations:

California Prop 65 -  **WARNING:** This product can exposure you to chemicals including dibutyl phthalate, which is known to the state of California to cause reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Section XVI - Other Information

### Hazardous Material Information System (United States):

Health	1
Flammability	1
Physical Hazards	0

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a

# SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Gold Evolution – SSP Translucent (250 ml Cartridge)**

Issue Date: 5/25/2023

Revision Date: 3/1/2024

SDS Number: 200-33505



registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (United States):**

**Flammability:** Not Determined

**Health:** Not Determined

**Instability/Reactivity:** Not Determined

**Special:** Not Determined

Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**MANUFACTURER DISCLAIMER:** This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.