

Section 1. Product and Company Identification**Product Name:** GranQuartz Lithium Silicate Densifier**Product use:** Dustproofing Hardener**Effective Date:** October 1, 2024

Replaces: NEW

Manufacturer Information: GranQuartz
455 Satellite Boulevard
Suwanee, GA 30024
800-458-6222
www.granquartz.com**Emergency Phone Number:** INFOTRAC (24-hr/7 days): 1-800-535-5053
Outside the United States: Call collect 1-352-323-3500
For Medical Emergency: Call 1-800-535-5053 CN109479**Section 2. Hazard Identification****GHS Pictograms:****GHS Signal Word:** WARNING

This product is alkaline. Avoid contact with eyes and skin. Keep out of reach of children.

The product may be harmful if it is inhaled or swallowed.

POTENTIAL HEALTH EFFECTS:**CODE OF HAZARD STATEMENTS:****Physical hazards**

None.

Health Hazards

H303-may be harmful if swallowed.

H312-Harmful in contact with skin.

H319-Causes serious eye irritation.

H333-May be harmful if inhaled.

Environmental hazards

None.

CODE OF PRECAUTIONARY STATEMENTS:**General**

P101-Keep out of reach of children.

P103-Read label before use.

Prevention statements

P202-Do not handle until all safety precautions have been read and understood.

P262-Do not get in eyes, on skin or on clothing.

P264-Wash thoroughly after handling using this product.

P280-Wear protective gloves/protective clothing/eye protection/face protection.

P284-Wear respiratory protection.

Response statements

P312-Call a POISON CENTER or doctor/physician if you feel unwell.

P331-DO NOT induce vomiting.

P340, Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P352, Wash with plenty of soap and water.

P362, Take off contaminated clothing and wash before reuse.

Storage

P403-Store in well-ventilated place.

P404-Store in a closed container.

P412-Do not expose to temperatures exceeding 60 °C (140 °F)

ROUTES OF ENTRY: Eye contact, skin adsorption, ingestion and inhalation.**CARCINOGENICITY:** None known at this time.

Section 3. Ingredients and Hazards Identification

| Components | | | | |
|-------------------|------------|-----------|-------------|--------------|
| Component | CAS # | EINECS No | % by weight | REACH Reg. # |
| Lithium Silicate | 12627-14-4 | 235-730-0 | 10-50 | Yes |
| Silane | Prop. | Prop. | 1-10 | |
| Water | 7732-18-5 | 231-791-2 | Balance | No |

Note. REACH Reg. # is the combination of the EINECS # and CAS #. The REACH Reg. # for lithium silicate is 235730012627144.

Section 4. First Aid Measures

Eye Contact: Flush eyes with water immediately while holding eyelids open. Remove contacts, if worn, after initial flushing and continue flushing for at least 15 minutes. Seek medical attention if irritation persists.

Skin Contact: Use soap and water to remove from the skin, remove contaminated clothing, clean thoroughly before reuse.

Inhalation: Move to fresh air. If not breathing, give rescue breathing. If breathing is difficult, give oxygen. Seek medical attention if breathing is still difficult.

Ingestion: If swallowed, get medical attention immediately. **DO NOT INDUCE VOMITING.** Never give anything by mouth to an unconscious person.

Section 5. Fire Fighting Measures

Flash Point: Not flammable Flammability Limits: NE

Fire Fighting Media: Dry chemical, carbon dioxide, and water spray.

Special Fire Fighting Procedures: First responders need to wear full-bunker gear with SCBA, never enter a confined space unless fully protected with proper personal protective equipment (PPE). Material is alkaline and may cause the floor to be slippery.

Section 6. Accidental Release Measures

Clean-up Procedures: Material is alkaline wear proper PPE. Stop the source of the release if you are not put at risk. Use absorbent material (such as sand or kitty litter) to absorb the spill, use plastic shovel to pick up absorbent for disposal.

Spills and Leaks: Dispose in accordance to local, state or federal regulations.

Section 7. Handling and Storage

Handling: Do not get into eyes. Do not taste or swallow. Wash thoroughly after handling.

Storage: Store in original labeled container. Keep in cool and dry areas. Do not exceed 60 °C (140 °F).

Section 8. Exposure Control/Personal Protection

Introductory Remarks: Consider the potential hazards of this product outlined in section 3. Use process exposures such as local exhaust ventilation, to control over exposure to airborne levels above recommended exposure limits.

Personal Protection:

Eyes: Wear safety goggles or safety glasses to prevent eye contact.

Body: Long sleeve shirts, long pants, socks, rubber boots and chemical resistant gloves.

Hands: Chemical resistant gloves

Respiratory: Wear an approved respirator (NIOSH TC-84A rated or EN 14387) that provides protection from this product if the airborne concentrations exceed the recommended exposure limits. **Other:** None

Section 9. Physical and Chemical Properties

| | | | |
|----------------------------------|--------------------------------------|-------------------------|----------------------------|
| Odor/Color | Slight to none / opaque, dries clear | Vapor Pressure | < 2.0 torr @ 68 °F (20 °C) |
| pH | 11-12 | Density(water=1) | 1.05 @ 68°F (20 °C) |
| % Volatile by weight | < 90 | Solubility | > 99 % in water |
| Evaporation rate(water=1) | < 1.0 | Boiling Point | 212 °F (100 °C) |
| Freezing point | 0 °C (32 °F) | | |

Section 10. Stability and Reactivity

Chemical Stability: Considered stable under normal ambient temperatures.

Hazardous Decomposition: If complete combustion, oxides of carbon and silicates are formed.

Hazardous Polymerization: Will not occur

Incompatibility~ Materials to Avoid: May react with strong oxidizing agents, strong acids and metal salts.

Section 11. Toxicological Information

Acute Eye Irritation: Irritating.

Acute Skin Irritation: Chronic exposure may be irritating.

Acute Dermal Toxicity: Not expected to be toxic through the skin.

Acute Inhalation Toxicity: Not determined, expected to be an irritant to the respiratory system.

Carcinogenic Effects: None

Existing Medical Conditions Aggravated by Exposure: Exposure to eyes and skin may cause irritation to pre-existing conditions.

Section 12. Ecological Information

Ecotoxicity: The toxicity of this product has not been determined.

Environmental Fate: This product should be expected to be readily biodegradable.

Section 13. Disposal Considerations

Waste Disposal Method: What ever cannot be saved for recovery or recycling should be managed by the local, state or Federal Regulations.

Container Handling and Disposal: All containers should be triple rinsed and disposed of according to local, state and Federal regulations.

Section 14. Transport Information

Ground Classification: Not regulated by US DOT

Shipping Name: GranQuartz Lithium Silicate Densifier

Technical Shipping Name: None

UNFIC: None

ID Number: None

Packaging Group: None

Labels: No US DOT Labels

Not regulated by IATA or IMO

| |
|---|
| Section 15. Regulatory Information |
|---|

EPCRA 311/312 Categories: Immediate (Acute) Health Effects: Yes
 Delayed (Chronic) Health Effects: Yes
 Fire Hazard: No
 Sudden Release of Pressure: No
 Reactivity: No



European Community: irritating (Xi) substances

Right to know classification: All ingredients are listed in PA and NJ.

TSCA: All ingredients listed or exempt from listing.

Reportable Quantity (RQ): None

Prop. 65: None

WHMIS: Xi (Irritant to the eyes and skin)

All ingredients are listed as chemical inventories of ACIS, ECL, EEC, ENCS, EU, Israel, MAC, MAK, MITI,

PICCS, SWISS, Taiwan, USA and UK

ABBREVIATIONS:

| | | | |
|--------|--|--------|--|
| CAS # | Chemical Abstract Service Number | EINECS | European Inventory of existing Commercial Chemical Sales |
| °C | Celsius temperature scale | °F | Fahrenheit temperature scale |
| Prop. | Proprietary | PE | Personal Protective Equipment |
| TLV | Threshold Limit Value | TWA | Time Weighted Average |
| STEL | Short-term Exposure Limit | PEL | Permissible Exposure Limit |
| OSHA | Occupational Safety & Health | NIOSH | National Institute of Safety & Health |
| NFPA | National Fire Protection Agency | WHMIS | Workplace Hazardous Materials Information System |
| NTP | National Toxicology Program | IARC | Int. Agency for Research on Cancer |
| RCRA | Resource Conservation Recovery Act | TSCA | Toxic Substance Control Act |
| EC50 | Effective Dose | LC50 | Lethal Inhalation Concentration |
| LD50 | Lethal Dose | CAS | Chemical Abstract Service Number |
| LEL | Lower explosive limit | UEP | Upper explosive limit |
| NDA | No Data Available | ND | Not determined |
| NE | None established | NA | Not Applicable |
| < | Less Than or Equal To | > | Greater Than or Equal To |
| CNS | Central Nervous System | CI | China |
| DSL | Canada | ECL | Korean Existing Chemicals List |
| EEC | European Economic Commission | ENCS | Japanese Existing and New Chemical List |
| EU | European Union | MAC | Netherlands |
| MAK | Germany | MITI | Japan |
| PICCS | Philippines | SWISS | Giftliste 1 |
| UK | United Kingdom | USA | United States |
| VOC | Volatile organic content | ACGIH | American Conference of Government Industrial Hygienists |
| SARA | Superfund Amendments and Reauthorization Act | | |
| AICS | Australian Inventory of Chemical Substances | | |
| IARC | International Agency for Research on Cancer | | |
| Taiwan | List of Toxic Chemical Substances regulated under Taiwan Toxic Chemical Substances Control Act of 1086 | | |

| |
|--------------------------------------|
| Section 16. Other Information |
|--------------------------------------|

Hazardous Material Information (HMIS)**National Fire Protection Association (NFPA)**

| | | | |
|---------------------|---|---|-------------|
| Health | 1 | 1 | Health |
| Fire | 0 | 0 | Fire |
| Reactivity | 0 | 0 | Instability |
| Personal Protection | C | | NA |

Health 4 Deadly 3 Extreme Danger 2 Dangerous 1 Slight hazard 0 No hazard

Fire 4 < 73 °C 3 < 100 °C 2 < 200 °C 1 >200 °C 0 Will not burn

Reactivity/Instability 4 – May detonate 3 Explosive 2 Unstable 1 Normally stable 0 Stable

Risk phrases: R36, Irritating to eyes; R37, Irritating to respiratory system; and R38, Irritating to skin.

Safety phrases: S2, Keep out of reach of children; S24, Avoid contact with skin; S25, Avoid contact with eyes; S37, Wear suitable gloves; and S39, Wear eye/face protection.