



## One, Two, Three, Four, Buff... and Done!

This industry revolutionizing technology allows you to replace the traditional metal and resin bond series of 9 steps (50 grit resin - 100, 200, 400, 800, 1500, 3000, and well beyond 8000) with 2-5 steps! By using this system you can achieve as much as a 50% reduction in labor and time on the job, as well as reduction in the products needed to restore virtually all of the surface types you will encounter in the field. These pads are designed to be used on a standard 175-300 RPM swing machine and with water.

### STEP 1 PAD

Replaces traditional diamonds in 50, 100, 200 and 400 grit (i.e. the step one pad removes damage like a 50 grit traditional diamond but leaves the scratch pattern of a 400 grit pad).

### STEP 2 PAD

Replaces traditional diamonds in 200, 400, and 800 grit.

### STEP 3 PAD

Replaces traditional diamonds in 800, 1500, and 3,000 grit.

### STEP 4 PAD

Replaces traditional diamonds in 3,000 and 8,000 grit and beyond.

For the final polishing step we recommend using our 11,000 grit Monkey Pad for the highest color, clarity and gloss.

	CHEETAH PADS			
Size	Step 1	Step 2	Step 3	Step 4
17"	CP17S1E	CP17S2E	CP17S3E	CP17S4E
20"	CP20S1E	CP20S2E	CP20S3E	CP20S4E

17" shown

"I have been using the Cheetah Pads for about 5-6 years with great success. I have tried DIP pads with good results, but I find more comfort with the Cheetah's. There is no guessing on the wear of the pads and getting consistent cuts. Plus I find the life expectancy for Cheetah's to be a better value."

~ Galen Roth, Roth Restoration, South Carolina

Our 5" and 8" Cheetah Pads are manufactured using our same proprietary technology as our floor pads but are designed with a different configuration to allow for more surface contact for smaller hand work jobs. These pads work great for countertop work, shower stalls, edge work and stairs.

They are best suited to use on a variable speed hand grinder/polisher so you can use the low speed for the grinding and the higher speeds for your final polish.

These pads also work great underneath planetary style machines for floor work.

Our 17 and 20 inch pads are designed to be used on a 175 rpm standard swing machine.



	CHEETAH PADS			
Size	Step 1	Step 2	Step 3	Step 4
5"	CP5S1E	CP5S2E	CP5S3E	CP5S4E
8"	CP8S1E	CP8S2E	CP8S3E	CP8S4E

*Pro tip:* Using an additional dry 11,000 grit Monkey Pad for a quick final pass will give you just a little more color and clarity in some situations.

## CHEETAH PUCKS

Cheetah Pucks are suited to all types of restoration but are geared towards the more seasoned stone restoration professional. These are recommended for your most aggressive restoration needs such as terrazzo, concrete, granite and lippage removal jobs. They are available in 5" attachments and attach to a Velcro riser or weighted drive plate. They replace the same traditional metal and resin bond diamonds as our Cheetah Pads.



17" riser with  
4 Cheetah Pucks



20" riser with  
5 Cheetah Pucks

	CHEETAH PUCKS			
Size	Step 1	Step 2	Step 3	Step 4
5"	CP5PUCK1E	CP5PUCK2E	CP5PUCK3E	CP5PUCK4E