

## CONSTRUCTION COMPRESSION SPRAYERS – ACETONE

**ACETONE**

Designed to resist the application of acetone in the construction like acetone concrete sealers, acetone deco concrete stains and low voc acetone solvents.

- Even when they look like normal sprayers these particular models are built to resist acetone because of the materials and EPDM seals.
- Very strong tank, designed to last long, also light to be carried easily.
- The hose connects to the tank for the lower side to guarantee a full discharge of the liquid. It includes a spring that helps the hose not to get clogged.
- The compression system made of polypropylene assures a long service without problems and low maintenance needed.
- The spray wand is made of brass, plastic flat fan nozzle and shut-off valve with filter.
- You can pressurize the tank with an external air font in has a shredder valve.



# CARACTERÍSTICAS TÉCNICAS

SPECIFICATIONS	DESCRIPTION			
N° Cat.	310135l	319305	322310	189310
Total tank capacity	0.53 gal	1.9 gal	3.5 gal	3.9 gal
Capacity of use	0.4 gal	1.3 gal	2.3 gal	3.9 gal
Straps	N/A	Polyester non absorbent 1.5" width		
Pumping system	Compression			Piston
Piston sleeve	N/A	Elastomer 1.4 "		
Working pressure	22 - 36 psi 1.5 - 2.5 bar			87 psi - 6 bar
Aprox. Weight	1 lb	5 lb	6.8 lb	11 lb
Hose	N/A	EPDM 38 "		
Shut-off valve	N/A	Professional ergonomic with filter		N/A
Spray wand	N/A	Brass 20.5"		
Nozzle	N/A	Plastic: fan and holo cone		Fan tip plus hollow cone tip



Cleaning and dissolving

## BENEFITS:

This is the preferred model that combines:

- Easy to use , very soft pumping

- Security:

One piece tank

Anti spillage

Spraying system that supports good pressure

Tank with a base

- Commodity:

Shut-off valve with handle

Good straps to carry

- Application

Very safe and steady.

