

Technical Data Sheet

719 Series

Used with flat-bed or friction feed plotters and also available with slot fed or tractor fed computer holes, this product is intended to be used with stone and smooth surfaces. This product has a clear polyester liner on the outside along with a yellow film between the rubber and outside liner to hold centers in place when transferring designs. Available in 10 yard or 20 yard length rolls.

12-3/4 to 30" 10 Yard Roll Slot Fed (YPS) Tractor Fed (YPT) Friction Fed (Y)

Standard Widths

12-3/4" 18-3/4" 15" 27-1/2" 25" 32-3/4"

30"

Storage & Shelf Life

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/-6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

Nominal Values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive

Regular

Total Thickness (mil)

49 (1.24 mm)

Tensile Strength (lbs/in)

5.7(25.90 N/25mm)

180° Adhesion to Steel (oz/in)

42(11.89 N/25mm)

Elongation (% at break)

390

l iners

Clear PET outside liner with yellow PET middle liner

Get in touch

www.Ublaststencil.com



Phone

706-283-2289 706-283-2280 Toll free

1-855-590-7070

Fax

706-283-2290



=mail

1039 Crosstie Drive, Elberton, GA 30635



Address

info@ublaststencil.com

^{*}Only 15" and 30" available for YPS models