



**MAKINEX**<sup>®</sup>

# Power Solutions Power Generator 16 kW

## Highly Portable 16kW 480V Dual Phase Generator



**Compact Design**



**Dual Phase Outlets**



**16kW Output**

Unleash Versatile Power. This compact and portable 16kW 480V generator is your dual-phase solution, driven by an advanced radial flux alternator for high-frequency and inductive load capabilities. Bid farewell to tow-behind generators and embrace its compact size. A galvanized frame ensures robust reliability. RCD and RCBO protection enhance equipment and user safety, while eliminating downtime for 480V three-phase power setup.



### SPECIFICATIONS:

Voltage	120/480V Single Phase; 480V Three Phase
Frequency	60HZ
Max output	2500W (120V) / 13500W (480V)
Rated output	2500W (120V) / 12500W (480V)
Rated power factor	0.8
Max Amps single phase	30A @ 240V
Max Amps three phase	30A @ 480V
Sockets provided	120V GFCI receptacle / 480V 3 phase receptacle (30 amp)
Dry weight	342lbs/155kg
Noise level (7m)	NO LOAD - 72dB
Engine type	Twin cylinder Air Cooled Petrol
Engine model	Honda GX690
Starting system	Key Start
Displacement	688CC
Fuel economy	0.92gal @ 50% LOAD
Fuel tank	9.0G/34L
Dimensions	30.4in/773mm (L) x 20.8in/530mm (W) x 35.5in/902mm (H)

Outlets Provided	9kW	16kW 240V	16kW 480V	23kW 480V
50A Three-Phase		 CS8369		 CS8369
50A Single-Phase		 CS6369		
30A Three-Phase	 L15-30R		 L16-30R	 L16-30R
30A Single-Phase	 L6-30R	 L14-30R		 L6-30R
20A Single-Phase	 20A GFCI	 20A GFCI	 20A GFCI	 20A GFCI

**Ideal For:**



Concrete Cutting



Concrete Coring



Back-Up Power



Welding



Construction



Film Studios



## Features:



1. Electric / Key Start



2. 2x 30A Single Phase sockets



3. 1 x 50A Three phase socket



4. Galvanised Durable Frame



5. Lightweight – 342lbs/155kg

## Makinex Generator Range:



1. Power Generator 9 kW



2. Power Generator 23 kW



3. Power Generator 32 kW