

# COBBLE COAT™ HIGH SOLIDS

*Solvent-Based Clear Sealer for  
Concrete Pavers, Natural Stone, and  
Concrete Surfaces*

- Wet look appearance
- Years of protection against sun and water damage
- Prevents color of pavers from fading
- Non-yellowing
- Stabilize joints between pavers, preventing mold and algae growth, weeds, and anthills





# COBBLE COAT™ HIGH SOLIDS

Product Numbers: 132-1G (1 Gal.), 132-5G (5 Gal.)

## Product Description

Surfacelogix® Cobble Coat High Solids is a water clear, solvent-based sealer designed to protect and beautify interlocking brick pavers, concrete floors, and Texture Deck. Cobble Coat High Solids is made from 100% acrylic resins and is higher in solids than most conventional concrete sealers. Cobble Coat provides excellent resistance to water and UV light with unusually good adhesion to a variety of substrates.

Use Cobble Coat High Solids on driveways, patios, pool decks, parking lots, walkways, etc. constructed of concrete pavers, concrete, or natural stone. Cobble Coat High Solids is not recommended for pavers installed over a solid surface or on surfaces where moist moisture is unable to dissipate.

## How To Use

**Before You Begin:** Surfaces must be clean and free of any contaminants before sealing. Cobble Coat High Solids' performance is directly related to how thoroughly the surface is prepared. All grease, oil and potential contaminants must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results. Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. SurfaceLogix® Cobble Clean, Cobble Prep, and Cobble Oxhide may be used for specific cleaning situations.

**Mixing:** Stir product.

### Applications:

**Roller:** Apply with a 3/8" to 3/4" nap roller cover. Avoid over rolling. Always maintain a wet edge.

**Airless Sprayer:** Spray by overlapping each pass.

Always apply in an even film deposit and maintain a working wet line.

**On Bare Surface:** One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces.

**Over Previously Sealed Surface:** One coat is recommended. Do not apply more frequently than every 18 months to avoid a build up of sealer.

**Clean Up:** Clean sprayer and tools with SurfaceLogix® Reducer immediately after use. Leave Reducer in the line of machine after flushing with water.

**Maintenance:** Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

## Additional Information

**Coverage:** 200 to 300 sq. ft. per gallon per coat. Coverage will depend on surface porosity, joint width, and method of application. Second coat will take slightly less product.

**Curing:** Dry to Touch: 1 hr., Recoat: 4 hrs., Full Cure: 48 hrs.

**Packaging:** Available in 1-gallon pail (8 lbs.) and 5-gallon pail (45 lbs.). 132-1G: 4 per case, 180 per pallet. 132-5G: 36 per pallet.

**Storage & Shelf Life:** Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

**Technical Data Sheet:** Additional product information can be found on this product's technical data sheet (TDS). Scan the QR code to view the TDS.

