



COBBLE LOC™ **WITH GRIP**

*Anti-Slip Waterborne Clear Sealer for
Concrete Pavers, Natural Stone, and
Concrete Surfaces*

- Eco-friendly and low-VOC
- Pressure clean and seal in the same day
- Locks down paver joint sand and inhibits mold, weeds, and ant hills
- Catalyzed product that resists chemicals and oil
- Top coat for colored sealers and surface treatments such as Coloron, Colorcrete, Antique Stain, TD One Step, and Texture Deck

COBBLE LOC™ WITH GRIP

Product Numbers: 131G-1G (1 Gal.), 131G-5G (5 Gal.)

Product Description

Surfacelogix® Cobble Loc with Grip carries the newest technology in waterborne sealers for concrete, brick pavers, and other hardscape surfaces, together with enhanced grip for hard surfaces like decks and walkways that may be slippery. Cobble Loc with Grip may also be used over most porous surfaces as it has excellent water and marking resistance, and at the same time, improves anti-slip properties. Unlike other clear finishes, Cobble Loc with Grip contains a transparent additive that provides a rough finish, yet maintaining its gloss finish and excellent resistance to chemicals.

Use Cobble Loc with Grip on driveways, pool decks, entryways, walkways, median strips, and patios. Cobble Loc with Grip is not recommended for pavers installed over a solid surface or on surfaces where moisture is unable to dissipate.

How To Use

Before You Begin: Surfaces must be clean and free of any contaminants before sealing. Cobble Loc with Grip performance is directly related to how thoroughly the surface is prepared. Do not apply when the temperature of the air or the surface to be coated is below 50°F or above 100°F. Testing on a small area of your surface is always recommended to ensure desired results. Smooth concrete must be etched. Scrape and sand all loose material prior to application. Surfacelogix® Cobble Clean, Cobble Prep, and Cobble Oxhide may be used for specific cleaning situations.

Mixing: Cobble Loc with Grip is a two-component kit. Part A must be mixed with Part B. A 1-gallon kit includes a quart of Part B, and a 5-gallon kit includes a short filled 5-gallon pail and a 1-gallon pail of Part B. Dilute one part of mixed sealer with one part water. (Mix will become thick, but will flow immediately after adding water). For best results, it is recommended to

mechanically mix with a power mixer for a minimum of 10– 15 minutes, before applying.

Applications: Roller: Using rollers to apply Cobble Loc with Grip is not recommended. If necessary, rollers may be used to back roll excess sealer.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line; do not over-apply. On Bare Surface: One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces. Over Previously Sealed Surface: One coat is recommended.

Clean Up: Clean sprayer and tools with water and Surfacelogix® Cobble Clean immediately after use. Flush water through the line of the sprayer until clear.

Maintenance: Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios. Rinse with water.

Additional Information

Coverage: 200 to 300 sq. ft. per gallon per coat. Coverage will depend on surface porosity, joint width, and application method. Second coat will take slightly less product.

Curing: Dry to touch: 2 to 6 hrs. (varies with conditions). Recoat: 2 to 6 hrs. Full Cure: 48 to 72 hrs.

Packaging: Available in 1-gallon cans (9 lb.) and 5-gallon pails (45 lb.). 131G-5G: 4 per case, 180 per pallet. 131G-1G: 36 per pallet.

Storage & Shelf Life: Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 80°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

Technical Data Sheet: Additional product information can be found on this product's technical data sheet (TDS). Scan the QR code to view the TDS.

