

Technical Data Sheet

Page 1 of 2

- Properties:** AKEMI® Polishing Fluid No. 10-2012 is a fast-hardening product made of highly efficient waxes and synthetic resins, dissolved in hydrocarbons. Treated areas obtain a brilliant, anti-slippery surface with a strong colour intensification.
- Application Area:** AKEMI® Polishing Fluid No.10-2012 is suited for the care of floors, staircases or window sills made of fine-ground or polished natural and artificial stone, e.g. marble, granite, slate, terrazzo, travertine and similar for indoor use. The quality corresponds to the classic "edge finishing fluat".
- Instructions for Use:**
1. Clean the surfaces thoroughly with AKEMI® Stone Cleaner. They must be clean and absolutely dry before use of AKEMI® Polishing Fluid No. 10-2012. Ideal temperature for application 15 - 25°C.
 2. Apply a thin layer with a cloth or brush, for larger areas apply with a mop.
 3. Repeat application on very absorbent, non-polished surfaces.
 4. Polish surfaces with a soft cloth or a white nylon pad and a floor polishing machine when their appearance has become dull.
 5. For regular cleaning use AKEMI® Mild Stone Soap.
- Special Notes:**
- For professional use only.
 - Use afin® Liquid Glove to protect your hands.
 - Objects in the working area which are not resistant to solvents, s.a. various synthetic materials, rubber, lacquered areas, must be protected.
 - At temperatures below 9°C the product becomes viscous, below 0°C it becomes almost solid.
 - Storage at a temperature of 15°C will render it ready to be worked again.
 - Apply the product in a thin layer, only, otherwise the surface will not take a good polish.
 - Films of polishing fluid can be removed by AKEMI® Wax Stripper.
 - For proper waste disposal, the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Technical Data:**
- | | |
|-----------|---------------------------------------|
| Colour: | Slightly yellowish |
| Coverage: | approx. 15 - 30 m ² /liter |
| Density: | approx. 0.75 g/cm ³ |
- Storage:** If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 24 months from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.

TDS 02.22

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.