



PROSOCO®

# Consolideck®

CONCRETE FLOORING PRODUCTS

## Wax & Cure Remover

Easy-to-use Consolideck® Wax & Cure Remover preps concrete floors for hardening and densifying or other penetrating protective treatments, as well as grinding and polishing.

The low-odor cleaner quickly removes a variety of waxes and acrylics – including most lower-solids cure and seals – from concrete floors. That leaves the concrete free of old coatings that can block treatments from penetrating, or clog up the heads on grinding and polishing equipment.

Water-rinsable Wax & Cure Remover can be used in concentrate, or diluted with fresh water, depending on the job.

### ADVANTAGES

- Removes waxes, acrylics and most low-solids cure & seals from concrete floors.
- Low odor for interior use.
- Does not affect concrete color.
- Contains readily biodegradable materials.

### Limitations

- Surfaces are slippery during application. Use appropriate caution.
- Product efficiency is reduced in cold temperatures.
- May damage synthetic or reflective glass.

### REGULATORY COMPLIANCE

#### VOC Compliance

Consolideck® Wax & Cure Remover is compliant with compliant with all national, state and district VOC regulations.

### TYPICAL TECHNICAL DATA

<b>FORM</b>	Colorless liquid
<b>SPECIFIC GRAVITY</b>	1.05
<b>pH</b>	not applicable
<b>WT/GAL</b>	8.76 lbs
<b>ACTIVE CONTENT</b>	not applicable
<b>TOTAL SOLIDS</b>	not applicable
<b>VOC CONTENT</b>	4% maximum
<b>FLASH POINT</b>	>200° F (>93° C) ASTM D 3278
<b>FREEZE POINT</b>	not applicable
<b>SHELF LIFE</b>	2 years in tightly sealed, unopened container

### SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

**24-Hour Emergency Information:**  
**INFOTRAC at 800-535-5053**

# Product Data Sheet

## Consolideck® Wax & Cure Remover

### PREPARATION

Protect people, vehicles, property, painted surfaces, plants and all surfaces not set for cleaning from product, splash and wind drift. Protect and/or divert pedestrian and auto traffic.

Some metal finishes and glass installed in recent years may be damaged by product. Test or protect if needed.

### Surface and Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 50°F (10°C).

Do not apply at temperatures below 40°F (4°C). If freezing conditions exist prior to application, let concrete thaw.

### Equipment

Apply with a long-handled brush or mop and pump-up sprayer. Use a brush or scrubbing machine for light scrubbing. Use a mop or wet vac as needed to take up the spent cleaner and debonded coating.

Pressure-wash (under 1,000 psi) or mop with fresh water only if needed to remove excess residue.

### Storage and Handling

Store in a cool, dry place away from other chemicals. Keep tightly closed when not dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory sealed containers in a dry place. Maintain temperatures of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

### APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

**ALWAYS TEST** a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

### Dilution & Mixing

Dilute with clean water.

*Light Wax Build-up:*

1 part product to 10 parts water

*Heavy Wax Build-up:*

1 part product to 3 parts water

*Low-Solids Cure & Seals:*

Full strength

### Coverage Rates

Coverage varies based on concrete porosity and texture. Always test. Coverage stated is per gallon of prepared cleaner.

- 300–500 square feet
- 28–47 square meters

### Application Instructions

1. Apply with low-pressure spray.
2. Allow to dwell for 5–10 minutes.
3. Scrub with a stiff bristle brush or a mechanical scrub machine.
4. Take up as much spent cleaner and dissolved coating as possible.
5. Rinse or mop the floor with fresh water, if needed.

### Cleanup

Clean tools and equipment with fresh water.

### BEST PRACTICES

Allow more dwell time for Wax & Cure Remover in temperatures below 50°F (10°C). In rare instances where floors are exposed to freezing temperatures, make sure the concrete is thawed out and surface temperature is above 40°F (4°C).

Make sure cleaned floors are free as possible of spent cleaner and debonded coatings. A thorough mop, wet-vac or machine scrub usually gets up enough residue so the cleaned floor can be treated, once dry.

Surfaces are slippery during application. Use appropriate caution.

If needed, mop or pressure-rinse the cleaned floor with fresh water to flush away excess.

To remove higher-solids cure and seals, use Consolideck® Cure & Seal Remover.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free, at 800-255-4255.

# Product Data Sheet

## Consolideck® Wax & Cure Remover

### **WARRANTY**

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of

this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

### **CUSTOMER CARE**

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care – technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at [www.prosoco.com](http://www.prosoco.com), for the name of the PROSOCO representative in your area.

