

Solvent Blend to Restore Acrylic Sealers

Restore-A-Seal is a strong blend of key solvents and surfactants designed to emulsify and re-flow old and faded solvent-based acrylic sealers. Thick layers of old sealer with a dingy, dull look can be made fresh again. Restore-A-Seal penetrates down through the deepest layers of sealer to help the acrylics soak back into the concrete substrate, removes trapped moisture, and helps eliminate blushing.

Restore-A-Seal is also used prior to resealing. Some older acrylic sealers can get very hard and brittle after exposure to the elements. Saturating a previously sealed surface with Restore-A-Seal before the new coat is applied softens the existing acrylic, giving the new sealer a stronger bond for better service life.

Typical Uses:

- **Stamped and Decorative Concrete**
- **Stained Concrete**
- **Exposed Aggregate**
- **Prior to Re-Sealing**

Product Advantages :

- **Removes Trapped Moisture**
- **Pure Solvents, Zero Solids**
- **Works at Lower Temperatures**
- **Alternative to Stripping Old Coating**
- **Works Faster than Xylene**

Coverage:

Typical application rate 150-250 sq ft per gallon. Especially thick coatings may require multiple applications.

Directions for Use:

Substrate Preparation:

ENVIRONMENTAL CONDITIONS: Rain should not be forecast for 24 hours after application. Water present on the surface or high humidity may lead to undesired results. Product should be applied when surface temperature is between 40° and 80° and at least five degrees above the dew point.

Mixing Instructions:

Material should be stirred well prior to application. Long term storage may allow material to separate.

For Use on Solvent-Based Sealers Only

Substrate Temperature – 40° to 80° F

VOC Content - <100 g/L

Packaging:

1-Gallon Cans | 5-Gallon Pails

FOR PROFESSIONAL USE ONLY

Technical Data Sheet

Application Instructions:

Use soap and water to thoroughly clean the surface prior to application. Product will work more effectively when applied during the cooler part of the day, allowing a longer dwell time. Apply with a pump-up sprayer resistant to Xylene, or by using a solvent-resistant paint roller. Apply evenly to the surface. Use enough Restore-A-Seal to completely re-wet the existing sealer through to the bottom layer. Agitating the wetted surface with a roller will aid in softening the existing sealer faster. If needed repeat the process after the sealer is hard enough to walk on. Allow the sealer to dry at least 24 hours before returning to foot traffic, and at least 48 hours before heavy traffic.

When used prior to re-sealing wait for the surface to become hard enough to walk on before applying the new coat of sealer. Wait times will vary with temperature. Generally, the application of the new sealer should begin no sooner than 2 hours and no longer than 6 hours after the surface is treated with Restore-A-Seal.

Slip Resistance Disclaimer:

Notice: The Occupational Safety and Health Administration (OSHA) and the American Disabilities Act (ADA) have set enforceable standards for slip-fall protection on walking surfaces. The ADA standards are the more stringent and require a minimum coefficient of friction (CoF) on level walking surfaces of 0.6 and on ramped walking surfaces of 0.8. The system applicator/ end user assumes all responsibility to provide a flooring system that meets all current safety standards. Neither Durável nor its selling agents will be responsible for any injury that may be incurred in a slip-fall accident. Furthermore, Durável recommends the use of slip-resistant aggregate in all coatings or floor systems that could possibly be exposed to wet conditions or become contaminated with oils, grease, or other potential lubricants.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Protect from temperature extremes.

Disposal:

Recycle and/or dispose of contents and containers in accordance with local, regional, national, and international regulations.

Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature. May be extended with reasonable care.

Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range.

Technical Data Sheet

Warranty:

IMPORTANT!

Before using any Durável product, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY – VISIT Durável.com FOR THE LATEST VERSION.

Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

Safety Instructions:

For Professional Use Only

Keep Out of Reach of Children and Animals

Highly Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposures.

Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash hands and arms thoroughly after handling. Do not touch eyes. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Get emergency medical help immediately. IF ON SKIN: wash with plenty of water and soap. IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If exposed or concerned, get medical advice. Get medical help if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical help. If eye irritation persists: Get medical help. Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish.

Technical Data Sheet

PROP65 WARNING: This product contains chemicals known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Always Review SDS & Technical Data Prior to Use

