

## Technical Information Sheet

### **PREMIUM WATER BASED IMPREGNATOR EXCELLENT PROTECTION FROM OIL, GREASE AND WATER STAINS**

#### **APPLICATION**

313P is a water based impregnator that offers protection from both oil and water borne stains. 313P is easy and safe to use, has no smell and may be used for interior and exterior applications, on polished and unpolished surfaces. Ideal for all stone kitchen counter tops, bathrooms, furniture and floors.

#### **DIRECTIONS**

- 1) Clean surface with GranQuartz Stone Care Systems 515C.
- 2) Allow surface to dry completely (normally 24 hours) before impregnation treatment.
- 3) Apply 313P undiluted directly to small, manageable areas using a sprayer, brush or roller.
- 4) Allow 10 to 15 minutes for impregnator to penetrate the surface. Do not allow material to dry, re-wet where needed.
- 5) Apply a second coat, wet on wet.
- 6) Allow 5 minutes for penetration of second application.
- 7) Completely remove all excess material using a squeegee or towel. **No material should remain on surface.** Allow to dry for 48 hours before covering or beginning maintenance.

NOTE: 313P must be applied to completely dry surface. **This product may cause slight etching on polished surfaces such as marble, limestone, travertine, terrazzo and other calcium containing stone. Testing on these stones is imperative.** Always impregnate the entire surface in same work session to prevent color variations.

**Test in a small area prior to general application to determine application amounts and appearance.**

**COVERAGE:** 100 to 200 sq. feet per liter.

**CONTENTS:** propan-2-ol (CAS-No. 000067-63-0), water (CAS-No. 7732-18-5)

**VOC-INFO:** 95.0 g per liter

This coating is to be applied without thinning or diluting. Close container when not in use.

#### **EMERGENCY RESPONSE PHONE NUMBER**

**1-800-255-3924**

Made in Germany for:  
GranQuartz Stone Care Systems  
P.O. Box 2206 Tucker, GA 30085-2206  
1-800-458-6222