

Technical Information Sheet

POROUS STONE IMPREGNATOR **STAIN PROTECTION FOR HONED, TEXTURED & OTHER POROUS STONE**

APPLICATION

353P offers maximum protection from water borne stains for porous stone. 353P is a silicone impregnator specifically formulated for honed, textured and other porous stone (**not recommended for polished granite**) and is also excellent for masonry surfaces, unglazed clay tiles and grout. Used for interior and exterior applications, 353P allows the stone to breathe naturally, cures quickly and offers a totally natural appearance.

DIRECTIONS

- 1) Clean surface with GranQuartz Stone Care Systems 515C.
 - 2) Allow surface to dry completely (normally 24 hours) before impregnation treatment.
 - 3) Protect all solvent sensitive surfaces adjoining the work area.
 - 4) Apply 353P undiluted directly to small, manageable areas using a sprayer, brush or roller.
 - 5) Allow 10 to 15 minutes for impregnator to penetrate the surface. **Do not allow product to dry**, re-wet where needed.
 - 6) Apply a second application, wet on wet.
 - 7) Allow 5 minutes for penetration of the second application.
 - 8) Completely remove all excess product using a squeegee or towel. **No impregnator should remain on the completed surface.**
 - 9) Allow to dry for 48 hours before covering or beginning maintenance.
- Test in a small area prior to general application to determine application amounts and appearance.**

COVERAGE: 50 to 150 sq. feet per liter.

<Symbol GHS02> <Symbol GHS07> <Symbol GHS08> <Symbol GHS09> Danger
Hydrocarbons. Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Store locked up.

CONTENTS: naphtha (petroleum), hydrodesulphurized heavy (CAS-No. 064742-82-1)

VOC-INFO: 740.9 g per liter

This coating is to be applied without thinning or diluting. Close container when not in use.

EMERGENCY RESPONSE PHONE NUMBER

1-800-255-3924

Made in Germany for:
GranQuartz Stone Care Systems
P.O. Box 2206 Tucker, GA 30085-2206
1-800-458-6222