

Technical Information Sheet

COLOR ENHANCING IMPREGNATOR **MATTE FINISH STAIN PROTECTION FOR HONED, TEXTURED & OTHER POROUS** **STONE**

APPLICATION

355E is a color enhancing silicone impregnator intended for use on honed and textured stone only. 355E offers a high degree of protection that enhances the natural appearance of the stone without gloss and protects it from water based stains and mineral deposits. Use 355E in all interior and most exterior applications where color enhancement is desired. 355E is UV resistant and allows the stone to breathe naturally.

DIRECTIONS

- 1) Clean surface with GranQuartz Stone Care Systems 515C or for textured granite surfaces, with GranQuartz Stone Care Systems 725C.
- 2) Allow surface to dry completely (normally 24 hours) before sealing.
- 3) Protect all areas not to be impregnated
- 4) Apply 355E undiluted directly to small, manageable areas using a sprayer, brush or roller.
- 5) Allow 10 to 15 minutes for impregnator to penetrate the surface. **Do not allow product to dry**, re-wet where needed.
- 6) Apply a second coat, wet on wet.
- 7) Allow 5 minutes for penetration of the second application.
- 8) Completely remove all excess product using a squeegee or towel. **No impregnator should remain on the completed surface.**
- 9) Allow to dry for 48 hours before covering or beginning maintenance.
Test in a small area prior to general application to determine application amounts and appearance.

COVERAGE: 75 to 150 sq. feet per liter.

<Symbol GHS02> <Symbol GHS07> <Symbol GHS08> <Symbol GHS09> Danger
Hydrocarbons. Flammable liquid and vapour. May be fatal if swallowed and enters airways.
Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or
cracking. Keep out of reach of children. Keep away from heat/sparks/open flames/hot
surfaces. – No smoking. IF SWALLOWED: Immediately call a POISON CENTER or
doctor/physician. Do NOT induce vomiting. Store locked up.

CONTENTS: xylene (CAS-No. 001330-20-7), naphtha (petroleum), hydrodesulphurized
heavy (CAS-No. 064742-82-1), solvent naphtha (petroleum), light arom. (CAS-No. 064742-
95-6)

VOC-INFO: 740.4 g per liter

This coating is to be applied without thinning or diluting. Close container when not in use.

EMERGENCY RESPONSE PHONE NUMBER
1-800-255-3924

Made in Germany for:
GranQuartz Stone Care Systems

P.O. Box 2206 Tucker, GA 30085-2206
1-800-458-6222