

Technical Information Sheet

STONE SEALER/ENHANCER SATIN GLOSS SEALER FOR TEXTURED STONE SURFACES

APPLICATION

357E is a modified acrylic sealer/enhancer intended for use on textured stone only. 357E cures to an ultra hard and durable finish that enhances the natural appearance of the stone with a satin gloss while protecting it from oil, grease and mineral deposits. Use 357E in most interior applications where color enhancement is desired. 357E is UV resistant and allows the stone to breathe naturally.

DIRECTIONS

- 1) Clean surface with GranQuartz Stone Care Systems 515C or for textured granite surfaces, with GranQuartz Stone Care Systems 725C.
- 2) Allow surface to dry completely (normally 24 hours) before sealing.
- 3) Protect all areas that adjoin the work area.
- 4) Apply 357E undiluted directly to small, manageable areas using a sprayer, brush or roller.
- 5) Make sure 357E is evenly spread with no puddles and allow approximately 1 hour to dry.
- 6) If a second application is needed to achieve the desired appearance, repeat step 4.
- 7) To ensure proper curing, protect the surface from foot traffic and moisture for 8 to 12 hours or until completely hardened.

NOTE: Do not walk on the sealed surface until dry. ***Ensure that the subsurface setting materials have completely dried prior to using this product. The drying process may take several weeks in mud-set applications.***

Test in a small area prior to general application to determine application amounts and appearance.

COVERAGE: 75 to 175 sq. feet per liter.

<Symbol GHS02> <Symbol GHS07> <Symbol GHS09> Warning

Flammable liquid and vapour. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only outdoors or in a well-ventilated area. Immediately call a POISON CENTER or doctor/physician. Store locked up. Dispose of contents and container in accordance with local and national regulations.

CONTENTS: xylene (CAS-No. 001330-20-7), solvent naphtha (petroleum), light arom. (CAS-No. 064742-95-6)

VOC-INFO: 720.9 g per liter

This coating is to be applied without thinning or diluting. Close container when not in use.

EMERGENCY RESPONSE PHONE NUMBER

1-800-255-3924

Made in Germany for:
GranQuartz Stone Care Systems
P.O. Box 2206 Tucker, GA 30085-2206
1-800-458-6222