

## Technical Information Sheet

### **PROFESSIONAL IMPREGNATOR STAIN PROTECTION FOR POLISHED STONE**

#### **APPLICATION**

413S is a highly effective silicone impregnator designed for the **Stone Professional**. 413S is fast and easy to apply, cures quickly and offers long term stain protection on all polished stone surfaces. 413S is exceptionally effective on polished granite counter tops. 413S leaves the stone looking completely natural and is UV resistant.

#### **DIRECTIONS**

- 1) Ensure the surface is clean and completely dry.
- 2) Protect all solvent sensitive surfaces adjoining the work area.
- 3) Apply 413S with a sprayer, brush or paint roller. For floors, spray the material on manageable areas and roll with a paint roller to ensure even coverage.
- 4) Allow 10 minutes for penetration, then apply a second application wet on wet and allow 5 minutes more to ensure complete impregnation.
- 5) Remove all excess product from surface and dry thoroughly. **No product should remain on the surface.**

**Test in a small area prior to general application to determine application amounts and appearance.**

**COVERAGE:** 150 to 200 sq. feet per liter.

<Symbol GHS02> <Symbol GHS07> <Symbol GHS08> Danger

Carbohydrates, C9-C11, n-alkane, iso-alkane. Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local and national regulations.

**CONTENTS:** naphtha (petroleum), hydrosulphurized heavy (CAS-No. 064742-82-1)

**VOC-INFO:** 735.7 g per liter

This coating is to be applied without thinning or diluting. Close container when not in use.

#### **EMERGENCY RESPONSE PHONE NUMBER**

**1-800-255-3924**

Made in Germany for:  
GranQuartz Stone Care Systems  
P.O. Box 2206 Tucker, GA 30085-2206  
1-800-458-6222