

## Technical Information Sheet

### **HEAVY DUTY PORCELAIN, CERAMIC & GROUT CLEANER** **INTENSIVE DEEP CLEANING FOR TILE AND GROUT**

#### **APPLICATION – RECOMMENDED FOR PROFESSIONAL USE**

631C is a heavy duty alkaline based cleaner for use on porcelain, quarry tile and other unglazed ceramic tile and is excellent as a grout cleaner. **631C is not for polished stone.** 631C is especially suited for cleaning food service areas. 631C can be used for construction clean up, to remove wax coatings, to clean oil and grease spills and is highly effective in restoring tile and grout that have darkened with time due to ground-in dirt and wax.

#### **DIRECTIONS**

- 1) Remove any loose dirt or dust.
- 2) Mix 631C with clean water. See dilution rates below.
- 3) Wet surface with clean water prior to applying 631C solution.
- 4) Apply diluted solution with a sprayer or mop.
- 5) Scrub with mop, buffing pad or non-abrasive stiff bristle brush.
- 6) Allow solution to **dwelt on the surface for 10 to 30 minutes** making sure that solution does not dry on surface. Re-wet as needed.
- 7) After adequate dwell time, vacuum solution, flood rinse and vacuum again.
- 8) Continue to rinse until all solution has been removed.

**Test in a small area prior to general application to determine application amounts and appearance.**

**DILUTION RATES:** Periodic or food service area cleaning: 1 part 631C to 5 parts of clean water. Construction clean up: 1 part 631C to 2 parts of clean water. Old grout and heavy wax coatings: 1 part 631C to 1 part of clean water.

**COVERAGE:** 150 to 750 sq. feet per liter.

<Symbol GHS05> Danger

Sodium hydroxide, D-Glucopyranose, oligomeric, C10-16-alkyl glycosides. May be corrosive to metals. Causes severe skin burns and eye damage. Keep out of reach of children. Keep only in original container. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Store locked up.

**CONTENTS:** anionic surfactants, propan-2-ol (CAS-No. 000067-63-0), ethylene glycol monobutyl ether; butylcellosolve (CAS-No. 000111-76-2), sodium-hydroxide (CAS-No. 001310-73-2), water (CAS-No. 7732-18-5)

#### **EMERGENCY RESPONSE PHONE NUMBER**

**1-800-255-3924**

Made in Germany for:  
GranQuartz Stone Care Systems  
P.O. Box 2206 Tucker, GA 30085-2206  
1-800-458-6222