



Characteristics & Technical Data

% Solids by Weight (+/- 3%):	42%
QUV (ASTM D G-54):	2,000 hours with no gloss loss
WT./Gal	8.70 lbs.
Coverage:	200-300 SqFt/Gal @ 3mil DFT
Pot Life:	2 Hours
VOCs:	<50 G/L

1. Manufacturer

SurfaceLogix – a Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069
Phone: 954.971.9111
Fax: 954.971.6623
Email: support@surfalogix.net
surfalogix.net

2. Product Description

Cobble Loc with Grip carries the newest technology in waterborne sealers for concrete, brick pavers and other hardscape surfaces, together with enhanced grip for hard surfaces like decks and walkways that may be slippery. **Cobble Loc with Grip** may also be used over most porous surfaces as it has excellent water and marking resistance, and at the same time improves anti-slip properties. Unlike other clear finishes, **Cobble Loc with Grip** contains a transparent additive that provides a rough finish, yet maintaining its gloss finish and its excellent resistance to chemicals.

3. Applications

Use **Cobble Loc with Grip** on driveways, pool decks, entryways, walkways, median strips, and patios.

Cobble Loc with Grip is not recommended for pavers installed over a solid surface or on surfaces where moisture is unable to dissipate.

4. Properties & Special Features

- Eco friendly & emits super low VOCs.
- Provides an anti-slip surface finish
- Pressure clean and seal in the same day.
- Locks down paver joint sand.
- Inhibits mold, weeds and ant hills.
- Catalyzed product that resists chemicals.
- Top clear coat for colored sealers and surfaces that need grip.

5. Directions

Before You Begin: Surfaces must be clean and free of any contaminants before sealing. **Cobble Loc with Grip** performance is directly related to how thoroughly the surface is prepared. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results.

Surface Preparation: Smooth concrete must be etched. Scrape and sand all loose material prior to application. Cobble Clean, Cobble Prep and Cobble Oxhide may be used for specific cleaning situations.

Mixing Instructions: **Cobble Loc with Grip** is a two component kit. Part A must be mixed with Part B. Part A includes the grip enhancing additive.

A 1 gallon kit includes a quart of Part B & a 5 gallon kit includes a short filled 5 gallon pail and a one gallon can of Part B. Mix part A Cobble Loc with Grip & part B with a good power mixer for a minimum of 2 - 5 minutes, and then dilute 1 part of mixed sealer to one part of water with good mixing.

Applications: It is not recommended to apply **Cobble Loc with Grip** using rollers; only use if need to back roll to remove excess.



Clear Sealers: COBBLE LOC with GRIP
131A-6G-GRIP, 131A-1G-GRIP

Technical Data Sheet

COBBLE LOC with Grip

Semi Gloss Finish

5. Directions (Continued)

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line.

On Bare Surface: One coat is normally sufficient, however for porous surfaces and uncoated surfaces two thin coats (2 dry mils) provide the best results.

Over Previously Sealed: One coat is recommended.

6. Packaging

Size	Package	Per Case	Units / Pallet
1 gallon kit	Pail	4	148
5 gallon kit	Pail	N/A	36

9 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

7. Coverage

1 gallon covers 200 to 300 square feet per coat. Coverage will depend on surface porosity, joint width and application method. Second coat will take slightly less product.

8. Curing Information

Dry To Touch: 2 to 6 Hours (varies with conditions)

Recoat: 2 to 6 hours

Full Cure: 48 to 72 Hours

9. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Mix well the product before use.

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11. Shipping

Land & Sea: Not Regulated

Packing Group: III

Flash Point: >180F

12. Clean Up

Clean sprayer and tools with water and SurfaceLogix Cobble Clean immediately after use. Flush water through the line of the sprayer until clear.

13. Health Hazard Information

Eye Contact: Wear eye protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes. Do not rub eyes. Remove contact lenses if worn.

Inhalation: Use a NIOSH approved respirator.

Use with adequate ventilation.

Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.

Skin: Avoid prolonged contact with skin.

Wash hands immediately with water and soap if in contact with hands.

It is the sole responsibility of the applicator to determine whether a non-skid additive is appropriate for the job.

14. Technical Support

Test product in an inconspicuous area for adhesion and finish observation.

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

Test product in an inconspicuous area for adhesion and finish observation.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.