Poultice Part A

Deep Cleaning Solution



www.miraclesealants.com

Deep Cleaning Action For Most Surfaces Including:

- Sanded Grout
- Clay Pavers ■ Limestone
- Glazed Tile
- Brick ■ Non-sanded Grout
- Masonry
 - Quarry Tile ■ Ceramic Tile
- Marble ■ Stucco
- Concrete ■ Any Acid-Sensitive Natural Stone

Uses

- Kitchen Counters Kitchen Floors ■ Lobby Floors
 - Bathroom Floors
- Bathroom Showers ■ Porches & Patios

■ Terrazzo

■ Interior Walls ■ Exterior Walls ■ Monuments

Special Features

- Easy-to-Use ■ No Ácid
- Interior & Exterior Use
- Safe for All Polished Stone

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. Liquid Poultice is a unique two part formulation, (Bottle A & Bottle B), designed for deep cleaning all porous stone surfaces and grout. The percolating cleaning action of Liquid Poultice penetrates deep into the pores of the surface to safely lift out mold stains, mildew stains, algae stains, fungus stains, food grease, coffee, tea and other types of foreign matter from natural stone, grout, tile, concrete, stucco and masonry surfaces.

Liquid Poultice is a non-acidic cleaner that will not harm the polish on polished stone surfaces.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. User must determine suitability of the product for their intended use.

Protect Neighboring Surfaces

Always protect neighboring surfaces including masonry, wood, carpet, metal, landscaping and other non masonry surfaces.

APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using.

Thoroughly mix 1 part of Liquid Poultice (Bottle A) with 2 parts hot water. (Cold water can be used but cleaning action will be reduced). Add 1 part **Activator (Bottle B)** to the above mixture. Once the **Activator** is added, be sure to keep the mixture vented to prevent oxygen build up. Mix in an open container. Once Activator (Bottle B) has been added, the solution must be used within 72 hours.

Wet the surface to be cleaned with water lightly before starting. Apply Liquid Poultice with Mira Brush a clean mop, self-feeding floor machine or sprayer. Allow the solution to stand for a minimum of 45 minutes while agitating periodically with the appropriate scrub brush. DO NOT allow solution to dry on the surface. If surface starts to dry, add more **Liquid Poultice** Solution. Extract all the dirty remains with a wet vacuum system. Rinse the surface thoroughly with hot water and allow to dry. Difficult stains may require a second application. On wall surfaces a fine mist of **Liquid Poultice** maybe left to dry after initial cleaning is complete. Liquid Poultice will continue to pull dirt to the surface for up to 72 hours after completion. Allow to dry 24 - 72 hours before sealing the surface.

Heavy Duty Cleaning: To remove lime, hard water deposits, efflorescence, rust and other dirt and grime use **HDAC** or **Phosphoric Acid Cleaner** as directed.

Water, Stain & Slip Protection

To protect cleaned areas from future soiling, staining and increase static coefficient of friction. We recommend applying the appropriate Miracle Penetrating Sealer/Impregnator.

Color and Gloss Enhancement

For added color with "Textured and Non polished" surfaces, **511 Seal & Enhance** or **Mira Matte** may be used. For porous type "Pavers", **511 Seal & Enhance** may be used as directed.

Polish Enhancement

Periodically use Mira Dust, Mira Polish, Marble Conditioner or Granite **Brite** as directed.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application method. Used as directed, Liquid Poultice will cover approximately 500 - 1,000 square feet per gallon (45 - 93 square meters per 3.785 liters).

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide.** Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store Liquid Poultice (Bottle A) and Activator (Bottle B) upright in their original containers, properly sealed and unmixed. Stored at 77° F (25° C), **Liquid Poultice** will have a shelf life of 12 months. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT. 1-800-350-1901 • Fax: 1-626-443-1435 website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

Liquid Poultice is an alkaline liquid. Store in cool area. Only use this product in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Continue to ventilate until odors are completely eliminated. Avoid contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surfaces has thoroughly dried. Refer to the SDS for additional information.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.